

Flexible Screened CY PVC (YSLYCY) Multicore Control Cable

pro-POWER



RoHS
Compliant

Application

This flexible screened connecting cable is ideal for instrumentation and control equipment, for tooling machinery production lines and, in flexible applications for free movement without tensile load. Suitable for use in dry, moist and wet rooms. This cable is not used for outdoor or underground installation.

CY control cables are not suitable for fixed wiring applications requiring compliance with the regulations set out in BS7671.

Characteristics

Voltage Rating	: 300/500V
Test Voltage	: 4kV
Temperature Rating	: Fixed: -40°C to +80°C Flexed: -5°C to +70°C
Minimum Bending Radius	: Fixed: 4 × overall diameter Flexed: 12.5 × overall diameter

Cable Standards

VDE 0207-363-3, VDE 0285-525-2-51, VDE 0285-525-1, VDE 0285-525-2-11, VDE 0482-332-1-2, VDE 819-102 (TM54)
Flame Retardant according to IEC 60332-1-2



UK Laboratory Tested

This product is subject to the Quality Assurance protocols of The Cable Lab®, a UKAS accredited ISO 17025 cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



Regulatory Compliance

This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



Construction

Conductor

Class 5 flexible plain copper wires

Insulation

PVC (Polyvinyl Chloride)

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER

Flexible Screened CY PVC (YSLYCY) Multicore Control Cable

pro-POWER

Separator

PET (Polyester Tape)

Screen

TCWB (Tinned Copper Wire Braid)

Sheath

PVC (Polyvinyl Chloride)

Core Identification

Black with white number

From 3 cores: Black with white number + Green/Yellow

Sheath Colour

Grey

Dimensions

Part Number	No. of Cores	Nominal Cross Sectional Area mm ²	Nominal Thickness of Insulation mm	Nominal Thickness of Sheath mm	Nominal Overall Diameter mm	Nominal Weight kg/km
PP001555	2	0.5	0.4	0.6	5	35
PP001556	2	0.75	0.4	0.6	5.5	45
PP001557	2	1	0.4	0.7	6.1	56
PP001558	3	0.5	0.4	0.6	5.4	48
PP001559	3	0.75	0.4	0.7	6	61
PP001560	3	1	0.4	0.7	6.4	71
PP001561	3	1.5	0.4	0.7	7.1	90
PP001562	3	2.5	0.5	0.8	8.6	136
PP001563	4	0.5	0.4	0.7	6	61
PP001564	4	0.75	0.4	0.7	6.5	75
PP001565	4	1	0.4	0.7	7	89
PP001566	4	1.5	0.4	0.7	7.7	114
PP001567	4	2.5	0.5	0.8	9.4	173
PP001568	5	0.5	0.4	0.7	6.5	73
PP001569	5	0.75	0.4	0.7	7	89
PP001570	5	1	0.4	0.7	7.6	107
PP001571	5	1.5	0.4	0.8	8.6	142
PP001572	5	2.5	0.5	0.9	10.4	216
PP001573	7	0.5	0.4	0.7	7	89
PP001574	7	0.75	0.4	0.7	7.6	112
PP001575	7	1	0.4	0.8	8.4	139
PP001576	7	1.5	0.4	0.8	9.3	180
PP001577	7	2.5	0.5	1	11.5	283

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER

Flexible Screened CY PVC (YSLYCY) Multicore Control Cable



Part Number	No. of Cores	Nominal Cross Sectional Area mm ²	Nominal Thickness of Insulation mm	Nominal Thickness of Sheath mm	Nominal Overall Diameter mm	Nominal Weight kg/km
PP001551	12	0.5	0.4	0.8	9.2	143
PP001552	12	0.75	0.4	0.8	10	181
PP001553	12	1	0.4	1	11.2	230
PP001554	12	1.5	0.4	1.1	12.7	307

Electrical Characteristics

Nominal Cross Sectional Area mm ²	Current Carrying Capacities 30°C Continuous Loading A	Maximum Resistance of Conductor at 20°C Ω/km
0.5	9	39
0.75	12	26
1	15	19.5
1.5	18	13.3
2.5	26	7.98

Part Number Table

Description	No. of Cores	Nominal Cross Sectional Area mm ²	Reel Length	Part Number
Flexible Screened CY PVC (YSLYCY) Multicore Control Cable	2	0.5	50m	PP001555
	2	0.75		PP001556
	2	1		PP001557
	3	0.5		PP001558
	3	0.75		PP001559
	3	1		PP001560
	3	1.5		PP001561
	3	2.5		PP001562
	4	0.5		PP001563
	4	0.75		PP001564
	4	1		PP001565
	4	1.5		PP001566
	4	2.5		PP001567
	5	0.5		PP001568
	5	0.75		PP001569

Flexible Screened CY PVC (YSLYCY) Multicore Control Cable



Description	No. of Cores	Nominal Cross Sectional Area mm ²	Reel Length	Part Number
Flexible Screened CY PVC (YSLYCY) Multicore Control Cable	5	1	50m	PP001570
	5	1.5		PP001571
	5	2.5		PP001572
	7	0.5		PP001573
	7	0.75		PP001574
	7	1		PP001575
	7	1.5		PP001576
	7	2.5		PP001577
	12	0.5		PP001551
	12	0.75		PP001552
	12	1		PP001553
	12	1.5		PP001554

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell Limited 2016.

X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)