

# Flexible YY PVC (YSLY) Multicore Control Cable

pro-POWER

RoHS  
Compliant



## Application

This flexible YY multicore control cable for instrumentation and control equipment, for tooling machinery production lines, and in flexible applications for free movement without tensile load. Suitable for dry, ambient, wet places. These indoor cables are not used for external or underground installation.

YY control cables are not suitable for fixed wiring applications requiring compliance with the regulations set out in BS7671.

## Characteristics

Voltage Rating	: 300/500V
Test Voltage	: 4kV
Temperature Rating	: Fixed: -40°C to +80°C Flexed: -5°C to +70°C
Minimum Bending Radius	: Fixed: 4 × overall diameter Flexed: 12.5 × overall diameter

## Cable Standards

VDE 0207-363-3, VDE 0285-525-2-51, VDE 0285-525-1, VDE 0285-525-2-11, VDE 0482-332-1-2, VDE 819-102 (TM54)  
Flame Retardant according to IEC 60332-1-2



## UK Laboratory Tested

This product is subject to the Quality Assurance protocols of The Cable Lab®, a UKAS accredited ISO 17025 cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



## Regulatory Compliance

This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab® as meeting the requirements of the BSI RoHS Trusted Kitemark™.



## Construction

### Conductor

Class 5 flexible plain copper wires

### Insulation

PVC (Polyvinyl Chloride)

www.element14.com  
www.farnell.com  
www.newark.com  
www.cpc.co.uk

pro-POWER

# Flexible YY PVC (YSLY) Multicore Control Cable

pro-POWER

## Sheath

PVC (Polyvinyl Chloride)

## Core Identification

Black with white number

From 3 cores: Black with white number + Green/Yellow

## Sheath Colour

Grey

## Dimensions

Part Number	No. of Cores	Nominal Cross Sectional Area mm <sup>2</sup>	Nominal Thickness of Insulation mm	Nominal Thickness of Sheath mm	Nominal Overall Diameter mm	Nominal Weight kg/km
PP001620	2	0.5	0.4	0.7	4.8	36
PP001621	2	0.75	0.4	0.7	5.2	46
PP001622	2	1	0.4	0.7	5.6	56
PP001623	2	1.5	0.4	0.8	6.4	73
PP001624	2	2.5	0.5	0.9	7.6	113
PP001625	3	0.5	0.4	0.7	5.1	44
PP001626	3	0.75	0.4	0.7	5.5	55
PP001627	3	1	0.4	0.8	6.1	69
PP001628	3	1.5	0.4	0.8	6.8	91
PP001629	3	2.5	0.5	0.9	8.3	140
PP001630	3	4	0.6	1	10	210
PP001631	3	6	0.65	1.1	11.5	293
PP001632	4	0.5	0.4	0.7	5.5	54
PP001633	4	0.75	0.4	0.8	6.2	70
PP001634	4	1	0.4	0.8	6.7	85
PP001635	4	1.5	0.4	0.9	7.6	116
PP001636	4	2.5	0.5	1	9.3	179
PP001637	4	4	0.6	1.1	11.2	269
PP001638	4	6	0.65	1.2	12.8	374
PP001639	5	0.75	0.4	0.8	6.7	83
PP001640	5	1	0.4	0.9	7.5	104
PP001641	5	1.5	0.4	0.9	8.3	136
PP001642	5	2.5	0.5	1.1	10.3	213
PP001643	5	4	0.6	1.2	12.4	321
PP001644	5	6	0.65	1.3	14.3	447
PP001645	7	0.75	0.4	0.9	7.5	108
PP001646	7	1	0.4	0.9	8.1	130

www.element14.com  
www.farnell.com  
www.newark.com  
www.cpc.co.uk

pro-POWER

# Flexible YY PVC (YSLY) Multicore Control Cable



Part Number	No. of Cores	Nominal Cross Sectional Area mm <sup>2</sup>	Nominal Thickness of Insulation mm	Nominal Thickness of Sheath mm	Nominal Overall Diameter mm	Nominal Weight kg/km
PP001647	7	1.5	0.4	1	9.2	177
PP001648	7	2.5	0.5	1.1	11.2	277
PP001609	8	0.75	0.4	0.9	8.1	120
PP001610	8	1	0.4	1	9	150
PP001611	8	1.5	0.4	1	10	200
PP001612	12	0.5	0.4	1	9.1	139
PP001613	12	0.75	0.4	1	9.9	179
PP001614	12	1	0.4	1.1	10.9	225
PP001615	12	1.5	0.4	1.2	12.4	302
PP001616	18	0.5	0.4	1.1	10.7	201
PP001617	18	0.75	0.4	1.2	11.9	230
PP001618	18	1	0.4	1.2	12.9	324
PP001619	18	1.5	0.4	1.4	14.8	446

## Electrical Characteristics

Nominal Cross Sectional Area mm <sup>2</sup>	Current Carrying Capacities 30°C Continuous Loading	Maximum Resistance of Conductor at 20°C
	A	Ω/km
0.5	9	39
0.75	12	26
1	15	19.5
1.5	18	13.3
2.5	26	7.98
4	34	4.95
6	44	3.3

## Part Number Table

Description	No. of Cores	Nominal Cross Sectional Area mm <sup>2</sup>	Reel Length	Part Number
Flexible YY PVC (YSLY) Multicore Control Cable	2	0.5	50m	PP001620
	2	0.75		PP001621
	2	1		PP001622
	2	1.5		PP001623
	2	2.5		PP001624
	3	0.5		PP001625
	3	0.75		PP001626
	3	1		PP001627

# Flexible YY PVC (YSLY) Multicore Control Cable



Description	No. of Cores	Nominal Cross Sectional Area mm <sup>2</sup>	Reel Length	Part Number
Flexible YY PVC (YSLY) Multicore Control Cable	3	1.5	50m	PP001628
	3	2.5		PP001629
	3	4		PP001630
	3	6		PP001631
	4	0.5		PP001632
	4	0.75		PP001633
	4	1		PP001634
	4	1.5		PP001635
	4	2.5		PP001636
	4	4		PP001637
	4	6		PP001638
	5	0.75		PP001639
	5	1		PP001640
	5	1.5		PP001641
	5	2.5		PP001642
	5	4		PP001643
	5	6		PP001644
	7	0.75		PP001645
	7	1		PP001646
	7	1.5		PP001647
	7	2.5		PP001648
	8	0.75		PP001609
	8	1		PP001610
	8	1.5		PP001611
	12	0.5		PP001612
	12	0.75		PP001613
	12	1		PP001614
	12	1.5		PP001615
	18	0.5		PP001616
	18	0.75		PP001617
18	1	PP001618		
18	1.5	PP001619		

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell Limited 2016.

# X-ON Electronics

Authorized Distributor

*Click to view similar products for [Pro Power manufacturer](#).*

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)