

6	2.54 mm	3.81 mm	62200621821
8	3.81 mm	5.08 mm	62200821821
10	5.08 mm	6.35 mm	62201021821
12	6.35 mm	7.62 mm	62201221821
14	7.62 mm	8.89 mm	62201421821
16	8.89 mm	10.16 mm	62201621821
20	11.43 mm	12.70 mm	62202021821
28	16.51 mm	17.78 mm	62202821821
30	17.78 mm	19.05 mm	62203021821
40	24.13 mm	25.40 mm	62204021821
50	30.48 mm	31.75 mm	62205021821
60	36.83 mm	38.10 mm	62206021821

Kind Properties:

Properties		Value	Unit			
Standard Polarities ¹⁾		04;08;10;14;16;20;28				
Pitch	Р	1.27	mm			
Quality Class		3 as per CECC 75 301-802				
Rows		Dual				
Gender		Female				

deneral Frupernes.

•	
Operating Temperature	-40 °C up to +105 °C
Compliance	Lead free / RoHS

Electrical Properties:

Properties	Test conditions		Value
Rated Current		I _R	1
Working Voltage			100
Withstanding Voltage	1 min		500
Contact Resistance		R	20
Insulation Resistance		R _{ISO}	1000

Standard:

UL Approval	E323964

Packaging Properties:

m	Packaging	Tube
	Packaging Unit (Qty.)	62
_		


¹⁾ Delivery ex stock for standard polarities, non standard have extended leadtimes and MOQ

Material Properties:

Insulator Material	PA9T
Insulator Flammability Rating	UL94 V-0
Insulator Color	Black
Contact Material	Copper Alloy

Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions		CREATED DaMa	CHECKED GM		GENERAL TOLERANCE DIN ISO 2768-1m		PROJECTION METHOD	÷
Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0		DESCRIPTION						
www.we-online.com eiSos@we-online.com	Header W	K-PHD			ORDER CODE	42182	21	
		1 1	evision 02.000	status Valid		DATE (YYYY-MM-DE 2017-07-03	·	BUSINESS UN eiCan

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. More a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. More a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. More a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use a fortient reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use a fortient reliability standard is especially adverning such uses the parties have executed an agreement specifically governing such uses the parties have executed an agreement specifically governing such uses the parties have executed an agreement specifically governing such uses the parties have executed an agreement specifically governing such uses the parties have executed an agreement specifically governing such uses the parties have executed an agreement specifically governing such uses the parties have executed an agreement specifically governing such uses the parties have executed an agreement specifically governing such uses the parties have executed an agreement specifically governing such uses the parties



Preheat Temperature Typical	T _{s typical}	120 °C	120 °C
Preheat Temperature Max	T _{s max}	130 °C	130 °C
Preheat Time $\rm t_s$ from $\rm T_{s\ min}$ to $\rm T_{s\ max}$	t _s	70 seconds	70 seconds
Ramp-up Rate		150 °C max.	150 °C max.
Peak temperature	Tp	250 °C - 260 °C	235 °C - 260 °C
Time of actual peak temperature	tp	max. 10 seconds max. 5 seconds each wave	max. 10 seconds max. 5 seconds each
Ramp-down Rate, Min		~ 2 K/ second	~ 2 K/ second
Ramp-down Rate, Typical		~ 3.5 K/ second	~ 3.5 K/ second
Ramp-down Rate, Max		~ 5 K/ second	~ 5 K/ second
Time 25°C to 25°C		4 minutes	4 minutes

¹⁾ refer to EN61760-1:2006 refer to EN61760-1:2006

Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions	CREATED OHECKED GENERAL TOLEPANCE DaMa GM DIN ISO 2768-1m					PROJECTION METHOD	÷
Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0	1.27mm THT Straight Dual Socket					I	
www.we-online.com eiSos@we-online.com	Header W	/R-PHD	-		ORDER CODE	42182	21
		revision 002.000	status Valid		DATE (YYYY-MM-DE 2017-07-03	·	BUSINESS UN eiCan

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. More & Co KG products are neither designed and the vision control, stantanto, reliability standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. More a control, transportation (automative control, transportation (gluonotive control, transportation signal, disaster prevention, medical, public information network etc... Wurth Elektronic component which is used in leachtraic inclusion to performance.

General:

- This electronic component is designed and developed with the intention for use in general electronics equipment.
- Before incorporating the components into any equipment in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.
- In addition, even electronic component in general electronic equipment, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed by the user before usage.
- The connector is designed and manufactured to be used within the datasheet specified values.
- Do not use the connector outside the datasheet specifications
- Prevent any damage or scratches on the connector, especially on the actuator.
- Direct mechanical impact to the product shall be prevented (e.g overlapping of the PCB's).
- The responsibility for the applicability of the customer specific products and use in a particular customer design is always within the authority of the customer. All technical specification for standard products do also apply to customer specific products.
- The Connectors are designed to be used along with Würth Elektronik counterparts and tools. Würth Elektronik cannot insure the
 reliability of these components while being used with other products.

Product Specific:

Soldering:

- The solder profile must comply with the WE technical soldering specification, otherwise this will void the warranty.
- Other soldering methods are not verified and have to be validated by the customer at his own risk.

Cleaning and Washing:

- Parts are not constructed for washing, so washing can cause malfunction afterwards.
- Cleaning agent that are used to clean the customer applications might damage or change the characteristics of the component, body, pins and termination.
- Please do not submerse our washable products into water or cleaning agents or put them in locations exposed to water completely.
- When cleaning by hand (brushing), please do not use excessive force on our connectors to avoid malfunction afterwards, because customer could deform function relevant areas.
- We recommended a solution without organic acid (preserve the plating against corrosion) volatile, without residues and compatible with the plastic.

sensivity but all products shall be used before the end of the period of 12 months based on the products date code solderability can't be warranted.

Handling:

- Do not repeatedly operate the connector with excessive force. It may damage or deforms the contact dome which it
- In the case a product requires particular handling precautions, in addition to the general recommendations mentior will appear on the product datasheet.

Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions	CREATED DaMa	CHECKED GM		GENERAL TOLERANCE DIN ISO 2768-1m		PROJECTION METHOD	÷
Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com elSos@we-online.com	1.27mm 1 Header W		ight D	ual Socket	ORDER CODE 62201	42182	21
		evision 102.000	status Valid		DATE (YYYY-MM-DE 2017-07-03	·	BUSINESS UNI eiCan

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Morec & Co K products are neither designed on intended for use in areas such as military, aerospace, eviation, nuclear control, stransportation (automotive control, transportation signal, disaster prevention, medical, public information tectors or performance.

1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications

It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications. In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component. Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at www.we-online.com.

3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty.

4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter.

5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected.

available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the availability expectancy before or when the product for application design-in disposal is considered. The approach name apply in the case of individual agreements deviating from the foregoing for customer-specific products.

7. Property Rights

All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, develor well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will Elektronik eiSos GmbH & Co. KG does not warrant or represent that any licens implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Elektronik eiSos Group", last version available at www.we-online.com.

Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions		CREATED DaMa	CHECKED GM		GENERAL TOLERANCE DIN ISO 2768-1 m		PROJECTION METHOD	÷
Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0		1.27mm THT Straight Dual Socket						
www.we-online.com eiSos@we-online.com	Header V	/R-PHD	-		ORDER CODE	42182	21	
			REVISION 002.000	status Valid		DATE (YYYY-MM-DE 2017-07-03	·	BUSINESS UT eiCan

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is not authorized tor use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. More & Co K6 products are neither designed nor intended for use in areas such as military, aerospace, availation, nuclear ontolito, stainarine, transportation signal, disaster prevention, medical, public information network etc.. Worth Elektronik eSos 6mbH & Co K6 must be informed about the intent of such usage before the design-in stage. In addition, sufficient relia

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for wurth manufacturer:

Other Similar products are found below :

 687001
 742700
 74270062
 74437349220
 744741101
 750314624
 750341638
 31402
 686626050001
 744741471
 744772681
 744777

 749119950
 750312504
 890334025009
 IC-744885
 875115350002
 865230143004
 860160275030
 600690282801
 178050601
 615008138221

 750311898
 744999
 7446823003
 7446323004
 744028
 66201621822
 7446221012
 744720
 760895431
 760895651
 662006236022

 64900621822
 418117270910
 890334026014
 744839208072
 744762A/RFI
 74651174R
 744838180160
 750310346
 861011384014

 750817018
 3020903
 885342
 2603019321001
 2603019021001
 2606039021001
 2608019324001
 2607019213001