

General tolerance 0,05

Pattern Properties:

Properties		Value
Pin to Pin (Middle)	p _l	8.89

Article Properties:

Properties		Value	Unit
Pins		16	
Pin to Pin (Middle)	P_{l}	8.89	mm
Length	L	10.56	mm

GENERAL TOLERANCE Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions DaMa GM DIN ISO 2768-1m Max-Eyth-Str. 1 74638 Waldenburg 1.27mm SMT Straight Dual Socket Germany Tel. +49 (0) 79 42 945 - 0 **Header WR-PHD** www.we-online.com 62331621021 eiSos@we-online.com DATE (YYYY-MM-DD) BUSINESS UN STATUS 002.000 Valid 2017-07-03 WÜRTH ELEKTRONIK

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreo & Co KG products are neither designed nor intended for use in areas such as a military, aerospace, existion, nuclear control, strain control, train control, train control, ship control, ship control, train control, ship control, trai

8	3.81 mm	5.48 mm	62330821021
10	5.08 mm	6.75 mm	62331021021
12	6.35 mm	8.02 mm	62331221021
14	7.62 mm	9.29 mm	62331421021
16	8.89 mm	10.56 mm	62331621021
18	10.16 mm	11.83 mm	62331821021
20	11.43 mm	13.10 mm	62332021021
22	12.70 mm	14.37 mm	62332221021
24	13.97 mm	15.64 mm	62332421021
26	15.24 mm	16.91 mm	62332621021
28	16.51 mm	18.18 mm	62332821021
40	24.13 mm	25.80 mm	62334021021
50	30.48 mm	32.15 mm	62335021021
60	36.83 mm	38.50 mm	62336021021

Kind Properties:

Properties		Value			
Standard Polarities 1)		04;08;10;14;16;20;28			
Pitch	Р	P 1.27			
Quality Class		3 as per CECC 75 301-802			
Rows		Dual			
Gender		Female			
Coplanarity		100			

¹⁾ Delivery ex stock for standard polarities, non standard have extended leadtimes and MOQ

	Insulator Color	Black
	Contact Material	Copper Alloy
	Contact Plating	Gold
	Contact Type	Stamped

General Properties:

Operating Temperature	-40 °C up to +105 °C
Compliance	Lead free / RoHS

Electrical Properties:

Properties	Test conditions		Value
Rated Current		I _R	1
Working Voltage			100
Withstanding Voltage	1 min		500
Contact Resistance		R	20
Insulation Resistance		R _{ISO}	1000

Standard:


III Approval	F000004
UL Approval	E323964

Packaging Properties:

Packaging	Tape and Reel with Pad
Packaging Unit (Qty.)	900

GENERAL TOLERANCE CHECKED Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions DaMa GM DIN ISO 2768-1m Max-Eyth-Str. 1 74638 Waldenburg 1.27mm SMT Straight Dual Socket Germany Tel. +49 (0) 79 42 945 - 0 **Header WR-PHD** www.we-online.com 62331621021 eiSos@we-online.com DATE (YYYY-MM-DD) BUSINESS UN REVISION STATUS 002.000 Valid 2017-07-03 WÜRTH ELEKTRONIK

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreo & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control), transportation signal, disaster prevention, medical, public information network etc.. Worth Elektronik elSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability functions or performance.




Ī	Preheat Temperature Max	T _{s max}	200 °C
	Preheat Time t_s from $T_{s min}$ to $T_{s max}$	t _s	60 - 120 seconds
	Ramp-up Rate (T _L to T _P)		3 °C/ second max.
	Liquidous Temperature	T _L	217 °C
	Time t _L maintained above T _L		60 - 150 seconds
	Peak package body temperature	T _p	see table
	Time within 5°C of actual peak temperaure Ramp-down Rate (T _L to T _P)		20 - 30 seconds
			6 °C/ second max.
	Time 25°C to peak temperature		8 minutes max.

¹⁾ refer to IPC/JEDEC J-STD-020D refer to IPC/ JEDEC J-STD-020E

Package Classification Reflow Temperature:

Properties	Volume mm³ <350	Volume mm ³ 350-2000	V >
PB-Free Assembly I Package Thickness < 1.6 mm ¹⁾	260 °C	260 °C	2
PB-Free Assembly Package Thickness 1.6 mm - 2.5 mm	260 °C	250 °C	2
PB-Free Assembly Package Thickness ≥ 2.5 mm	250 °C	245 °C	2

1) refer to IPC/JEDEC J-STD-020D refer to IPC/ JEDEC J-STD-020E



This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreo & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control), transportation signal, disaster prevention, medical, public information network etc.. Worth Elektronik elSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability functions or performance.

General:

- This electronic component is designed and developed with the intention for use in general electronics equipment.
- Before incorporating the components into any equipment in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.
- In addition, even electronic component in general electronic equipment, when used in electrical circuits that require high safety,
 reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed by the user before usage.
- The connector is designed and manufactured to be used within the datasheet specified values.
- Do not use the connector outside the datasheet specifications.
- Prevent any damage or scratches on the connector, especially on the actuator.
- Direct mechanical impact to the product shall be prevented (e.g overlapping of the PCB's).
- The responsibility for the applicability of the customer specific products and use in a particular customer design is always within the authority of the customer. All technical specification for standard products do also apply to customer specific products.
- The Connectors are designed to be used along with Würth Elektronik counterparts and tools. Würth Elektronik cannot insure the
 reliability of these components while being used with other products.

Product Specific:

Soldering:

- The solder profile must comply with the WE technical soldering specification, otherwise this will void the warranty.
- Other soldering methods are not verified and have to be validated by the customer at his own risk.

Cleaning and Washing:

- Parts are not constructed for washing, so washing can cause malfunction afterwards.
- Cleaning agent that are used to clean the customer applications might damage or change the characteristics of the component, body, pins and termination
- Please do not submerse our washable products into water or cleaning agents or put them in locations exposed to water completely.
- When cleaning by hand (brushing), please do not use excessive force on our connectors to avoid malfunction afterwards, because customer could deform function relevant areas.
- We recommended a solution without organic acid (preserve the plating against corrosion) volatile, without residues and compatible with the plastic.

sensivity but all products shall be used before the end of the period of 12 months based on the products date code solderability can't be warranted.

Handling:

- Do not repeatedly operate the connector with excessive force. It may damage or deforms the contact dome which it
- In the case a product requires particular handling precautions, in addition to the general recommendations mention
 will appear on the product datasheet.

Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions		CREATED CHECKED GENERAL TOLERANCE DAMA GM DIN ISO 2768-1m					PROJECTION METHOD	+
Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0				aight [Dual Socket			
www.we-online.com eiSos@we-online.com		Header V	VR-PHD			62331	62102	21
	WÜRTH ELEKTRONIK	1	REVISION 002.000	status Valid		DATE (YYYY-MM-D 2017-07-03	,	BUSINESS UNI eiCan

This electronic component has been designed and developed for usage in general electronic equipment only. This product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreo & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Wiirth Elektronik eiSos GmibH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliaments that require high safety and reliability functions or performance.

1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications

It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications. In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component. Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at www.we-online.com.

3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty

4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter.

5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected.

available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the availability expectancy before or when the product for application design-in disposal is considered. The approach name apply in the case of individual agreements deviating from the foregoing for customer-specific products.

7. Property Rights

All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, develor well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will Elektronik eiSos GmbH & Co. KG does not warrant or represent that any licens implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Elektronik eiSos Group", last version available at www.we-online.com.

Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions		DaMa	GM		GENERAL TOLERANCE DIN ISO 2768-1m		PROJECTION METHOD	+
Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0	1.27mm SMT Straight Dual Socket							
www.we-online.com eiSos@we-online.com		Header WR-PHD				62331621021		
	WÜRTH ELEKTRONIK	1	REVISION 002.000	status Valid		DATE (YYYY-MM-DI 2017-07-03	· .	BUSINESS UNF eiCan

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreo & Co Kg products are neither designed nor intended for use in areas such as military, aerospace, avaidon, nuclear control, shap control, sh

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for wurth manufacturer:

Other Similar products are found below:

687001 742700 74270062 74437349220 744741101 750314624 750341638 31402 686626050001 744741471 744772681 744777

749119950 750312504 890334025009 IC-744885 875115350002 865230143004 860160275030 600690282801 178050601 615008138221

750311898 744999 7446823003 7446323004 744028 66201621822 7446221012 744720 760895431 760895651 662006236022

64900621822 418117270910 890334026014 744839208072 744762A/RFI 74651174R 744838180160 750310346 861011384014

750817018 3020903 885342 2603019321001 2603019021001 2606039021001 2608019324001 2607019213001