



MMD-TA-11B

▶ MUTING SAFETY RELAYS



MMD-TA-11B MUTING MODULE DIN MOUNT RELAY
OUTPUTS 24V

Part Number: 75090

CERTIFICATIONS



SPECIFICATIONS

Primary Housing Material	Polycarbonate
Contacts	AgNi (gold-flash)
Safety Input - Dual Channel (Dry Contact)	10-50 mA @ 15-30 V dc
Safety Input - Reset	10-50 mA @ 15-30 V dc
Design Rating	Cat. 4; PL e; SIL 3
Dimension (H x W x D in mm)	84 x 67.5 x 118
Electrical Life (Cycles @ VA)	120,000 @ 1380 VA
IP Rating	IP20
Max Operating Temperature (°C)	50
NEMA Rating	NEMA 1
Relative Humidity	95% @ 50° C
Input Operation	Simultaneous within 3.0 s

Input Resistance	250 Ω max. per channel
Output Configuration	2 NO (6 A); 1 NC (6 A)
Mechanical Life (Operations in Millions)	50
Pollution Degree	2
Power Consumption	300 mA
Response Time (ms)	20 (max.)
Supply Protection	Short circuit protected to +24 V dc and dc common
Supply Voltage	24 V dc +/- 15%
Terminal Type	Removable
Vibration	10-55 Hz at 0.35 mm
Muting	Yes



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [banner manufacturer](#):

Other Similar products are found below :

[Q45VR2FPQ](#) [BTA23S](#) [RS-11](#) [L16F](#) [2LM3](#) [2PBA](#) [LM8-1](#) [LMT](#) [SM312CV](#) [SM31RQD](#) [LS4ELQ](#) [FX1](#) [Q45BB6LLQ](#) [QM42VP6AFV150Q](#)
[D12SP6FP](#) [MBCC-412](#) [BA23S](#) [BT21S](#) [BTA13S](#) [LM4-2](#) [QS18VN6LP](#) [ES-FA-6G](#) [T183E](#) [SLSP30-600Q88](#) [SLSP30-1200Q88](#)
[OTBVN6QD](#) [OPBA5](#) [PBAT](#) [SBLV1](#) [SMA91EQD](#) [SMA91E](#) [SMA912LVQD](#) [SMA912DQD](#) [SM2A312CVQD](#) [SM2A912LVQD](#)
[SM312FP1H](#) [SM31RL](#) [TL70RAQ](#) [TL70RQ](#) [K50LGRYPQ](#) [BRT-THG-4X4-5](#) [T18-2VNDL-Q8](#) [SLLP14-1190P88](#) [SME312DQD](#)
[SM312CUQD](#) [BR-2](#) [BR23P](#) [SM2A312FPQD](#) [SM2A312LVQD](#) [SM31EQD](#)