



K50BCLR2A120Q-39906

▶ PRODUCTS FOR INDUSTRIAL AUTOMATION



K50 Beacon EZ-LIGHT: 1-Color Perimeter & Top View

Mode: Flash Only 1.6Hz Voltage: 85-130 V ac

Housing: Polycarbonate IP69K Colors: Red

Micro 3-pin Quick Disconnect

Part Number: 39906

SPECIFICATIONS

Housing Style	Base Mount - Dome Window
Primary Housing Material	Polycarbonate
Indication	Yes
Mounting Thread	30 mm
Color Option 1/Job Light	Red
Current - Color (mA)	60
Connection Type	Integral QD
Number of Pins/Conductors	3
Supply Voltage	85-130 V ac
Max Input Response Time (ms)	1
Size/Length (mm)	50
Environmental Rating	IP69K

Max Op. Relative Humidity Non-Condensing (%)	95% @ 50°C
Max Op. Temperature (°C)	50
Min Op. Temperature (°C)	-40
Primary Window Material	Polycarbonate
Vibration and Mechanical Shock	Meets Mil. Std. 202F requirements method 201A. Also meets IEC 947-5-2; 30G 11 ms duration, half sine wave.
Feature: Washdown Rated	Yes
Feature: Audible	No
Feature: Chemical Resistant	No
Modbus RTU	No



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [banner manufacturer](#):

Other Similar products are found below :

[Q45VR2FPQ](#) [BTA23S](#) [RS-11](#) [L16F](#) [2LM3](#) [2PBA](#) [LM8-1](#) [LMT](#) [SM312CV](#) [SM31RQD](#) [LS4ELQ](#) [FX1](#) [Q45BB6LLQ](#) [QM42VP6AFV150Q](#)
[D12SP6FP](#) [MBCC-412](#) [BA23S](#) [BT21S](#) [BTA13S](#) [LM4-2](#) [QS18VN6LP](#) [ES-FA-6G](#) [T183E](#) [SLSP30-600Q88](#) [SLSP30-1200Q88](#)
[OTBVN6QD](#) [OPBA5](#) [PBAT](#) [SBLV1](#) [SMA91EQD](#) [SMA91E](#) [SMA912LVQD](#) [SMA912DQD](#) [SM2A312CVQD](#) [SM2A912LVQD](#)
[SM312FP1H](#) [SM31RL](#) [TL70RAQ](#) [TL70RQ](#) [K50LGRYPQ](#) [BRT-THG-4X4-5](#) [T18-2VNDL-Q8](#) [SLLP14-1190P88](#) [SME312DQD](#)
[SM312CUQD](#) [BR-2](#) [BR23P](#) [SM2A312FPQD](#) [SM2A312LVQD](#) [SM31EQD](#)