


## Plug SLS4...-L

In-line, Ø 4 mm, with spring-loaded MULTILAM for self-assembly of test leads.

Soft insulator.

**Solder connection.**



Assembly instructions MA116

[www.staubli.com/electrical](http://www.staubli.com/electrical)

Order No.	Type	Rated voltage/current	Cable (A)		*Colors												
22.2646-*	SLS410-L	30 VAC / 19 A 60 VDC / 19 A	Ø 3.0 mm	1.0 mm <sup>2</sup>	<table border="1"> <tr> <td>Au</td> <td>21</td> <td>22</td> <td>23</td> <td>24</td> <td>25</td> </tr> <tr> <td></td> <td>26</td> <td>27</td> <td>28</td> <td>29</td> <td></td> </tr> </table>	Au	21	22	23	24	25		26	27	28	29	
Au	21	22	23	24	25												
	26	27	28	29													

### Component parts

22.2170-*	KT410-L	Insulator for SLS410-L
22.1011	LS410-L	Plug for SLS410-L

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [staubli](#) manufacturer:*

Other Similar products are found below :

[23.3070-21,+ -22,+ -23,+ -24,+ -25](#) [61.7607-21 25M](#) [66.9706-21](#) [63.9358-22](#) [28.0127-10027](#) [49.0126-05023](#) [49.0126-20024](#) [28.0124-20029](#)  
[22.2633-23](#) [23.3020-28](#) [66.9407-05028](#) [49.7049-24](#) [60.7008-999-21](#) [61.7664-999-23](#) [61.7612-100-22](#) [14.0034-29](#) [23.0440-21](#) [28.0116-05022](#) [28.0116-05023](#) [24.0224-21](#) [65.9098-21](#) [64.9214-2122](#) [23.3060-24](#) [67.9799-22](#) [61.7607-29 25M](#) [23.3120-28](#) [49.0126-05024](#) [49.0126-05025](#) [49.0079-05023](#) [66.9392-15022](#) [66.9407-05027](#) [66.9408-10028](#) [67.9770-100-21](#) [22.1027 & 22.2380-23](#) [61.7611-100-33](#) [60.7018-100-21](#) [28.0116-20022](#) [28.0125-02522](#) [66.9328-25](#) [65.3314-21,+ -22,+ -23,+ -24,+ -25,+ -29](#) [22.3006-21](#) [28.0055-05024](#) [23.3120-20](#) [49.0126-02525](#) [28.0126-05024](#) [28.0126-20020](#) [28.0124-05020](#) [28.0125-05021](#) [28.0125-20023](#) [22.2656-25](#)