### OC25G02PNBN00NUH1



#### **General Information**

Extended Product Type: OC25G02PNBN00NUH1 Product ID: 1SCA134811R1001

EAN: 6417019635613

**Catalog Description:** OC25G02PNBN00NUH1 Cam switch

OC25 Cam switch, Ith=25A, Change-Over, 2-contacts, Snap-on door mounting, Black Basic Long Description:

handle. Black handle and frontplate with standard text are included. Special engraved

frontplates to be ordered as separate items.

#### Categories

Products » Low Voltage Products and Systems » Switches » Cam Switches

**Ordering** 

**Minimum Order Quantity:** 1 piece **Customs Tariff Number:** 85365080

**Popular Downloads** 

**Data Sheet, Technical Information:** 1SCC302009C0201 Wiring Diagram: 1SCC302014M0201

**Dimensions** 

**Product Net Width:** 51 mm **Product Net Height:** 51 mm **Product Net Depth:** 83 mm **Product Net Weight:** 0.09 kg

**Technical** 

Rated Operational Current AC-22A (500 V) 20 A

(690 V) 20 A (l<sub>e</sub>):

Rated Operational Current AC-23A

(l<sub>e</sub>):

(500 V) Three Phase 8.1 A (230 V) Three Phase 15 A (400 V) Three Phase 15 A

(690 V) Three Phase 5.9 A

Rated Operational Power AC-23A

(P<sub>e</sub>):

(690 V) Three Phase 4.8 kW (500 V) Three Phase 4.8 kW (230 V) Three Phase 2.6 kW (400 V) Three Phase 7.5 kW

Conventional Free-air Thermal

Current (Ith):

q = 40 °C 25 A

Conventional Thermal Current (Ithe): Fully Enclosed 25 A

Rated Continuous Thermal Current: 25 A Rated Impulse Withstand Voltage 4 kV

(U<sub>imp</sub>):

690 V Rated Insulation Voltage (Ui): Rated Operational Voltage: 690 V

Rated Short-time Withstand Current for 1 s 0.3 kiloampere rms

(I<sub>cw</sub>):

Power Loss: 1.8 W **Pollution Degree:** 3

Handle Type: Basic handle

**Special Functions:** Change-over switch: With 0-position: 12 o' clock, step angle 60°, front plate

HAND-OFF-AUTO

Color: Black

Mounting Type: Snap-on door mounting

**Number of Contacts:** 2 **Number of Poles:** 

**Terminal Type:** Screw Terminals

**Technical UL/CSA** 

Ampere Rating UL/CSA: 600 V AC 25 A

Certificates and Declarations (Document Number)

**Declaration of Conformity - CE:** 1SCC302005D0201

Instructions and Manuals:	1SCC302013F0006
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 Width:	70 mm
Package Level 1 Length:	122 mm
Package Level 1 Height:	70 mm
Package Level 1 Gross Weight:	0.09 kg
Package Level 1 EAN:	6417019635613
Classifications	
Classifications	
Object Classification Code:	Q
Object Classification Code: ETIM 5:	EC002611 - Control switch
Object Classification Code:	•
Object Classification Code: ETIM 5:	EC002611 - Control switch
Object Classification Code: ETIM 5:	EC002611 - Control switch
Object Classification Code: ETIM 5:	EC002611 - Control switch
Object Classification Code: ETIM 5:	EC002611 - Control switch
Object Classification Code: ETIM 5:	EC002611 - Control switch
Object Classification Code: ETIM 5:	EC002611 - Control switch
Object Classification Code: ETIM 5: ETIM 6:	EC002611 - Control switch

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

## Click to view similar products for abb manufacturer:

Other Similar products are found below:

TV10-516R 017667013 RF727 2CMA100178R1000 2CMA100163R1000 5SDD 92Z0401 ESV14-BS EZS-21-250 F204AC-40/0.03 F36225/0.03 GJL1211201R8000 GJL1211501R8000 GJL1213001R0017 GJL1213001R0101 GJL1311001R0011 GJL1311001R0101
GJL1311001R8010 GJL1311201R0001 GJL1313001R0011 GJL1313001R0101 GJL1317201R0001 A40-30-10-84 AF09-30-01-11
AF460-30-11-68 1455 B14-250 EF45-30 ERG297 HSC2-20 ISAM201904R1001 ISAM350000R1003 ISAZ721201R1009
ISAZ721201R1014 ISAZ721201R1025 ISBL157001R1310 ISBL277001R1300 ISBL277001R4100 ISBL367001R1300
ISBL387001R4100 ISBN010110R1001 ISBN010110R1010 ISBN010140R1022 ISBN010140R1122 ISDA057197R1 ISFA611101R1002
ISFA611130R1103 ISFA611131R1101 ISFA611143R1101 ISFA611202R1108 ISFA611203R1108