

## Dino-Lite AM7915MZTL - EDGE



The AM7915MZTL is part of the Long Working Distance (LWD) range and with its Long Working Distance and magnification range from 10 - 140x, it is suitable for a wide range of applications where extra distance to the object or a larger field of view is required.

The main features of the AM7915MZTL are:

- 5 Megapixel Edge sensor
- Extended Depth of Field (EDOF)
- Extended Dynamic Range (EDR)
- 10-140x Magnification & Long working distance
- Automatic Magnification Reading (AMR)
- Adjustable polarizer
- Flexible LED Control (FLC)

Model AM7915MZTL  Resolution 5 megapixel (2592x1944)  Magnification 10-140x  Interface USB 2.0  Nr. of LED's 8  LED on/off switchable Yes  LED color White  Housing Aluminium alloy housing  Microtouch Yes  Output Picture, video  Video Frame Rate up to 30 frames-per-second  Measurement Yes  Calibration Yes  Diffuser available: Yes (N3C-D included)  Infrared filter: IR cut-filter >650 nm	
Magnification 10-140x Interface USB 2.0 Nr. of LED's 8 LED on/off switchable Yes LED color White Housing Aluminium alloy housing Microtouch Yes Output Picture, video Video Frame Rate up to 30 frames-per-second Measurement Yes Calibration Yes Diffuser available: Yes (N3C-D included)	
Interface USB 2.0  Nr. of LED's 8  LED on/off switchable Yes  LED color White  Housing Aluminium alloy housing  Microtouch Yes  Output Picture, video  Video Frame Rate up to 30 frames-per-second  Measurement Yes  Calibration Yes  Diffuser available: Yes (N3C-D included)	
Nr. of LED's  LED on/off switchable  Yes  LED color  White  Housing  Aluminium alloy housing  Microtouch  Yes  Output  Picture, video  Video Frame Rate  up to 30 frames-per-second  Measurement  Yes  Calibration  Yes  Diffuser available:  Yes (N3C-D included)	
LED on/off switchableYesLED colorWhiteHousingAluminium alloy housingMicrotouchYesOutputPicture, videoVideo Frame Rateup to 30 frames-per-secondMeasurementYesCalibrationYesDiffuser available:Yes (N3C-D included)	
LED colorWhiteHousingAluminium alloy housingMicrotouchYesOutputPicture, videoVideo Frame Rateup to 30 frames-per-secondMeasurementYesCalibrationYesDiffuser available:Yes (N3C-D included)	
Housing Microtouch Yes Output Picture, video Video Frame Rate up to 30 frames-per-second Measurement Yes Calibration Yes Diffuser available: Yes (N3C-D included)	
Microtouch Yes  Output Picture, video  Video Frame Rate up to 30 frames-per-second  Measurement Yes  Calibration Yes  Diffuser available: Yes (N3C-D included)	
Output Picture, video  Video Frame Rate up to 30 frames-per-second  Measurement Yes  Calibration Yes  Diffuser available: Yes (N3C-D included)	
Video Frame Rateup to 30 frames-per-secondMeasurementYesCalibrationYesDiffuser available:Yes (N3C-D included)	
Measurement Yes Calibration Yes Diffuser available: Yes (N3C-D included)	
Calibration Yes  Diffuser available: Yes (N3C-D included)	
Diffuser available: Yes (N3C-D included)	
Infrared filter: IR cut-filter >650 nm	
Polarizer: Yes, linear	
ESD safe Yes	
Compatibility Windows XP, Vista, 7, 8 & 10, MacOS 10.9 and up	
Software (Included) DinoCapture 2.0 (Windows), DinoXcope (Mac OS)	
Special feature:  Aut. Magn. reading, Ext. Dynamic Range (EDR), Ext. Field (EDOF), Flexible LED Control (FLC)	Depth of



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for dino-lite manufacturer:

Other Similar products are found below:

AM7515MZT AM7025X AM4113TL