

FPA350 350W Thick Film Heatsink Resistors



350 Watt resistor designed for various applications including traction; power supplies; speed drives; power supplies; control devices and robotics.



- Power Rating 350 watts at 85°C bottom case temp
 - Value Range R2 to 1M
 - Tolerance Options $\pm 5\%$ or $\pm 10\%$ standard
 - TCR Options $\pm 500\text{ppm}/^\circ\text{C}$ ($0.1 \Omega \leq 0.12 \Omega$) Standard
 - $\pm 150\text{ppm}/^\circ\text{C}$ ($>0.12 \Omega \leq 1\text{M} \Omega$) Standard
 - Maximum Voltage 5000Vdc
 - Dielectric Strength 7k Vrms / 50 Hz / 500 VA test time 1 min.
- Non-inductive design, high insulation & partial discharge performance
RoHS Compliant.

Characteristics

Power rating	350W at 85°C bottom case temp	Partial discharge	4kV rms. <10pC to IEC60270
Resistance range	R2 to 1M	Typical inductance	$\geq 80\text{nH}$ measured at 10Hz
Tolerance	$\pm 10\%$ (K) $\pm 5\%$ (J), $\geq 3R \pm 1\%$ (F)	Parallel capacitance	$\geq 40\text{pF}$ measured at 10Hz
Temperature coefficient	$\pm 500\text{ppm}/^\circ\text{C}$ ($0.1 \Omega \leq 0.12 \Omega$) $\pm 150\text{ppm}/^\circ\text{C}$ ($>0.12 \Omega \leq 1\text{M} \Omega$)	Capacitance / mass	$\geq 110\text{pF}$ measured at 10Hz
Maximum working voltage	5000 Vdc rms (50 Hz)	Short term overload	600W at 70°C for 10 sec
Working temperature range	-55°C to +150°C	Mounting screw / max. torque	M5 standard , 1.8Nm
Dielectric strength	7kV rms/50Hz/500VA test time 1 min	Contacts	(M4 on special request connection screw thread max 7mm)
Creepage distance	> 42mm std (higher on request)		

Test Specifications

Humidity 56 days / 40°C / Steady state 95%	$\Delta R \pm 0.25\%$
Temperature -55 / +125 / 5 cycles	$\Delta R \pm 0.20\%$
Shock 40g / 4,000 times	$\Delta R \pm 0.25\%$
Vibrations 2-500Hz / 10g	$\Delta R \pm 0.25\%$
Load life 3000 cycle Pn 30 min. on / 30 min. off	$\Delta R \pm 0.40\%$

ARCOL UK Limited,
Threemilestone Ind. Estate,
Truro, Cornwall TR4 9LG, UK.
T +44 (0) 1872 277431
F +44 (0) 1872 222002
E sales@arcolresistors.com

www.arcolresistors.com


The information contained herein does not form part of a contract and is subject to change without notice. ARCOL operate a policy of continual product development therefore, specifications may change.

It is the responsibility of the customer to ensure that the component selected from our range is suitable for the intended application. If in doubt please ask ARCOL.

FPA600 600W Thick Film Heatsink Resistors



Derating Curve




Ordering Procedure

Standard resistor: Specify series, watts, ohmic value, tolerance code. e.g FPA350 10R K

Dimensions

Air distance: 14mm [0.5512] min.
Creeping distance: 42mm [1.6535] min.

Terminal height 30/32
Standard



Other terminal dimensions available, contact ARCOL for more information

ARCOL UK Limited,
Threemilestone Ind. Estate,
Truro, Cornwall TR4 9LG, UK.
T +44 (0) 1872 277431
F +44 (0) 1872 222002
E sales@arcolresistors.com

www.arcolresistors.com

The information contained herein does not form part of a contract and is subject to change without notice. ARCOL operate a policy of continual product development therefore, specifications may change.

It is the responsibility of the customer to ensure that the component selected from our range is suitable for the intended application. If in doubt please ask ARCOL

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [ohmite](#) manufacturer:

Other Similar products are found below :

[OG1825](#) [6017E](#) [608-8E](#) [6112-EP-252E](#) [62645-10/10/10](#) [630HR025](#) [6532E](#) [CU1511](#) [D1000K5R0](#) [D100K600](#) [D225K2K2E](#) [D25K300](#)
[D25K750](#) [EVFL170EN4R7JE](#) [EVFT119EM47RJE](#) [EVFT170EN100JE](#) [F20J25KE](#) [F20J3K0E](#) [F30J50R](#) [F40J200](#) [F55J100](#) [F55J20K](#) [76303](#)
[805F10K](#) [805F250](#) [805F2K5](#) [805F75R](#) [80FR499](#) [810F20KE](#) [83FR121](#) [850F250](#) [MOX-1N-132505FE](#) [MOX-5-122002JE](#) [MOX-](#)
[750232506FE](#) [MOX-H-021004J](#) [MOX-H-042505JE](#) [MOX-J-045006F](#) [MOX-J-046004J](#) [PFE5K4R50](#) [PFR5K25R0](#) [90J10KE-B](#) [90J12K](#)
[90J47K](#) [90J56R](#) [90J5R6E](#) [91J2K2](#) [91J91RE](#) [92J1K0](#) [93J33R](#) [93J470](#)