

1.CABLE; (A)28AWG(7/0.12TC),NON-UI,NON-FOIL,2C+S,OD=3.0±0.2mm,BLACK COLOR,PVC JACKET. (B)28AWG(7/0.12TC),UL2919,AL+D+B,{[(28AWG*1C+D+AL)*3COAX+28AWG*5.5PAIR]},OD=9.0±0.2mm.BLACK WITH EMBOSS,PVC JACKET.

SHELL

PĂIR


- 2. LENGTH: L.
- 3. CONNECTORS: HDB15M*2PCS(BLACK INSULATOR), ø3.5 STEREO PLUG*2PCS(三段式)(SHELL NICKEL).
- 4. MOLD: MOLDING TYPE.
- 5. SCREW:四方模螺絲*4PCS.
- 6. CONTACTS:

•	HDB15P	1	6	2	7	3	8	4 14	5	12	10	13	11	15	9	64
	HDB15P	1 RC	6 RG	2 BC	7 BG	3 cc	8	4 14 PAIR	5 P.	12 ĂIR	10 P/	13 (IR	11 P/	15 ÃIR	9	64 SHELL
ø3.5 STEREO PLUG(P1)											64					
ø3.5 STEREO PLUG(P2)) [1	2	64				

7. Test machine test condition. A.100% OPEN, SHORT & INTERMITANCE TEST. B.CONDUCTOR RESISTANCE: 3ohms MAX: C.INSULATION RESISTANCE: 5M Min/,10ms:

8. ALL MUST BE MEET ON ROHS COMPLIANT.

	COMPANY	MF	RP 9	ITEM NO.	SVST-3MM	NO B			
	REVISION	DATE	DISCRIPTION	DRAWN					SCAL
	REV.A/0	2015.04.14		BY DESIGNED				Stellar Labs Computer +	
				BY		SPEC		Stellar Labs Computer +	
Ī				APPROVAL				PAG	



٩LE 4GE 1/1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for mcm manufacturer:

Other Similar products are found below:

NWTBATCAPMB13 27-505 27-4200 27-840 28-5958 50-10820 28-1510 27-5918 27-5977 24-12352 287-14020 28-6023 35SPS-3 28-6008 21-4605 21-4575 21-19084 21-12825 27-570 28-1525 83-17604 27-5833 27-6020 24-12345 28-6017 28-6032 21-18966 30-1530 28-970 27-560 26-120 CA68B 24-12344 28-6005 24-13075 PCM-2100-50 21-18956 28-6080 24-5360 24-1040 27-5917 28-6031 HD15MM35N-100F 28-975 27-4270 85-11102 27-5940 27-5949 27-6112 HD15MM35N-6F