



# WRAPTOR Series UltraTemp Polyimide Labels

**Part Number:**

WRAP-6-472

**Label/Tape Size:**

3 in H x 2 in W

**Material:**

Polyimide

**Material Number:**

B-472

**Color:**

White

## OVERVIEW

Flame Retardant Wire Wraps (B-472) are ideal for cable and wire bundle applications and label applications where self-extinguishing properties are required.

- Polyimide material specifically designed to self-extinguish and prevent flames from propagating
- Matte finish material with permanent acrylic adhesive can be thermal transfer printed or dot matrix printed
- RoHS compliant to 2005/618/EC MCV amendment to RoHS Directive 2002/95/EC
- Service temperature of -40°F to 212°F (-40°C to 100°C)
- **SPECIFICATIONS**

Anti-Skid Surface?	N/A
Material Number	<b>B-472</b>
Dimensions	3 in H x 2 in W
UOM	Roll of 1900 Labels
Finish	Matte
Indoor or Outdoor Use	N/A
Label/Tape Size	3 in H x 2 in W
Maximum Service Temperature °F	212 °F
Maximum Wire Diameter	0.32 in
Maximum Wire Gauge	3/1 gauge
Minimum Service Temperature °F	-94 °F
Minimum Wire Diameter	0.13 in
Minimum Wire Gauge	6 gauge
Pre-Printed Areas on Label	Colored Write-On Area
Printable Area Dimensions	3 in H x 2 in W
Printable Area Height	3 in
Printable Area Width	2 in
Product Number	129972
UPC	662820653004
Quantity per Roll	1900
Quantity per Row	1
Tamper Indication Type	N/A
Thickness	0.0032 in
Trade Name	Wraptor™ UltraTemp®
Adhesive Type	Acrylic
Applications	Cable & Wire Marking
Color	White
For Use with Printer	WRAPTOR™ Wire Marking System
Header	No Header
Label/Media Format	Roll
Material	Polyimide
Material Properties	Flame-Retardant
Print Technology	Thermal Transfer
Resistance Properties	Abrasion-Resistant, Chemical-Resistant, Corrosion-Resistant, Flame-Retardant, Humidity-Resistant, UV-Resistant
Shape	Rectangle
Suggested Ribbon Series	R2000, R4300, R6200

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [brady](#) manufacturer:*

Other Similar products are found below :

[BMP21-PLUS-KIT1](#) [M71C-2000-595-YL](#) [66271](#) [67063](#) [DAT-38-292-1](#) [DAT-38-292-2.5](#) [DAT-43-502-1](#) [134304](#) [ECL-107-619](#) [18453](#)  
[18617](#) [18669](#) [LAT-31-747-1](#) [LAT-5-747-10](#) [SCN03-1](#) [SCN03-8](#) [SCN10-7](#) [SCN10-8](#) [18472](#) [18489](#) [18581](#) [AF-1-9-PK](#) [PSPT-187-175-YL](#)  
[29690](#) [PTL-17-422](#) [PTL-42-439](#) [PWC-PK-1](#) [33108](#) [3450-A](#) [3450-D](#) [3450-G](#) [34511](#) [34513](#) [34515](#) [34517](#) [34518](#) [35400](#) [M71-22-423](#) [THT-](#)  
[12-727-10](#) [THT-17-7546-3](#) [THT-38-724-10](#) [THT-5-449-10](#) [THT-55-424-1](#) [THT-6-428-10](#) [THT-7-424-3](#) [33054](#) [33104](#) [33107](#) [3450-C](#) [3450-](#)  
[E](#)