


HAKKO FX-100 ESD SAFE
SOLDERING STATION

Raising the world standard in induction heating soldering irons



Compatible with T31 Series
Replacement tips
Part numbers

T31-XX BC1

 450°C ▶ 01 Indicates tip shape and size
 400°C ▶ 02
 350°C ▶ 03

Unlike conventional temperature setting systems, every tip in the lineup is fixed at either 350°C, 400°C or 450°C.

This makes managing the set temperature of the soldering iron easier than ever.


FX-100
Packing List


Station, Handpiece (FX-1001), Heat resistant pad, Power cord, Sleeve (green), Sleeve (gray), Iron holder, Instruction manual

Specifications

Power consumption	28 W (85 W)
Tip temperature	T31-01 Series: 450°C T31-02 Series: 400°C T31-03 Series: 350°C
Temperature stability	±1.1°C
Station	
Output power	50 W
Output frequency	13.56 MHz
Dimensions	127(W) × 150(H) × 167(D)mm
Weight	3 kg
Soldering Iron	
Tip to ground resistance	<2 Ω
Tip to ground potential	<2 mV
Heating element	IH (Induction heating)
Cord length	1.3 m
Total length (w/o cord)	190 mm with 2.4D tip for 350°C or 400°C 193 mm with 2.4D tip for 450°C
Weight (w/o cord)	31 g with 2.4D tip for 400°C

CA00441GbYa006 2016.6

HAKKO
HAKKO CORPORATION
 OVERSEAS AFFILIATES

 U.S.A.
 AMERICAN HAKKO PRODUCTS, INC.
 28920 AVENUE WILLIAMS VALENCIA, CA 91355, U.S.A.
 TEL: (661) 294-0090 FAX: (661) 294-0096
 Toll Free (800)88-HAKKO
 http://www.hakkousa.com

HEAD OFFICE
 4-5, SHIOKUSA 2-CHOME, NANIWA-KU, OSAKA, 556-0024 JAPAN
 TEL:+81-6-6561-3225 FAX:+81-6-6561-8466
 http://www.hakko.com E-mail:sales@hakko.com

HONG KONG
 HAKKO DEVELOPMENT CO., LTD.
 ROOM 1504, EASTERN HARBOUR CENTRE,
 28 HOI CHAK STREET, QUARRY BAY, HONG KONG.
 TEL: 2811-5588 FAX: 2590-0217
 http://www.hakko.com.hk
 E-mail:info@hakko.com.hk

SINGAPORE
 HAKKO PRODUCTS PTE LTD
 1, GENTING LINK #02-04
 PERFECT ONE, SINGAPORE 349518
 TEL: 6748-2277 FAX: 6744-0033
 http://www.hakko.com.sg
 E-mail:sales@hakko.com.sg

 Please access to the following for the other sales affiliates and distributors.
<http://www.hakko.com>

 Specifications and design are subject to change without notice. Copyright HAKKO Corporation. All right reserved.
 HAKKO is registered in countries and regions including the following. Japan, USA, South Korea, Singapore, China, the member of CTM.


A next-generation IH soldering iron

Featuring a small tip that packs enough heat power to change the face of high heat capacity, high-density micro-soldering

Unlike resistance-based heating systems that control temperature by turning heater power on and off via a sensor, the tip itself produces heat and maintains a constant temperature in induction heating system. This system comes into its own when using a small tip to solder spots requiring a lot of power.

Sleep/auto shutoff function

Safe design ensures soldering iron switches to sleep mode or auto shutoff mode when placed in iron holder.



Design emphasizes both functionality and workability

2013 Good Design Award winner.
The FX-100 enables smooth soldering of difficult areas thanks to a thin, light cord and responsive grip.

Large LCD displays information for easy operation and management

● ● ● Simple three-button operation

The station's three buttons can be used to switch between modes. The function of each button is displayed on the LCD screen for easy operation.



PROFILE 1
S:NO.001
U:HAKKO TARO
S:SN63 PB37

Profile

Lets you register station name, user names, solder types, for easier management and status confirmation.

TIP LOADS
approx.
000657 Points
<RESET> <OK>

Tip Loads

Lets you track tip wear by automatically recording the number of soldering operations*.
*This feature is only intended to serve as a general guide.

TIP TIME
0013 hours
<RESET> <OK>

Tip Time

Counts the length of time that the tip has been powered on. If you set a time with the alert function, the system will notify you when it is time to replace the tip.

<01>
N
■■■■■■

Tip Type

Displays the temperature type of tip currently in use.

Induction heating for excellent thermal efficiency

The unique Induction Heating (IH) system used by the HAKKO FX-100, which automatically heats the tips and rapidly returns it to the fixed temperature whenever a load is applied to the tip, includes HAKKO's proprietary "Power Assist" function.

This function provides less temperature drop and improved thermal recovery when soldering. And if you need a bit more power for those challenging solder joints, just select "Boost Mode".

*Power Assist is HAKKO's proprietary function that monitors current, detects drops in tip temperature, and increases power to assist thermal recovery characteristics.



*Rubber cleaner shown in photo is an optional part.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [hakko manufacturer](#):

Other Similar products are found below :

[A1006](#) [FT8002-01](#) [PTG-2T1G0008](#) [HFJ11-1G06ERL](#) [HFJ12-E2450ER-L11RL](#) [B3048](#) [FM203-15](#) [N1-L10](#) [A1014](#) [N1-20](#) [T12-D24](#)
[FM2023-04](#) [FT8003](#) [G3-1601](#) [T31-01JS02](#) [T33-BC4](#) [T33-BC5](#) [T33-D24](#) [950-CK](#) [A1013](#) [A1067](#) [A1187B](#) [A1379](#) [B1309](#) [B1787](#) [C1392B](#)
[A1553](#) [A1554](#) [FX300-03](#) [FT300](#) [918-T-1.6D/P](#) [C1148B/P](#) [111-SA](#) [T15-1006](#) [T15-1202](#) [N3-23](#) [B5045](#) [B5046](#) [N60-03](#) [N60-05](#) [N60-07](#)
[N60-09](#) [T12-1612](#) [C1148B](#) [HFJ11-1G11E-L11RL](#) [TG41-2006NRLTR](#) [T30-KU](#) [T12-BC2](#) [B3474](#) [A1560](#)