


Replacement Tips




T33-BC2 Shape 2BC







T33-BC4 Shape 4BC




T33-BC5 Shape 5BC




T33-BC6 Shape 6BC




T33-D24 Shape 2.4D




T33-D32 Shape 3.2D



T33-D5 Shape 5D





Packing list



Specifications

Power consumption	300 W
Temperature range	50 to 500°C
Temperature stability	±5°C at idle temperature

Station

Soldering Iron		
Weight	3.9 kg	
Dimensions	145 (W) × 107 (H) × 211 (D) mm	
Output voltage	AC 29 V	

Power consumption	260 W (29 V)
Tip to ground resistance	<2Ω
Tip to ground potential	<2 mV
Heating element	Composite heater
Cord length	1.2 m
Total length (without cord)	228 mm (with 4BC tip)
Weight (without cord)	50 g (with 4BC tip)

Station, Handpiece (FX-8002), Heat resistant pad, Power cord, Connecting cable, Iron holder (with cleaning wire), Instruction manual

CA00461EbYa004 2015.12

HAKKO CORPORATION **OVERSEAS AFFILIATES**

HEAD OFFICE

4-5, SHIOKUSA 2-CHOME, NANIWA-KU, OSAKA, 556-0024 JAPAN TEL:+81-6-6561-3225 FAX:+81-6-6561-8466 http://www.hakko.com E-mail:sales@hakko.com

U.S.A.

AMERICAN HAKKO PRODUCTS, INC.
28920 AVENUE WILLIAMS VALENCIA, CA 91355, U.S.A.
TEL: (661) 294-0096 FAX: (661) 294-0096
Toll Free (800)88-HAKKO

HAKKO DEVELOPMENT CO., LTD.
ROOM 1504, EASTERN HARBOUR CENTRE,
28 HOI CHAK STREET, QUARRY BAY, HONG KONG.
TEL: 2811-5588 FAX: 2590-0217 http://www.hakko.com.hk

SINGAPORE HAKKO PRODUCTS PTE LTD 1, GENTING LINK #02-04 PERFECT ONE, SINGAPORE 349518 TEL: 6748-2277 FAX: 6744-0033

Please access to the following for the other sales affiliates and distributors. http://www.hakko.com

Specifications and design are subject to change without notice. Copyright HAKKO Corporation. All right reserved. **②HAK**≪ is registered in countries and regions including the following. Japan, USA, South Korea, Singapore, China, the member of CTM.



Soldering Iron

Station Type **Heavy Duty Soldering Station**

HAKCOFX-801 ESD SAFE

Go Beyond the Limits! Super Power 300 Watts to Change the World of Soldering



Make the impossible possible with Super Power of 300 W Heater.

FX-801 can provide tremendous heating performance with super power 300 W composite heater.

Check out the powerful performance of FX-801 easily melting a bar solder. http://www.hakko.com/mov_e_fx801_feature1





Handles on unit body

Handles on unit body make it easy to carry.



Preset mode

Up to 6 settings can be preset and easily called up by Up/Down buttons.

*A number is displayed when preset temp. is changed.

Large LED display

A LED display roughly double the size of a previous model is very easy to see.

Password function

Settings can be locked from unnecessary changes by password function.

[AP[GEE

The same weight as the iron part of FX-838, 150 W soldering station, for operator's comfort and better workability.

Easy tip replacement

The composite tip makes tip replacement easy.

Auto Sleep/Auto Shut-off function

Safety design automatically enters sleep/shut-off function when an iron is placed in an iron holder. The function automatically cools down tip temperature and shut-off power when not in use for a certain period of time.

Compatible with N2 System (Option)

Replacing an iron part (FX-8002) with an optional N₂ iron part (FX-8003), it enables use of N2 system.

*Appropriate option nozzle assemblies for each tip shape are necessary.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for hakko manufacturer:

Other Similar products are found below:

A1006 FT8002-01 PTG-2T1G0008 HFJ11-1G06ERL HFJ12-E2450ER-L11RL B3048 FM203-15 N1-L10 A1014 N1-20 T12-D24
FM2023-04 FT8003 G3-1601 T31-01JS02 T33-BC4 T33-BC5 T33-D24 950-CK A1013 A1067 A1187B A1379 B1309 B1787 C1392B
A1553 A1554 FX300-03 FT300 918-T-1.6D/P C1148B/P 111-SA T15-1006 T15-1202 N3-23 B5045 B5046 N60-03 N60-05 N60-07
N60-09 T12-1612 C1148B HFJ11-1G11E-L11RL TG41-2006NRLTR T30-KU T12-BC2 B3474 A1560