

TWIST DRILLS





Twist drills DIN 338 type N HSSE-Co 5 ground in plastic box



Ø 1,0 - 10,0 mm in plastic box of 10 Ø 10,2 - 13,0 mm in plastic box of 5




















Twist drills DIN 338 type N HSSE-Co 5 ground in plastic case




























	No.	€
19-piece set of twist drills	A 215 214 RO	
25-piece set of twist drills	A 215 215 RO	

Twist drills DIN 338 type N HSSE-Co 5 ground in steel case



























	No.	€
19-piece set of twist drills	A 215 214	
25-piece set of twist drills	A 215 215	
















Twist drills DIN 338 type N HSS ground in plastic box



Ø 1,0 - 10,0 mm in plastic box of 10 Ø 10,2 - 13,0 mm in plastic box of 5


















Ø mm	™	mm	No.		€
Ø 1,0 mm	34,0 mm	12,0 mm	214 010 TX	10	
Ø 1,5 mm	40,0 mm	18,0 mm	214 015 TX	10	
Ø 2,0 mm	49,0 mm	24,0 mm	214 020 TX	10	
Ø 2,5 mm	57,0 mm	30,0 mm	214 025 TX	10	
Ø 3,0 mm	61,0 mm	33,0 mm	214 030 TX	10	
Ø 3,3 mm	65,0 mm	36,0 mm	214 033 TX	10	
Ø 3,5 mm	70,0 mm	39,0 mm	214 035 TX	10	
Ø 4,0 mm	75,0 mm	43,0 mm	214 040 TX	10	
Ø 4,2 mm	75,0 mm	43,0 mm	214 042 TX	10	
Ø 4,5 mm	80,0 mm	47,0 mm	214 045 TX	10	
Ø 5,0 mm	86,0 mm	52,0 mm	214 050 TX	10	
Ø 5,5 mm	93,0 mm	57,0 mm	214 055 TX	10	
Ø 6,0 mm	93,0 mm	57,0 mm	214 060 TX	10	
Ø 6,5 mm	101,0 mm	63,0 mm	214 065 TX	10	
Ø 6,8 mm	109,0 mm	69,0 mm	214 068 TX	10	
Ø 7,0 mm	109,0 mm	69,0 mm	214 070 TX	10	
Ø 7,5 mm	109,0 mm	69,0 mm	214 075 TX	10	
Ø 8,0 mm	117,0 mm	75,0 mm	214 080 TX	10	
Ø 8,5 mm	117,0 mm	75,0 mm	214 085 TX	10	
Ø 9,0 mm	125,0 mm	81,0 mm	214 090 TX	10	
Ø 9,5 mm	125,0 mm	81,0 mm	214 095 TX	10	
Ø 10,0 mm	133,0 mm	87,0 mm	214 100 TX	10	
Ø 10,2 mm	133,0 mm	87,0 mm	214 102 TX	5	
Ø 10,5 mm	133,0 mm	87,0 mm	214 105 TX	5	
Ø 11,0 mm	142,0 mm	94,0 mm	214 110 TX	5	
Ø 11,5 mm	142,0 mm	94,0 mm	214 115 TX	5	
Ø 12,0 mm	151,0 mm	101,0 mm	214 120 TX	5	
Ø 12,2 mm	151,0 mm	101,0 mm	214 122 TX	5	
Ø 12,5 mm	151,0 mm	101,0 mm	214 125 TX	5	
Ø 13,0 mm	151,0 mm	101,0 mm	214 130 TX	5	







€





Twist drills magazine DIN 338

type N HSS ground


type N HSS ground


Twist drill set DIN 345 type N HSS


No.

A 214 200 RO











Twist drills DIN 338 type N HSS rolled in plastic box



Ø 1,0 - 10,0 mm in plastic box of 10 Ø 10,2 - 13,0 mm in plastic box of 5




















Ø mm	★ mm	mm	No.		€
Ø 1,0 mm	34,0 mm	12,0 mm	201 010 TX	10	
Ø 1,5 mm	40,0 mm	18,0 mm	201 015 TX	10	
Ø 2,0 mm	49,0 mm	24,0 mm	201 020 TX	10	
Ø 2,5 mm	57,0 mm	30,0 mm	201 025 TX	10	
Ø 3,0 mm	61,0 mm	33,0 mm	201 030 TX	10	
Ø 3,3 mm	65,0 mm	36,0 mm	201 033 TX	10	
Ø 3,5 mm	70,0 mm	39,0 mm	201 035 TX	10	
Ø 4,0 mm	75,0 mm	43,0 mm	201 040 TX	10	
Ø 4,2 mm	75,0 mm	43,0 mm	201 042 TX	10	
Ø 4,5 mm	80,0 mm	47,0 mm	201 045 TX	10	
Ø 5,0 mm	86,0 mm	52,0 mm	201 050 TX	10	
Ø 5,5 mm	93,0 mm	57,0 mm	201 055 TX	10	
Ø 6,0 mm	93,0 mm	57,0 mm	201 060 TX	10	
Ø 6,5 mm	101,0 mm	63,0 mm	201 065 TX	10	
Ø 6,8 mm	109,0 mm	69,0 mm	201 068 TX	10	
Ø 7,0 mm	109,0 mm	69,0 mm	201 070 TX	10	
Ø 7,5 mm	109,0 mm	69,0 mm	201 075 TX	10	
Ø 8,0 mm	117,0 mm	75,0 mm	201 080 TX	10	
Ø 8,5 mm	117,0 mm	75,0 mm	201 085 TX	10	
Ø 9,0 mm	125,0 mm	81,0 mm	201 090 TX	10	
Ø 9,5 mm	125,0 mm	81,0 mm	201 095 TX	10	
Ø 10,0 mm	133,0 mm	87,0 mm	201 100 TX	10	
Ø 10,2 mm	133,0 mm	87,0 mm	201 102 TX	5	
Ø 10,5 mm	133,0 mm	87,0 mm	201 105 TX	5	
Ø 11,0 mm	142,0 mm	94,0 mm	201 110 TX	5	
Ø 11,5 mm	142,0 mm	94,0 mm	201 115 TX	5	
Ø 12,0 mm	151,0 mm	101,0 mm	201 120 TX	5	
Ø 12,2 mm	151,0 mm	101,0 mm	201 122 TX	5	
Ø 12,5 mm	151,0 mm	101,0 mm	201 125 TX	5	
Ø 13,0 mm	151,0 mm	101,0 mm	201 130 TX	5	
















Twist drills DIN 338 type N HSS-TiN ground in plastic box



Ø 1,0 - 10,0 mm in plastic box of 10 Ø 10,2 - 13,0 mm in plastic box of 5

















Ø mm	<mark>→ mm</mark> →	mm	No.	€
Ø 1,0 mm	34,0 mm	12,0 mm	250 010 TX	
Ø 1,5 mm	40,0 mm	18,0 mm	250 015 TX	
Ø 2,0 mm	49,0 mm	24,0 mm	250 020 TX	
Ø 2,5 mm	57,0 mm	30,0 mm	250 025 TX	
Ø 3,0 mm	61,0 mm	33,0 mm	250 030 TX	
Ø 3,3 mm	65,0 mm	36,0 mm	250 033 TX	
Ø 3,5 mm	70,0 mm	39,0 mm	250 035 TX	
Ø 4,0 mm	75,0 mm	43,0 mm	250 040 TX	
Ø 4,2 mm	75,0 mm	43,0 mm	250 042 TX	
Ø 4,5 mm	80,0 mm	47,0 mm	250 045 TX	
Ø 5,0 mm	86,0 mm	52,0 mm	250 050 TX	
Ø 5,5 mm	93,0 mm	57,0 mm	250 055 TX	
Ø 6,0 mm	93,0 mm	57,0 mm	250 060 TX	
Ø 6,5 mm	101,0 mm	63,0 mm	250 065 TX	
Ø 6,8 mm	109,0 mm	69,0 mm	250 068 TX	

Ø mm	<mark>→ mm</mark>	mm	No.	€
Ø 7,0 mm	109,0 mm	69,0 mm	250 070 TX	
Ø 7,5 mm	109,0 mm	69,0 mm	250 075 TX	
Ø 8,0 mm	117,0 mm	75,0 mm	250 080 TX	
Ø 8,5 mm	117,0 mm	75,0 mm	250 085 TX	
Ø 9,0 mm	125,0 mm	81,0 mm	250 090 TX	
Ø 9,5 mm	125,0 mm	81,0 mm	250 095 TX	
Ø 10,0 mm	133,0 mm	87,0 mm	250 100 TX	
Ø 10,2 mm	133,0 mm	87,0 mm	250 102 TX	
Ø 10,5 mm	133,0 mm	87,0 mm	250 105 TX	
Ø 11,0 mm	142,0 mm	94,0 mm	250 110 TX	
Ø 11,5 mm	142,0 mm	94,0 mm	250 115 TX	
Ø 12,0 mm	151,0 mm	101,0 mm	250 120 TX	
Ø 12,2 mm	151,0 mm	101,0 mm	250 122 TX	
Ø 12,5 mm	151,0 mm	101,0 mm	250 125 TX	
Ø 13,0 mm	151,0 mm	101,0 mm	250 130 TX	

Twist drills magazine DIN 338 type N HSS-TiN ground in plastic case







10 pcs. each of Ø 1,0 - 8,0 x 0,5 mm 5 pcs. each of Ø 8,5 - 10,0 x 0,5 mm

	No.	€
Twist drills magazine DIN 338 type N HSS ground	A 250 200 RO	



Twist drills DIN 338 type N HSS-TiN ground in plastic case






























A 250 215 TRO

Twist drills DIN 338 type N HSS-TiN ground in steel






















	No.	(E)
19-piece set of twist drills	A 250 214 T	
25-piece set of twist drills	A 250 215 T	

25-piece set of twist drills



STEP DRILLS







Step drills HSS + HSS-TiN, CBN ground, straight cut with split point













Size 0/9 I Ø 4,0 - 12,0 mm Size 1 I Ø 4,0 - 20,0 mm Size 2 I Ø 6,0 - 30,0 mm Point cut: work's specification with split point DIN 1412 C

Point angle: 118° Step angle: 90°

Ø tolerance: works specification

Surface: bright / titanium-nitride coated

right hand cutting

Packing unit: in plastic box of 1



	Size no.	Drilling range	No.	€
100	0/9	4,0 - 12,0	A101 050-9 TX	
HSS	1	4,0 - 20,0	A101 051 TX	
	2	6,0 - 30,0	A101 052 TX	

	Size no.	Drilling range	No.	€
	0/9	4,0 - 12,0	A 101 050-9 TTX	
HSS TIN	1	4,0 - 20,0	A 101 051 TTX	
	2	6,0 - 30,0	A 101 052 TTX	

Step drill set HSS, straight cut in plastic case











Size 0/9 / Size 1 / Size 2



	No.	€
3-piece set of step drills HSS, sizes 0/9, 1, 2	A 101 126 RO	

Step drill set HSS-TiN, straight cut in plastic case







Size 0/9 / Size 1 / Size 2



	No.	€
3-piece set of step drills HSS-TiN, sizes 0/9, 1, 2	A 101 126 TRO	





TAPER AND DEBURRING COUNTERSINKER







Taper and deburring countersinker HSS + HSS-TiN DIN 335 type C 90°













90° Counters. angle: Shank: cylindrical Cutting edges:

Surface: bright / titanium-nitride

right hand cutting

Packing unit: in plastic tubes of 1



	Ø2 mm	mm	No.	€
	6,3	45,0	102 107 TX	1,85 €
HSS	8,3	50,0	102 111 TX	2,00€
W. 100	10,4	50,0	102 114 TX	2,15 €
TO 500	12,4	56,0	102 116 TX	2,25 €
100	16,5	60,0	102 119-1 TX	2,95 €
	20,5	63,0	102 121 TX	3,50 €

	Ø2 mm	mm	No.	€
	6,3	45,0	102 107 TTX	
HSS	8,3	50,0	102 111 TTX	
	10,4	50,0	102 114 TTX	
TiN	12,4	56,0	102 116 TTX	
	16,5	60,0	102 119 -1 TTX	
	20,5	63,0	102 121 TTX	

Taper and deburring countersinker set HSS, in plastic box











DIN 335 type C 90° Ø 6,3 - 8,3 - 10,4 - 12,4 -16,5 - 20,5 mm



	No.	€
Taper and deburring countersinker set DIN 335 type C 90°	A 102 152 RO	

Taper and deburring countersinker set HSS-TiN, in plastic box





DIN 335 type C 90° Ø 6,3 - 8,3 - 10,4 - 12,4 -16,5 - 20,5 mm



	No.	€
Taper and deburring countersinker set DIN 335 type C 90°	A 102 152 TRO	





CORE DRILLS







Core drills HSS + HSS-TiN with weldon shank (3/4"), CBN ground, cutting depth 30,0 mm














Packing unit: in plastic tubes of 1



	Ø mm		mm	30,0 mm	No.	€
- 原子	12,0	19,0	63,0	30,0	108 212 TX	
HSS	14,0	19,0	63,0	30,0	108 214 TX	
12.5	16,0	19,0	63,0	30,0	108 216 TX	
	18,0	19,0	63,0	30,0	108 218 TX	
	20,0	19,0	63,0	30,0	108 220 TX	
	22,0	19,0	63,0	30,0	108 222 TX	
	24,0	19,0	63,0	30,0	108 224 TX	
	26,0	19,0	63,0	30,0	108 226 TX	
	28,0	19,0	63,0	30,0	108 228 TX	
	30,0	19,0	63,0	30,0	108 230 TX	
	32,0	19,0	63,0	30,0	108 232 TX	

	Ø mm		mm	30,0 mm	No.	(E)
	12,0	19,0	63,0	30,0	108 212 TTX	
HSS TIN	14,0	19,0	63,0	30,0	108 214 TTX	
	16,0	19,0	63,0	30,0	108 216 TTX	
	18,0	19,0	63,0	30,0	108 218 TTX	
	20,0	19,0	63,0	30,0	108 220 TTX	
	22,0	19,0	63,0	30,0	108 222 TTX	
	24,0	19,0	63,0	30,0	108 224 TTX	
	26,0	19,0	63,0	30,0	108 226 TTX	
	28,0	19,0	63,0	30,0	108 228 TTX	
	30,0	19,0	63,0	30,0	108 230 TTX	
	32,0	19,0	63,0	30,0	108 232 TTX	

Pilot pin Ø 6,35 x 77,0 mm for core drills HSS with weldon shank (¾")

Set of core drills HSS with weldon shank (3/4"), CBN ground, in steel case



Ø 12,0 - 14,0 - 16,0 -18,0 - 20,0 - 22,0 mm + 1 pilot pin Ø 6,35 mm



	No.	€
Set of core drills HSS with weldon shank	A 108 820	

Set of core drills HSS-TiN with weldon shank (3/4"), CBN ground, in steel case



Ø 12,0 - 14,0 - 16,0 -18,0 - 20,0 - 22,0 mm + 1 pilot pin Ø 6,35 mm



	No.	€
Set of core drills HSS-TiN with weldon shank	A 108 820 T	



THREAD-CUTTING





Thread-cutting set HSS in steel case











One round die ≈ DIN EN 22568 HSS ground M3 - M12

+ die stock DIN 225 - 25,0 x 9,0 mm



	No.	€
Thread-cutting set, 8 pcs.	A 245 014	

Hand tap set HSS in steel case









One three-piece set of hand taps DIN 352 HSS M3/M4/M5/M6/M8/M10/M12



	No.	€
Thread-cutting set, 21 pcs.	A 245 006	

Thread-cutting set HSS in steel case













One round die \approx DIN EN 22568 HSS / M3 - M12

- + 1 hand tap set DIN 352 HSS / M3 M12
- + die stock DIN 225 25,0 x 9,0 mm
- + 1 tap wrench DIN 1814 Size 11/2
- + 1 screwdriver

	No.	€
Thread-cutting set, 31 pcs.	A 245 013	



Thread-cutting set HSS in plastic case









Hand tap set DIN 352 HSS / M3 - M12

- + one round die ≈ DIN EN 22568 HSS / M3 M12
- + die stock DIN 225 20,0 x 5,0 / 20,0 x 7,0 / 25,0 x 9,0 / 30,0 x 11,0 / 38,0 x 14,0 mm
- + twist drills DIN 338 type N HSS ground Ø 2,5 / 3,3 / 4,2 / 5,0 / 6,8 / 8,5 / 10,2 mm
- + tap wrench size 1 / size 2 DIN 1814
- + 1 steel tap wrench size 1
- + 1 screwdriver
- + 1 screw-pitch gauge

	No.	€
Thread-cutting set, 45 pcs.	A 245 021	





Thread-cutting set HSS in steel case











Hand tap set DIN 352 HSS / M3 - M12

- + one round die ≈ DIN EN 22568 HSS / M3 M12
- + die stock DIN 225 20,0 x 5,0 / 20,0 x 7,0 / 25,0 x 9,0 / 30,0 x 11,0 / 38,0 x 14,0 mm
- + tap wrench size 1 + 2 DIN 1814
- + 1 screwdriver
- + 1 screw-pitch gauge

	No.	€
Thread-cutting set, 37 pcs.	A 245 020	



Thread-cutting set HSS in steel case














- + one round die \approx DIN EN 22568 HSS / M3 M12
- + die stock DIN 225 20,0 x 5,0 / 20,0 x 7,0 / 25,0 x 9,0 / 30,0 x 11,0 / 38,0 x 14,0 mm
- + twist drills DIN 338 type N HSS-R \emptyset 2,5 / 3,3 / 4,2 / 5,0 / 6,8 / 8,5 / 10,2 mm
- + tap wrench size 1 + 2 DIN 1814
- + 1 screwdriver
- + 1 screw-pitch gauge

	No.	€
Thread-cutting set, 44 pcs.	A 245 030	



Thread-cutting set HSS in steel case













Hand tap set DIN 352 HSS / M3 - M20

- + one round die ≈ DIN EN 22568 HSS / M3 M20
- + die stock DIN 225 -

20,0 x 5,0 / 20,0 x 7,0 / 25,0 x 9,0 / 30,0 x 11,0 / 38,0 x 14,0 / 45,0 x 18,0 mm

- + tap wrench size 1 + 3 DIN 1814
- + 1 screwdriver
- + 1 screw-pitch gauge

	No.	€
Thread-cutting set, 54 pcs.	A 245 040	





Hand taps M DIN 352 HSS ground in plastic case

Taper tap: 5 - 6 thread chamfer Second tap: 4 - 5 thread chamfer Final tap: 2 - 3 thread chamfer

Thread: metric, DIN ISO 13 ISO 2 / 6H Tolerance: right hand cutting















M	Pitch mm	Thread core hole Ø mm	mm	→	No.	€
M 3	0,50	2,5	40,0	10,0	230 030 TX	
M 4	0,70	3,3	45,0	12,0	230 040 TX	
M 5	0,80	4,2	50,0	13,0	230 050 TX	
M 6	1,00	5,0	56,0	15,0	230 060 TX	
M 8	1,25	6,8	63,0	18,0	230 080 TX	
M 10	1,50	8,5	70,0	24,0	230 100 TX	
M 12	1,75	10,2	75,0	29,0	230 120 TX	
M 14	2,00	12,0	80,0	30,0	230 140 TX	
M 16	2,00	14,0	80,0	32,0	230 160 TX	
M 18	2,50	15,5	95,0	40,0	230 180 TX	
M 20	2,50	17,5	95,0	40,0	230 200 TX	

Round dies M DIN EN 22568 HSS ground in plastic case

Type: Thread: Type B closed, preslotted metric, DIN ISO 13

ISO - 6g Tolerance:

Surface: bright right hand cutting






















М	Pitch mm	Thickness mm	Outside Ø mm	No.	(E)
M 3	0,50	5,0	20,0	237 030 TX	
M 4	0,70	5,0	20,0	237 040 TX	
M 5	0,80	7,0	20,0	237 050 TX	
M 6	1,00	7,0	20,0	237 060 TX	
M 8	1,25	9,0	25,0	237 080 TX	
M 10	1,50	11,0	38,0	237 100 TX	
M 12	1,75	14,0	38,0	237 120 TX	
M 14	2,00	14,0	38,0	237 140 TX	
M 16	2,00	18,0	45,0	237 160 TX	
M 18	2,50	18,0	45,0	237 180 TX	
M 20	2,50	18,0	45,0	237 200 TX	



MACHINE TAPS





Machine taps M DIN 371 / 376 type B with progressive tap HSS ground

Machine taps with reinforced shank for through threads.

Chamfer: type B, 4 - 5 threads with progressive tap

metric, DIN ISO 13 Thread: relief-ground Flanks:













М	Pitch mm	Thread core hole mm	™	mm w	Ø shank mm	No.	€
M 3	0,50	2,5	56,0	11,0	3,5	232 030 TX	
M 4	0,70	3,3	63,0	13,0	4,5	232 040 TX	
M 5	0,80	4,2	70,0	16,0	6,0	232 050 TX	
M 6	1,00	5,0	80,0	19,0	6,0	232 060 TX	
M 8	1,25	6,8	90,0	22,0	8,0	232 080 TX	
M 10	1,50	8,5	100,0	24,0	10,0	232 100 TX	
M 12	1,75	10,2	110,0	28,0	9,0	232 120 TX	

Machine taps M DIN 371 / 376 type C / 35° righthand spiral flutes HSS ground

Machine taps with reinforced shank and 35° right-hand spiral flutes for bottoming.

Chamfer: type C / 35° right-hand spiral flutes, 2-3 threads

Thread: metric, DIN ISO 13 relief-ground Flanks:













M	Pitch mm	Thread core hole mm	mm	mm	Ø shank mm	No.	€
M 3	0,50	2,5	56,0	11,0	3,5	234 030 TX	
M 4	0,70	3,3	63,0	13,0	4,5	234 040 TX	
M 5	0,80	4,2	70,0	16,0	6,0	234 050 TX	
M 6	1,00	5,0	80,0	19,0	6,0	234 060 TX	
M 8	1,25	6,8	90,0	22,0	8,0	234 080 TX	
M 10	1,50	8,5	100,0	24,0	10,0	234 100 TX	
M 12	1,75	10,2	110,0	28,0	9,0	233 120 TX	

Machine tap set HSS, in plastic case





















	No.	€
M DIN 371 / 376 - type B / M3 - M12	A 245 057 TX	
M DIN 371 / 376 - type C / 35° RSP / M3 - M12	A 245 058 TX	



Machine taps M DIN 371 / 376 type B with progressive tap HSS ground

Machine taps with reinforced shank for through threads.

Chamfer: type B, 4 - 5 threads with progressive tap

metric, DIN ISO 13 Thread: Flanks: relief-ground













М	Pitch mm	Thread core hole mm	mm →	mm mm	Ø shank mm	No.	€
M 3	0,50	2,5	56,0	11,0	3,5	232 030 ETX	
M 4	0,70	3,3	63,0	13,0	4,5	232 040 ETX	
M 5	0,80	4,2	70,0	16,0	6,0	232 050 ETX	
M 6	1,00	5,0	80,0	19,0	6,0	232 060 ETX	
M 8	1,25	6,8	90,0	22,0	8,0	232 080 ETX	
M 10	1,50	8,5	100,0	24,0	10,0	232 100 ETX	
M 12	1,75	10,2	110,0	28,0	9,0	232 120 ETX	

Machine taps M DIN 371 / 376 type C / 35° righthand spiral flutes HSS ground



Chamfer: type C / 35° right-hand spiral flutes, 2-3 threads

Thread: metric, DIN ISO 13 Flanks: relief-ground
















Machine tap set HSSE-Co 5, in plastic case





















	No.	€
M DIN 371 / 376 - type B / M3 - M12	A 245 057 ETX	
M DIN 371 / 376 - type C / 35° RSP / M3 - M12	A 245 058 ETX	



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for ruko manufacturer:

Other Similar products are found below:

214214 214100 214036 202040E 208040 214049 214053 214096 214140 101021 101062 232-040 102146 102303E 241 001 242-207

102114E 102411 245001 242-205 116048 102771 102785 244201 A215214RO A215215RO 217-020 214057 202030E 214034 214044

214081 215030 232025 237-030 241-010 241-101 244200 A214215RO 241 102 217-315 214047 208050 214062 230025 102-114

A101038 109220 270015 245002