

---

## PARATHOM CLASSIC B 40 5.7 W/827 E14 FR

PARATHOM CLASSIC B | LED lamps, classic mini-candle shape



---

### Areas of application

- Domestic applications
- General illumination
- Chandeliers
- Outdoor applications only in suitable luminaires

---

### Product benefits

- Long lifetime of up to 15,000 h
- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

---

### Product features

- LED alternative to conventional lamps
- Mercury-free lamps



---

Technical data

**Electrical data**

Rated wattage	5.70 W
Nominal wattage	5.70 W
Nominal voltage	220...240 V
Operating frequency	50...60 Hz
Power factor $\lambda$	> 0.50
Claimed equiv. conventional lamp power	40 W

**Photometrical data**


Nominal luminous flux	470 lm
Rated luminous flux	470 lm
Color temperature	2700 K
Color rendering index Ra	$\geq 80$
Light color (designation)	Warm White
Standard deviation of color matching	$\leq 6$ sdcM

**Light technical data**

Warm-up time (60 %)	< 0.50 s
Starting time	0.0 s

**Dimensions & weight**

---



Overall length	106.0 mm
Diameter	35.0 mm
Outer bulb	B35
Length	106.0 mm

**Lifespan**

---

## Product datasheet

Nominal lamp life time	15000 h
Rated lamp life time	15000 h
Number of switching cycles	100000
Lumen main.fact.at end of nom.life time	0.70
Lumen maintenance at end of service life	0.70

### Additional product data

Base (standard designation)	E14
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Appropriate disposal acc. to WEEE	Yes
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/In development, data preliminary

### Capabilities

Dimmable	No
----------	----

### Certificates & standards


Energy efficiency class	A+
Energy consumption	6 kWh/1000h

### Country specific categorizations

ILCOS	DRBB/F-5,7-220-240-E14-38/110
Order reference	PCLB40 5,7W/827

### Light Distribution

---



Spectral power distribution



Guarantee

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899961951	PARATHOM CLASSIC B 40 5.7 W/827 E14 FR	Shipping carton box 10	205 mm x 87 mm x 123 mm	2.19 dm <sup>3</sup>	758.00 g

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Product datasheet

---

### References / Links

For further products and actual information concerning LED lamps see

- ▶ [www.ledvance.com/ledlamps](http://www.ledvance.com/ledlamps)

For Guarantee see

- ▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)
- 

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [ledvance](#) manufacturer:*

Other Similar products are found below :

[4058075091450](#) [4058075079274](#) [4058075122161](#) [4058075122260](#) [4058075079915](#) [4058075097520](#) [4058075097544](#) [4058075069176](#)  
[4058075091436](#) [4058075091511](#) [4058075079038](#) [4058075079212](#) [4058075106376](#) [4058075097421](#) [4058075097698](#) [4058075811812](#)  
[4052899961951](#) [4052899958173](#) [4058075091559](#) [4058075091573](#) [4058075122185](#) [4058075122222](#) [4058075122246](#) [4058075122284](#)  
[4058075097667](#) [4058075107625](#) [4058075078970](#) [4058075079298](#) [4058075106239](#) [4058075812697](#) [4058075812710](#) [4052899961807](#)  
[4058075091498](#) [4052899961654](#) [4058075114302](#) [4052899961722](#) [4052899961289](#) [4058075811454](#)