

ST-8920 - Pressure and Flow Meter



Accuracy	±0.3%FSO (25°C)		
Repeatability	±0.2% (Max.±0.5% FSO)		
Linearity/Hysteresis	±0.29% FSO		
Pressure Range	±5000Pa		
Maximum Pressure	10psi		
Response Time	0.5 Seconds typical		
Low Battery indicator	Yes		
Over range indicator	OL		
Under range indicator	-OL		
Operating Conditions	0 to 50.0°C		
Storage Conditions	-10 to 60°C / 14 to 140°F		
Zero Adjust and Offset	Yes		
Data Hold	Yes		
Max / Min / AVG	Yes		
measurement units, ranges, & resolution	Units	Range	Resolution
	inH ₂ O	20.07	0.01
	PSI	0.7252	0.0001
	mbar	50	0.01
	kPa	-	-
	hPa	-	-
	Pa	5000	1
	inHg	-	-
	mmHg	-	-
	ozin ²	-	-
	ftH ₂ O	-	-
	cmH ₂ O	-	-
	mmH ₂ O	509.8	0.1
kgcm ²	-	-	
bar	-	-	
Air Velocity	Range	Resolution	Accuracy
m/s(meter per second)	1-80.00	0.01	±2.5% of reading at 10.00m/s
ft/min(feet per minute)	200-15733	1	Accuracy is function of velocity and duct size
km/h(kilometers per hour)	3.5-288.0	0.1	
MPH(miles per hour)	2.25-178.66	0.01	
Knots(nautical miles per hour)	2.0-154.6	0.1	
Air Flow	Range	Resolution	
CFM	0-99.999ft ³ /min	0.0001 to 100	
CMM	0-99.999m ³ /min	0.001 to 100	
Temperature	Range	Accuracy	Resolution
°C	0 to 50.0°C	±1.0°C	0.1°C
°F	32.0 to 122.0°F	±2.0°F	0.1°F

Remarks: If find any query of the above, please refer to our manual for details or contact us

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [tenma manufacturer](#):

Other Similar products are found below :

[21-10164](#) [21-10158](#) [72-7715](#) [BC0024434](#) [72-7712](#) [76-009](#) [76-081](#) [CBB019217](#) [CBB018722](#) [76-024](#) [72-13668](#) [72-13686](#) [72-13688](#) [72-13736](#) [72-13742](#) [72-13818](#) [72-13822](#) [72-13824](#) [72-13836](#) [72-13856](#) [72-13858](#) [72-13872](#) [72-13874](#) [72-13908](#) [72-13950](#) [72-13986](#) [72-14060](#) [72-14302](#) [72-3099](#) [76-1448](#) [76-1556](#) [76-019](#) [72-14400](#) [72-13762](#) [72-13812](#) [72-13826](#) [72-13832](#) [72-13888](#) [72-13942](#) [72-14008](#) [72-14014](#) [72-14048](#) [72-14148](#) [72-14230](#) [72-14334](#) [72-17175](#) [72-2655](#) [72-7615](#) [76-097](#) [72-9490](#)