

Dual Wall Tubing

Polyolefin, Skid Proof, Heat Shrink

pro-POWER

RoHS
Compliant



Description

It is Widely used in various fishing tackles, sport fittings, Equipment and commodities with hand device.

Specifications

Operating temperature : -55°C to +105°C
 Minimum Full Recovery Temperature : 110°C
 Minimum shrink temperature : 70°C
 Colour : Black
 Good Flexibility, Abrasion Resistant and Anti-Skid Performance

Technical Data

Property	Test Method	Typical Data
Tensile Strength	ASTM D 412	10.4Mpa
Longitudinal Elongation	ASTM D 412	≤8%
Elongation	ISO 1210	200%

Product Dimensions

Part Number	Size	As supplied		After recovery	
	Inch	Internal Diameter(mm)	Average Thickness	MAX Internal Diameter (mm)	Average Thickness
PP002010	20	≥20	0.5 ±0.15	11	0.9 ±0.15
PP002011	25	≥25	0.5 ±0.15	14.5	1 ±0.15
PP002012	30	≥30	0.6 ±0.15	17.5	1.2 ±0.15

Part Number Table

Description	Part Number
Tubing, Skid proof, Heat Shrink, Dual Wall, 20mm, Black, 1.6m	PP002010
Tubing, Skid proof, Heat Shrink, Dual Wall, 25mm, Black, 1.6m	PP002011
Tubing, Skid proof, Heat Shrink, Dual Wall, 30mm, Black, 1.6m	PP002012

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com
 www.farnell.com
 www.newark.com
 www.cpc.co.uk

pro-POWER

X-ON Electronics

Authorized Distributor

Click to view similar products for [Pro Power manufacturer](#).

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)