

THB.392.R4A

Micro XDry series anti condensation power distributor, 1 input 3 output, sealed interconnections, IP68



SPECIFICATION

Cable Entries	4
Number of Poles	4
Terminal Type	Screw
Body Material	PA66 GF UL94V0 / UL94 V2, Caps / TPE Seals
Colour	Black and green
IP Rating	68
Max Conductor Size (Sq mm)	4
Max Current (A)	15
Max Voltage (V)	450
Minimum Temp Rating °C	-40
Max Temp Rating °C	125
Minimum Cable Diameter (mm)	8
Maximum Cable Diameter (mm)	12
Depth (mm)	28
Fixing System	Screw
Length (mm)	80
Temperature "T" Rating	T85
Width (mm)	54

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [hylec manufacturer](#):

Other Similar products are found below :

[LN167001](#) [50.625 PA/3X7](#) [50.620 PA/R](#) [DESTB-1003](#) [THB.406.A1G](#) [THB.387.A4A.R](#) [K150-1032-00](#) [THB.380.3ASSY](#)
[GHG9601955R0004](#) [THB.381.M2A](#) [K151-1032-00](#) [HYKS-07612PP](#) [THB.382.A1A-KIT](#) [THB.390.A1AKIT](#) [THK.404.X2A00-F](#)
[PA244SKIT](#) [50.216 ES](#) [50.616M/EMVDL-F](#) [50.625 ES](#) [THB.387.A3A](#) [THB.405.A2A](#) [50.220 M-F](#) [HY435/12 FV](#) [THB110A6B-F](#) [50.216](#)
[M-F](#) [THB.387.B5A](#) [5625////1121](#) [THB.405.A2G](#) [THA.209.A1A](#) [K257-1012-00](#) [6000302CC](#) [TTK25BK-SD-F](#) [TTK20GY-SD-F](#) [DESTB-](#)
[0403](#) [THB.399.E3A-KIT](#) [50.625 PA/RSW](#) [HY508/3 V/3F](#) [5665/221](#) [THR.384.S3A](#) [THB.387.D4A](#) [THB.387.B4A](#) [THR.405.S5A](#)
[THB.387.A5A](#) [THB.387.C5A](#) [THB.387.D3A](#) [50.625 M/EMVDL-F](#) [THK.200.3T](#) [K160-1040-00](#) [6000337BC](#) [GHG9601955R0022](#)