

- Universal input voltage
- Compact and light weight
- Efficiency level VI
- Mains cord not included
- Exchangeable DC plugs
- Universal inngangsspenning
- Kompakt enhet, lett vekt
- Effektivitetsnivå VI
- Nettledning ikke inkludert
- Utskiftbare DC plugger



**Technical specifications**

**Tekniske data**

|                              |                               |                                                                                         |
|------------------------------|-------------------------------|-----------------------------------------------------------------------------------------|
| Input voltage:               | Inngangsspenning:             | 90-264 VAC, 50/60 Hz                                                                    |
| Line frequency:              | Frekvensområde:               | 47-63 Hz                                                                                |
| Max. output power:           | Maks. utgangseffekt:          | 40 W                                                                                    |
| Load regulation:             | Lastregulering:               | 3-5 %                                                                                   |
| Mains regulation:            | Linjeregulering:              | < 1%                                                                                    |
| Ripple:                      | Rippel:                       | 2% max                                                                                  |
| Efficiency, approx.:         | Virkningsgrad, ca.:           | >85,3% (avg. of 25,50,75 and 100% load)                                                 |
| Standby power:               | Tomgangseffekt:               | ≤ 0,3 W                                                                                 |
| Hold up time:                | Hold up time:                 | 10 ms (min)                                                                             |
| Temperature range            | Temperaturområde              |                                                                                         |
| • Operating:                 | • Drift:                      | -20°C - +40°C                                                                           |
| • With derating:             | • Med derating:               | +70°C                                                                                   |
| • Storage:                   | • Lagring:                    | -40°C - +85°C                                                                           |
| Derating:                    | Derating:                     | 0,67W/°C over 40°C                                                                      |
| Insulation class:            | Isolasjonsklasse:             | I                                                                                       |
| Insulation voltage           | Isolasjonsspenning            |                                                                                         |
| • Primary - secondary:       | • Primær - sekundær:          | 4242VDC (min)                                                                           |
| Safety:                      | Sikkerhet:                    | EN 60950                                                                                |
| EMC standards                | EMC standarder                |                                                                                         |
| • Emission:                  | • Emisjon:                    | EN 61000-6-3                                                                            |
| • Immunity:                  | • Immunitet:                  | EN 61000-6-1                                                                            |
| Reliability (MIL-HDBK-217F): | Pålitelighet (MIL-HDBK-217F): | MTBF > 100.000 hrs at 25°C                                                              |
| Input terminal:              | Inngangsterminal:             | 3-pin IEC-320 C14connector                                                              |
| Output terminal:             | Utgangsterminal:              | 1,2 m cable with exchangeable output plug<br>1,2 m sekundærledning med utskiftbar plugg |
| Dimensions (LxWxH):          | Ytre mål (LxBxH):             | 107 x 47 x 30 mm                                                                        |
| Weight:                      | Vekt:                         | 210 g                                                                                   |

**Voltage versions - Spenningsversjoner**

| Output (V)<br>Utgang (V) | Max. current (A)<br>Maks. strøm (A) | Max. output power (W)<br>Maks. utgangseffekt (W) |
|--------------------------|-------------------------------------|--------------------------------------------------|
| 12                       | 3,33                                | 40                                               |
| 24                       | 1,66                                | 40                                               |

**Safety approvals - Godkjenninger**



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [mascot manufacturer](#):*

Other Similar products are found below :

[6323125000](#) [5060 24/12V](#) [6323245000](#) [6320125000](#) [6321245000](#) [018126](#) [6322245000](#) [018127](#) [018128](#)