

- Universal input voltage
- Compact and light weight
- Efficiency level VI
- Mains cord not included
- Exchangeable DC plugs
- Universal inngangsspenning
- Kompakt enhet, lett vekt
- Effektivitetsnivå VI
- Nettledning ikke inkludert
- Utskiftbare DC plugger



**Technical specifications**

**Tekniske data**

Input voltage:	Inngangsspenning:	90-264 VAC, 50/60 Hz
Line frequency:	Frekvensområde:	47-63 Hz
Max. output power:	Maks. utgangseffekt:	60 W
Load regulation:	Lastregulering:	4-5 %
Mains regulation:	Linjeregulering:	< 1%
Ripple:	Rippel:	2% max
Efficiency, approx.:	Virkningsgrad, ca.:	>87% (avg. of 25,50,75 and 100% load)
Standby power:	Tomgangseffekt:	≤ 0,5 W
Hold up time:	Hold up time:	10 ms (min)
Temperature range	Temperaturområde	
• Operating:	• Drift:	-20°C - +40°C
• With derating:	• Med derating:	+70°C
• Storage:	• Lagring:	-40°C - +85°C
Derating:	Derating:	1W/°C over 40°C
Insulation class:	Isolasjonsklasse:	I
Insulation voltage	Isolasjonsspenning	
• Primary - secondary:	• Primær - sekundær:	4242VDC (min)
Safety:	Sikkerhet:	EN 60950
EMC standards	EMC standarder	
• Emission:	• Emisjon:	EN 61000-6-3
• Immunity:	• Immunitet:	EN 61000-6-1
Reliability (MIL-HDBK-217F):	Pålitelighet (MIL-HDBK-217F):	MTBF > 100.000 hrs at 25°C
Input terminal:	Inngangsterminal:	3-pin IEC-320 C14connector
Output terminal:	Utgangsterminal:	1,2 m cable with exchangeable output plug 1,2 m sekundærledning med utskiftbar plugg
Dimensions (LxWxH):	Ytre mål (LxBxH):	118 x 47 x 30 mm
Weight:	Vekt:	260 g

**Voltage versions - Spenningsversjoner**

Output (V) Utgang (V)	Max. current (A) Maks. strøm (A)	Max. output power (W) Maks. utgangseffekt (W)
12	5	60
24	2,5	60

**Safety approvals - Godkjenninger**



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [mascot manufacturer](#):*

Other Similar products are found below :

[6323125000](#) [5060 24/12V](#) [6323245000](#) [6320125000](#) [6321245000](#) [018126](#) [6322245000](#) [018127](#) [018128](#)