

Plug-in 130 Series		Plug-in PIN-strip for 130 Series		In-line 950 Series	
<ul style="list-style-type: none"> ● Plug-in solution at low cost ● 5mm pitch ● Modular interlocking construction 		<ul style="list-style-type: none"> ● Vertical mounting ● 5mm pitch 		<ul style="list-style-type: none"> ● Plug-in headers ● 5.08mm pitch ● Rising clamp mechanism 	
Part number	20.130/**	Part number	20.130/PS	Part number	21.950/**
Number of poles	2-12 poles	Number of poles	Strips of 24	Number of poles	2-24 poles
**Insert required No. of poles				**Insert required No. of poles	

Ratings

	UL 1059	CSA 22.2 No.158	DIN VDE 0627		UL 1059	CSA 22.2 No.158	DIN VDE 0627		UL 1059	CSA 22.2 No.158	DIN VDE 0627
Rated voltage	300 V	300 V	250 V	Rated voltage	300 V	300 V	250 V	Rated voltage	300 V	300 V	250 V
Rated current	10 A	10 A	10 A (T60)	Rated current	10 A	10 A	10 A (T60)	Rated current	15 A	15 A	12 A (T60)
Wire size	AWG 22-14	AWG 22-14	1.5mm ²	Rating impulse voltage/dirt level	4.0 kV/3			Wire size	AWG 22-12	AWG 22-12	2.5mm ²
Rating impulse voltage/dirt level	4.0 kV/3			Rated torque/screw size	0.4 Nm/M2.6			Rating impulse voltage/dirt level	4.0 kV/3		
Rated torque/screw size	0.4 Nm/M2.6							Rated torque/screw size	0.5 Nm/M3		

Maximum rated cross section

Single wire (solid)	1.5mm ²	Single wire (solid)	2.5mm ²
Stranded wire (flexible)	1.0mm ²	Stranded wire (flexible)	2.5mm ²
Stranded wire with Ferrules	1.0mm ²	Stranded wire with Ferrules	2.5mm ²

Materials

Insulating material	PA	Insulating material	PA	Insulating material	PA
Flammability class	UL94 V-0	Flammability class	UL94 V-0	Flammability class	UL94 V-0
Temperature range	-30°C/+105°C	Temperature range	-30°C/+105°C	Temperature range	-30°C/+105°C
Terminal block	CuZn	Contact PIN	CuZn	Terminal block	CuZn
Wire guard	CuBe			Contact	CuSn
Colour		Colour		Colour	
Grey	RAL 7016	Black	RAL 9011	Green	RAL 6018

Dimensions

Spacing	5.0mm	Spacing	5.0mm	Spacing	5.08mm
Stripped length	6.0mm	PCB hole diameter	1.5mm	Stripped length	6.0mm
Options: ● 10.0mm PIN pitch		Options: ● 10.0mm PIN pitch		Options: ● 5.0mm, 7.62mm PIN pitch	
● Printed terminals		● Horizontal mounts		● Printed terminals	
				● Coding	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for imo manufacturer:

Other Similar products are found below :

[20.155MV/12-E](#) [MC14N-S-10110AC](#) [MB09-S-10=24](#) [DPS-1-030-24](#) [SRF-1C-SL-12VDC](#) [MB09-S-1024](#) [LDC18RRS](#) [SFSYE0111](#)
[21.1500M/6-E](#) [20.3304M/2-E](#) [21.910M/5-E](#) [20.95MA/2-E](#) [21.95MHF/2-E](#) [PE69-4032](#) [DPS-1-060-24](#) [CS20A-A2](#) [CS20A-U1](#) [VFC02](#)
[MSSTC11DA06](#) [20.95MHF/3-E](#) [B3T10](#) [XKL-040-21](#) [20.3304M/4-E](#) [SRDH-1A-SL-24VDC](#) [20.2500M/5-E](#) [21.155MH/12](#) [SRRHN-2CN-](#)
[SL-12VDC](#) [20.920M/5-E](#) [MC10N-S-10110AC](#) [21.1550MF/8-E](#) [20.910M/6-E](#) [20.95MH/3-E](#) [21.95MV/3](#) [MA05-S-01230AC](#) [SRRHN-2CN-](#)
[SL-5VDC](#) [LB69-4040](#) [20.3001M/6](#) [21.1500M/3-E](#) [SFSYE0311](#) [21.95MHF/6-E](#) [20.95MV/2-E](#) [20.155MV/4-E](#) [20.155MH/4-E](#) [20.950M/2-E](#)
[MT5 1-50-FAR](#) [BS3P3REDO](#) [MB12-S-10=24](#) [MA05-S-1024DC](#) [20.155MVF/8-E](#) [20.2500MV/8-E](#)