Low Ohmic Resistor SMD

for current sense - thick film

Meggitt CGS

Key features

- up to 1 watt at 70°C •
- values down to R10
 - supplied on tape •
- ideal for current sensing
 - value marked •
 - packaged on 7" reels •
- custom designs available
 - attractive pricing •



						Electrical
	Туре	Power Rating	Maximum Working Voltage	Resistance Range (ohms)		Operating
				F (± 1%)	G (± 2%)J(± 5%)	Temperature
				E-96, E-24	E-24	Range
	RL73 2A	0.125W	1.11V	R20 ~ 10R		
	KL75_2A				R10 ~ 10R	- -55°C to +125°C
	RL73_2B	0.25W	1.58V	R20 ~ 10R		
		0.23 W			R10 ~ 10R	
	RL73_2E	0.5W	2.23V	R20 ~ 10R		
					R10 ~ 10R	
	RL73_2H	0.75W	2.73V	R20 ~ 10R		
					R10 ~ 10R	
	RL73_3A	1.0W	3.16V	R20 ~ 10R		
					R10 ~ 10R	
				1	1	

Rated AmbientTemperature +70°C

+ 0.2

Type


Temperature Coeffificent of Resistance

Resistors with 1% tolerance will have a TCR of 100ppm/°C Resistors with 2% or 5% tolerance will have a TCR of 200ppm/°C

Recommended Circuit Board Design

If this device is anticipated to run at full continuous power then action to improve the cooling should be taken. This can be a metal substrate, copper pad left under the chip or an opening in the PCB.

Dimensions



How to Order

ensions (
$C \pm 0.3$	D ± 0.1	${f d}^{+0.2}_{-0.1}$	_
0.4	0.5	0.3	w/7
0.5	0.6	0.4	
0.5	0.6	0.4	D
0.5	0.6	0.4	
0.5	0.6	0.4	d C
	C ± 0.3 0.4 0.5 0.5 0.5	$\begin{array}{ccc} 0.5 & 0.6 \\ 0.5 & 0.6 \\ 0.5 & 0.6 \end{array}$	C \pm 0.3 D \pm 0.1 d $\stackrel{+0.2}{_{0.1}}$ 0.4 0.5 0.3 0.5 0.6 0.4 0.5 0.6 0.4 0.5 0.6 0.4 0.5 0.6 0.4

RL73 2A	2.0	1.25	0.4	0.5	0.3
RL73 2B	3.2	1.6	0.5	0.6	0.4
RL73 2E	3.2	2.6	0.5	0.6	0.4
RL73 2H	5.0	2.5	0.5	0.6	0.4
RL73 3A	6.3	3.1	0.5	0.6	0.4
				2.0	

RL73	K	2A	1R0	G	TD
Common Part	T.C.R.	Chip Size	Resistance Value	Tolerance	Pack Style
KL/3	K - 200ppm (±2%/5%ToD	200mm 2E - 12:10	0.1 ohm (100 milli ohms) R10 1.0 ohm (1000 milli ohms) 1R0	$G = \pm 2\%$	TG - Cut Tape Lengths TE - 4000 Reel TD - 5000 Reel TP - 10000 Reel

SMD Resistors

type RL73 series

The RL73 series has a special metal glaze resistive element and a barrier layer beneath the solder to extend terminal life. This product satisfies the demand for a low ohmic shunt resistor to act as a current sensor. We can offer sizes and tighter tolerances as "specials" where demand justifies. $A \pm 1\%$ is offered between the resistance values 200 milli ohms and 10 ohms.

> Packaging: 4000 Pieces (7" Reel) 5000 Pieces (7" Reel) 10000 Pieces (13" Reel)

Please Request Full Data Sheet F0744



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for te connectivity manufacturer:

Other Similar products are found below :

570416-000 CLTEQ-M81CE-SSRELAY-4-20V D38999/24FJ4AN 358838-000 4-1195131-0 650069-000 SMD100-2 CB-1022B-78 RM707012 RP410012 MMS42 1-640426-8 2EDL4CM DTS20W19-11PD-3028-LC RM202615 NC6-P104-06 MSPS103B DTS26F21-41AE DTS26F21-41PE-LC DTS26F21-11SE-3028-LC 1932144-1 293545-4 LVR125S MS27466T25F4PB CKB-38-78010 1206SFF150F/63-2 D38999/20JB35HA D38999/24WJ20PA 1754138-1 TE1500A2R2J DTS24F25-29PC-3028-LC D38999/24WG11HA D38999/24WG11HN MS27467T21F11H DJT16E21-11HA 1206SFH150F/24-2 DTS24F19-11SC-3028-LC DTS24F21-41HN-LC DTS24F21-41AN DTS24F21-41PN-LC RP330024 MS27467T21F35J MS27467T21F11J MS27467T21F16H-LC MS27467T21F35H MS27467T21F41H-LC DJT16E21-11PA-LC DJT16E21-11HA-LC DJT16E21-11AA MS27467T21B11JA