

10

GENERAL TOOLING

METROLOGY

▼ WIDE-ARC PROTRACTOR

**DELA.1880.00**

- Rule length 400 mm.
  - Hardened steel.
  - Open protractor for angle readings 10 to 170°.
  - Protractor Ø 200 mm.
  - Degree graduations.
  - Sliding rule with locking screw.
- ΔΔ: 420 g.



▼ BASIC BEVEL PROTRACTOR

**DELA.1897.02**

- Stainless steel, without acute angle attachment.
  - Accurate to within 5 minutes of arc.
  - Length 300 mm.
  - Supplied in a case 370 x 145 x 35 mm.
- ΔΔ: 400 g.



▼ PRECISION BEVEL PROTRACTOR

**813B.S**

- Hardened stainless steel
  - Anti-glare matt chrome finish
  - Measuring range 0 to 360°.
  - Minimum vernier reading 5 minutes of arc.
  - Dimensions 315 x 75 x 20 mm.
  - Vernier diameter 70 mm.
  - Body graduated in four 90° sectors
  - Rotating dial with vernier.
  - Dial locking screw.
- 315 mm and 200 mm rules with 45° and 60° bevelled ends.
- 90 mm offset rule for small angles.
  - Sliding rule locking screw.
  - x10 magnification.
  - Cast iron support base.
  - Complete with a fitted rigid case 335 x 125 x 47 mm.
- ΔΔ: 1.445 kg.



**FEELER GAUGES**

▼ LONG METRIC FEELER GAUGES

- Rounded tips.



	Number of blades	Blade length mm	Blade width mm	Blade thickness in 1/100 mm	ΔΔ g
<b>804.L</b>	19	150	10	4-5-6-7-8-9-10-15-20-25	100
<b>804.SL</b>	19	250	10	30-35-40-50-60-70-80-90-100	210



▼ METRIC FEELER GAUGES

- Blade length 90 mm.

	Number of blades	Blade profile	Width x length of blades in mm	Blade thickness in 1/100 mm	ΔΔ g
<b>804</b>	19		10 x 90	4-5-6-7-8-9-10-15-20-25-30	60
<b>804.P</b>	19		10 x 90	35-40-50-60-70-80-90-100	60



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [facom](#) manufacturer:*

Other Similar products are found below :

[92A.5,5](#) [ARB.5.5X40](#) [ANXR10X75](#) [AEF.J6](#) [AEF.J1](#) [EH.107](#) [256.2.5](#) [MT.J3](#) [986058](#) [75.10](#) [84E.J1](#) [455B](#) [440.19](#) [44.6X7](#) [440.21](#) [R.306-25D](#) [R.217](#) [R.5](#) [J.13LA](#) [431.LE](#) [425.E](#) [R.216](#) [601](#) [AEF.1,5X35](#) [AEX.9X75](#) [AEX.7X35](#) [EH.103](#) [EH.102](#) [251A.2.5](#) [HB.2B](#) [75.7](#) [440.20](#) [435.E](#) [432.LMT](#) [44.12X13](#) [440.5H](#) [440.22](#) [R.304DA](#) [427.MT](#) [251A.3](#) [AEF.1,8X35](#) [440.30](#) [440.18](#) [440.8](#) [R.4](#) [J.19LA](#) [44.JE8](#) [417.PE](#) [416.PE](#) [S.208](#)