

# Television Coaxial Cable

## Low Loss Air Spaced 75Ω

pro-POWER

### Features:

- Low loss general purpose TV download cable with 5-cell air spaced polyethylene insulated
- 1/1.0 plain solid copper conductor with plain copper braid screen
- Sheathed overall in brown PVC
- These 75Ω coaxial cables are used for the reception of UHF analogue and digital signals broadcast from terrestrial transmitters
- The cable range is designed for use in areas where the signal level is average to strong



### Specifications:

Inner conductor nominal diameter	1 Cu
Dielectric nominal diameter	4.8 Semi airspaced PE
Outer conductor nominal diameter	5.25 Cu braid
Outer sheath nominal diameter	6.5 PVC

### Mechanical Properties

Maximum bending radius: single bend	25
-------------------------------------	----

### Electrical Properties

Nominal DC resistance Ω/Km inner (outer) conductor	25 (24)	
Nominal characteristic impedance (Ω)	75	
Nominal capacitance (pF/m)	55	
Minimum RLR (dB)	10 - 450MHz 451 - 1,000MHz 1,001 - 1,800MHz	20 18 17
Minimum screening effectiveness (dB)		45
Nominal attenuation ±5% dB/100m	5MHz 50MHz 100MHz 200MHz 450MHz 600MHz 860MHz 1,000MHz	1.7 5.4 7.8 11.2 17.2 20 24.4 26.4

### Part Number Table

Description	Part Number
Cable, Coaxial, TV, 75R	268770

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com  
www.farnell.com  
www.newark.com  
www.cpc.co.uk

pro-POWER

# X-ON Electronics

Authorized Distributor

*Click to view similar products for [Pro Power manufacturer](#).*

Other Similar products are found below :

[PPCY4C075100M](#) [PPCY3C10050M](#) [PPC217](#) [PP001328](#) [PP001316](#) [PP001109](#) [PP001088](#)

[PP000940](#) [PP030](#) [PP000909](#) [PP001326](#) [PP001308](#) [PP000877](#) [PP000868](#) [PP000704](#)

[PP001163](#) [PP001156](#) [PP001085](#) [PP000510](#) [PP001076](#) [PP000944](#) [PP000914](#) [PP000407](#)

[PP000386](#) [PP000870](#)