



## Y.105B

- Capacity  $\varnothing$  5 mm aluminium rivets and  $\varnothing$  4 mm steel rivets.
  - Grips shaped for optimum comfort.
  - Return-spring to closed position prevents loss of rivet.
  - Cushioning system when pin snaps.
  - Supplied with 3 nosepieces  $\varnothing$  3 to 3.2 mm - 4 mm - 4.8 to 5 mm.
  - Knurled nosepieces for hand-fitting.
-  632 g.



▼ Dessins Techniques



Zoom



Y.105B

▼ Données Techniques

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [facom](#) manufacturer:*

Other Similar products are found below :

[92A.5,5](#) [ARB.5.5X40](#) [ANXR10X75](#) [AEF.J6](#) [AEF.J1](#) [EH.107](#) [256.2.5](#) [MT.J3](#) [986058](#) [75.10](#) [84E.J1](#) [455B](#) [440.19](#) [44.6X7](#) [440.21](#) [R.306-25D](#) [R.217](#) [R.5](#) [J.13LA](#) [431.LE](#) [425.E](#) [R.216](#) [601](#) [AEF.1,5X35](#) [AEX.9X75](#) [AEX.7X35](#) [EH.103](#) [EH.102](#) [251A.2.5](#) [HB.2B](#) [75.7](#) [440.20](#) [435.E](#) [432.LMT](#) [44.12X13](#) [440.5H](#) [440.22](#) [R.304DA](#) [427.MT](#) [251A.3](#) [AEF.1,8X35](#) [440.30](#) [440.18](#) [440.8](#) [R.4](#) [J.19LA](#) [44.JE8](#) [417.PE](#) [416.PE](#) [S.208](#)