

Vermason		Product Information	No: PIS 042	
	Page 1 of 1	Issue No 4	Date May 2003	Approved by

EARTH BONDING POINT BAR

Code J6501 to J6535
Farnell Part No 433-147 / 433-160

- The EBP bar should be fixed to the edge of a bench or other suitable work equipment within reach and accessible to all connecting ground cords, but where it is unlikely to be knocked and damaged or hinder the operator.
- Mount EBP bar with two M5 pan-head screws, minimum 12mm long
- Connect earthing cord to a suitable earth. A spare ring terminal is supplied if the cord needs to be shortened.
- The bar is 72 x 37 x 38mm in size and is made of ABS. It can be supplied in grey or yellow. The yellow bar has a rear cover to prevent access to the resistors.
- The bars are available with a variety of connectors: 4, 7 or 10mm stud 4mm female or male safety socket. Maximum three connectors per bar.
- Resistors are usually built-in to each connector. The resistors are $1M\Omega \pm 5\%$ rated at 1W. They will withstand 500V DC for over 6 minutes.

For further information, please contact
Vermason Ltd, 1 Avenue One, Letchworth, Hertfordshire SG6 2HB. UK
Tel: +44(0)1462 672005 Fax: +44(0)1462 670440
e-mail : sales@vermason.co.uk
www.vermason.co.uk

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [vermason](#) manufacturer:

Other Similar products are found below :

[203015](#) [237670](#) [230260](#) [238711](#) [35594](#) [230660](#) [072425B](#) [50424](#) [242296](#) [229775](#) [J6609](#) [VER-29082](#) [47200](#) [231725](#) [231250](#) [242270](#) [47201](#)
[230480](#) [203065](#) [237200](#) [229100](#) [249205](#) [230310](#) [229795](#) [230647](#) [230370](#) [231275](#) [237675](#) [231280](#) [35267](#) [242278](#) [231345](#) [35595](#) [229135](#)
[230646](#) [VER-26457](#) [230420](#) [35592](#) [35622](#) [241030](#) [241100](#) [ASBB4](#)