

Portable Replacement Tips and O-Rings

Soldapullt® Part No.	Tip Part No.	Tip Image	i.d.	L	Replacement O-Ring Part No.
AS196	LS197		.136" (3.4mm)	.53" (13.5mm)	ODS31
DS017	SRT12		.136" (3.4mm)	.53" (13.5mm)	ODS31
DS017LS	LS197		.136" (3.4mm)	.53" (13.5mm)	ODS31
DS117	SRT12		.136" (3.4mm)	.53" (13.5mm)	OA193 & ODS31
DS317	LS197		.136" (3.4mm)	.53" (13.5mm)	OA195 & ODS31
DS517	LS561		.098" (2.5mm)	.53" (13.5 mm)	OA197
PT109	SRT12		.136" (3.4mm)	.53" (13.5mm)	OSB32
PT209	MRT16		.098" (2.5mm)	.53" (13.5mm)	OSB32
PT409	LS197		.136" (3.4mm)	.53" (13.5mm)	OSB32
SS011	LS363A		.136" (3.4mm)	.53" (13.5mm)	OS130
SS102	LS364A		.098" (2.5mm)	.53" (13.5mm)	OS130
SS343	LS915		.070" (1.8mm)	.53" (13.5mm)	OS130
SS350	LS363		.136" (3.4mm)	.53" (13.5mm)	OS130
SS750LS	LS751		.107" (2.7mm)	.50" (12.7mm)	OS130
US140	SRT12		.136" (3.4mm)	.53" (13.5mm)	ODS31
US340	LS197		.136" (3.4mm)	.53" (13.5mm)	ODS31

Maintenance Tip: Use OL111 O-Ring lube for lubrication and longer tool life



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [edsyn manufacturer](#):

Other Similar products are found below :

[LN 261](#) [LN270](#) [SW021/2,0/30](#) [PUK 10 ALL](#) [SLT01](#) [ST706](#) [MA10LS](#) [MA 1070](#) [OS130](#) [SU8500-S5](#) [SS 350 G CHALLENGER](#) [AN122](#)
[FXM5002](#) [SR670](#) [ZD12](#) [FXS5008](#) [ET110](#) [MA10](#) [SAC5250](#) [CB138](#) [SP 375 B](#) [LS363](#) [OL111](#) [AS196](#) [CS468-1](#) [HS307](#) [LT382LF](#) [FL911](#)
[SAC1250-3](#) [SA8250](#) [WL675](#) [FL 19 222](#) [SS8500](#) [SP 625 B](#) [RB641](#) [HS106BC](#) [HS106BC-5](#) [SA1250](#) [PT109](#) [SAC5250-3](#) [SC8250](#) [SP 250 B](#)
[SP 500](#) [LP 20 PIXTER](#) [SC1250](#) [LN 260 B](#) [LT392LF](#) [LT394](#) [SW2.5/15](#) [ALM 2010](#)