



- Ground cord used to connect mats to (Earth Bonding Point) plugs
- One end terminated with female snap socket; other end with M5 ring terminal
- 1 megohm (1 x 10⁶ ohms) current limiting resistor in socket end
- 2.5mm cord diameter
- PVC insulation with 7 ends duplex tinsel copper conductor

Item #	Description
VER-26972	CORD,STRAIGHT,0.7M,10MMSOCKET/ M5 RING TERMINAL

"EPA ground cords shall be used to make electrical connections between groundable points and the EPA ground facility.

Where a single resistor is used in the EPA ground cord, this shall be located near the groundable point. Where more than one resistor is used, a resistor of a minimum resistance value of one half the total resistance shall be located near the groundable point.

When accessible, the EPA ground cord and its groundable point connection shall be shrouded by insulating material." (EN 61340-5-1 section 5.3.4 EPA ground cords)

Unless otherwise noted, tolerance is ±10% Specifications and procedures subject to change without notice.





Straight Cord, 10mm Socket, M5 Ring Terminal

VERMASON

UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH, HERTS, SG6 2TD UK

PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440 E-MAIL:Service@Vermason.co.uk, INTERNET: Vermason.co.uk

Drawing Number VER-26972

DATE: September 2015

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for vermason manufacturer:

Other Similar products are found below:

203015 237670 230260 238711 35594 230660 072425B 50424 242296 229775 J6609 VER-29082 47200 231725 231250 242270 47201 230480 203065 237200 229100 249205 230310 229795 230647 230370 231275 237675 231280 35267 242278 231345 35595 229135 230646 VER-26457 230420 35592 35622 241030 241100 ASBB4