

Anti-static series electronics pliers






Compact models for manoeuvrability


▷ ISO 9654, DIN ISO 9654, NF ISO 9654.

- Slimmer bullet-nose profile combines cutting performance with manoeuvrability.

- Model 405 is suitable for cutting piano wire \varnothing 0.4 mm.

$\Delta\Delta$: 65 g.

|  | Cut | Cu - Ni wire \varnothing mm | Fe wire 30 HRc \varnothing mm |
|--|---|----------------------------------|---|
| 405.E |  | 0,3 - 1,3 | 0,7 |
| 406.E |  | 0,1 - 1,3 | 0,7 |
| 407.E |  | 0,1 - 1,3 |  |






Stocky models for versatility


▷ ISO 9654, DIN ISO 9654, NF ISO 9654.

- Clean cut in a variety of materials, from copper to piano wire \rightarrow 0.5 mm.

- Available with offcut retaining system.

$\Delta\Delta$: 65 g.

|  | Cut | Cu - Ni wire \varnothing mm | Fe wire 30 HRc \varnothing mm | Offcut retainer |
|--|---|----------------------------------|------------------------------------|--------------------|
| 405.10E |  | 0,3 - 1,4 | 0,8 | |
| 405.10RE |  | 0,3 - 1,2 | 0,7 | • |








Long-reach models for accessibility


▷ ISO 9654, DIN ISO 9655, NF ISO 9654.

- Up to 1.5 to 2 mm more reach than standard cutting pliers

- Available with offcut retaining system.

$\Delta\Delta$: 65 g.

|  | Cut | Cu - Ni wire \varnothing mm | Fe wire 30 HRc \varnothing mm | Offcut retainer |
|--|---|----------------------------------|---|--------------------|
| 425.E |  | 0,1 - 1,3 |  | |
| 435.E |  | 0,1 - 1,3 | 0,7 | |
| 435.RE |  | 0,1 - 1,2 | 0,7 | • |







Slim-nose models with back clearance


▷ ISO 9654, DIN ISO 9655, NF ISO 9654.

- For cutting behind components and reaching under obstacles such as coils or resistors.

- Anti-static user-comfort type only.

$\Delta\Delta$: 65 g.

|  | Cut | Cu - Ni wire \varnothing mm | Fe wire 30 HRc \varnothing mm |
|--|---|----------------------------------|---|
| 436.E |  | 0,1 - 1,2 | 0,7 |
| 426.E |  | 0,1 - 1,2 |  |



Heavy-duty models






▷ ISO 9654, DIN ISO 9654, NF ISO 9654.


- For tough applications and repetitive work on a wide range of materials.

- Piano wire : 405.12 C : 0.8 mm ; 405.12 RC : 0.6 mm.

- Available with offcut retaining system.

$\Delta\Delta$: 105 g.

|  | Cut | Cu - Ni wire \varnothing mm | Cu - Ni wire \varnothing mm | Offcut retainer |
|--|---|----------------------------------|----------------------------------|--------------------|
| 405.12E |  | 0,4 - 2,0 | 1,0 | |
| 405.12RE |  | 0,4 - 1,5 | 0,9 | • |
| 415.E |  | 0,3 - 2,0 | 1,0 | |
| 415.RE |  | 0,3 - 1,5 | 0,8 | • |



X-ON Electronics

Authorized Distributor

Click to view similar products for [Facom](#) manufacturer.

Other Similar products are found below :

[VE3PB](#) [AMR](#) [ANX30X125](#) [AP3X150VE](#) [AEJ1](#) [AEFJ2](#) [AWHH3X75](#) [A402J2](#)
[A35X100VE](#) [985753](#) [7519](#) [A55X150VE](#) [R360NANO](#) [R217](#) [427MT](#) [89SJP8](#) [405E](#)
[40512E](#) [ANJ4PB](#) [AR55X150](#) [R32](#) [AND1X100](#) [AEFJ1](#) [758](#) [251A25](#)