





VER - 27100

Description

This is a straight grounding cord, with either a 10mm male snap stud or 10mm female snap socket and two 4mm banana jacks in the molded head. The banana jacks provide grounding for two wrist straps. The other end of the grounding cord is terminated by a 5mm ring terminal, a 4mm plug or a 10mm socket. A common ground point or earth bonding point (EBP) ties together several elements of an EPA such as bench working surface, floor mat or wrist strap. In this manner, all are kept at the same electrical potential.

Note: Cord does not include a current limiting resistor.

Specification

Conductor: 7 end tinsel wire

Cord length: 4m
Colour: Black
Molded plug end pull force: > 3kg

Item	Description
VER-26473	EBP Cord, 4m, 10mm Stud, 2 x Banana Jacks, M5 Ring Terminal
VER-27100	EBP Cord, 4m, 10mm Socket, 2 x Banana Jacks, Banana Plug, Crocodile Clip,
	10mm Term Socket

"Common ground point, grounded device or location where the conductors of two or more ESD control items are bonded" [EN 61340-5-1 Edition 1.0 2007-08 clause 3.1]

Unless otherwise noted, tolerance is ±10% Special manufactured items are not returnable for credit.



Earth Bonding Plug Cord

VERMASON

UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH, HERTS, SG6 2TD UK
PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440
E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk

Drawing Number VER-26473

DATE:December 2015

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for vermason manufacturer:

Other Similar products are found below:

203015 237670 230260 238711 35594 230660 072425B 50424 242296 229775 J6609 VER-29082 47200 231725 231250 242270 47201 230480 203065 237200 229100 249205 230310 229795 230647 230370 231275 237675 231280 35267 242278 231345 35595 229135 230646 VER-26457 230420 35592 35622 241030 241100 ASBB4