

Wide Range IR Thermometer with Type K input


✓ **Measures both non-contact and contact temperature plus stores up to 20 readings**

42515 Features:

- Wide temperature range for IR temperature and type K thermocouple measurements
- Automatic emissivity adjustment (for temperatures 212°F or higher)
- Memory stores up to 20 readings
- Adjustable high/low visual and audible alarm
- MAX/MIN/AVG/DIF features display highest, lowest, average, and MAX minus MIN values
- Large LCD display with bright backlight
- Built-in laser pointer improves aim
- Data Hold, Auto power off, and Low battery indication
- Complete with 9V battery, type K probe and case

TP200 Features:

- Spring-loaded jaw for secure grip on pipes from 0.25" (6.35mm) to 1.5" (38mm) diameter
- For use with any Thermometer or MultiMeter with a Type K thermocouple input
- Measurement range: -4 to 200°F (-20 to 93°C)
- Accuracy: ±5% FS
- Complete with attached 36" (0.9m) cable and Type K connector



Type K input for contact measurements

Measure temperature in hard to reach areas

TP200 Type K clamp probe provides hands-free secure grip when measuring temperature on pipes up to 1.5" (38mm) diameter

Specifications:	Model 42515
Range:	IR: -58 to 1472°F (-50 to 800°C) Type K: -58 to 2498°F (-50 to 1370°C)
Basic Accuracy:	IR: (±2% Reading or 4°F / 2°C) whichever is greater <932°F/500°C ±(2.5%rdg+5°)> 932°F/500°C Type K: (±1.5% Reading ±5°F or 3°C)
Max. Resolution:	0.1°F/°C
Emissivity:	Adjustable 0.10 to 1.00
Field of View:	13:1 distance to target ratio
Dimensions:	3.2 x 1.6 x 6.3" (82 x 42 x 160mm)
Weight:	6.4oz (180g)

Ordering Information:

42515-TIR Thermometer with Type K Clamp Probe Kit

42515-T-NISTLIR Thermometer with Type K Clamp Probe Kit

*42515-T-NISTL: Limited NIST for Certificate of Traceability for 42515 meter only



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Environmental Test Equipment](#) category:

Click to view products by [Extech](#) manufacturer:

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [S-11](#) [FLUKE-LDG](#) [382153](#) [FM100](#) [RH210](#) [382253](#) [MO290-P](#)
[GEO-CABLE-REEL-50M](#) [T197914](#) [RD300-L](#) [IR11BD](#) [IR11GM](#) [IR12GM](#) [IR21BD](#) [IR31CE](#) [IR32BC](#) [IR33BC](#) [MP7217TC](#) [NGM-1](#) [SGX-](#)
[7NH3](#) [UT381](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-NmHc-100](#) [3.000.401](#) [AX-7535](#) [CS-9S6SS-A](#) [P 2800 A](#) [P 2801](#) [P 2802](#) [P 5039](#) [P 5130](#) [P](#)
[5055](#) [P 5060](#) [P 5065](#) [P 5086](#) [P 5090](#) [P 5110](#) [P 5115](#) [P 5135](#) [P 5140](#) [P 5145](#) [P 5150](#) [P 5160](#)