



Wide Range InfraRed Thermometer

Non-contact InfraRed Thermometer measures from -54.0°F to 1000°F

With laser pointer to identify target area and improve aim

Features:

- Wide range temperature measurements from -54°F to 1000°F without contact
- · Large LCD display with backlighting
- Built-in laser pointer to improve aim
- °F/°C switchable with 0.1° resolution to 199.9
- Fixed emissivity (0.95) covers 90% of surface applications
- · Narrow field of view
- · Audible and visible overrange indicators
- Automatic Data Hold
- Pocket size meter
- Complete with 9V battery and carrying case

Applications:

- Measure surface temperature of objects which are difficult to reach or unsafe to contact
- Measure hot spots in electrical panels and equipment
- In-process temperature measurements





Specifications	
Range	-58 to 1000°F or -50 to 538°C
Accuracy	±2% of reading or ±4°F/ 2°C (whichever is greater)
Resolution	0.1°F/°C
Emissivity	0.95 fixed
Display	Backlit LCD
Power	9V battery
Field of view	8:1 (at 8" distance measure 1" target)
Dimensions	8.3x3.5x1.5" (211x89x38mm)
Weight	6.4oz. (200g)

Ordering Information:

42530.....Wide Range InfraRed Thermometer 42530-NIST42530 with NIST Cerificate



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160