



8, 9, 15 NO PIN

ELECTRO-OPTICAL CHARACTERISTICS  $T_A=25^{\circ}\text{C}$   $I_f=10\text{mA}$

| PARAMETER       | MIN                  | TYP | MAX | UNITS          | TEST COND            |
|-----------------|----------------------|-----|-----|----------------|----------------------|
| PEAK WAVELENGTH | 635                  |     |     | nm             |                      |
| FORWARD VOLTAGE | 2.1                  | 2.5 |     | V <sub>f</sub> |                      |
| REVERSE VOLTAGE | 5.0                  |     |     | V <sub>r</sub> | $I_f=100\mu\text{A}$ |
| AXIAL INTENSITY | 4000                 |     |     | μcd            | $I_f=10\text{mA}$    |
| EMITTED COLOR:  | RED                  |     |     |                |                      |
| FACE COLOR:     | GRAY                 |     |     |                |                      |
| SEGMENT COLOR:  | MILKY WHITE DIFFUSED |     |     |                |                      |

LIMITS OF SAFE OPERATION AT 25°C PER DIE

| PARAMETER                | UNITS | MAX        |
|--------------------------|-------|------------|
| PEAK FORWARD CURRENT*    | mA    | 150        |
| STEADY CURRENT           | mA    | 30         |
| POWER DISSIPATION        | mW    | 105        |
| DERATE FROM 25°C         | mW/°C | -1.2       |
| OPERATING, STORAGE TEMP. | °C    | -40 TO +85 |
| SOLDERING TEMP.          | °C    | +260       |
| 2.0mm FROM BODY          |       |            |
| * $t < 10\mu\text{s}$    |       |            |

UNCONTROLLED DOCUMENT

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X=X±0.5 (±0.020), X=X±0.5 (±0.020), X=X±0.25 (±0.010), X=XXX±0.127 (±0.005), LEAD SIZE±0.05 (±0.002), LEAD LENGTH±0.75 (±0.030), MIN=-0.00, MAX=+0.00, DECIMAL PRECISION

PART NUMBER

LDF-U8004B1

REV.

635nm HIGH INTENSITY RED DISPLAY,  
GRAY FACE, WHITE SEGMENTS.

CONFIDENTIAL INFORMATION  
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES. RELIABILITY NOTE  
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

290 E. HELEN ROAD  
PALATINE, IL 60067-6976  
PHONE: +1.847.359.2790  
US WEB: www.lumex.com  
TW WEB: www.lumex.com.tw



DRAWN BY: CT  
CHECKED BY: YA  
APPROVED BY: YA  
DATE: 1.8.01  
PAGE: 1 OF 1  
SCALE: N/A

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LED Displays & Accessories](#) category:*

*Click to view products by [Lumex](#) manufacturer:*

Other Similar products are found below :

[LTC-2721WC](#) [LTC-4624JD](#) [LTC-4627G](#) [LTC-4627WC](#) [LTD-5021AWC](#) [LTM-8522G](#) [LTP-4323P](#) [LTP-747G](#) [LTS-3361JG-06](#)  
[F416SYGWA/S530-E3](#) [1668](#) [HT-F196NB-5323](#) [IPD2131-27](#) [SA03-12EWA](#) [LDD-E2802RD](#) [LDD-E306MI](#) [LDQ-N514RI](#) [LDS-A3506RD](#)  
[LDS-A3926RI](#) [LDT-M516RI](#) [SC03-12HDB](#) [SI-B9T151550WW](#) [SI-B9V171550WW](#) [SLC-3PF-WL](#) [1624](#) [LTC-2621JD](#) [LTC-2623WC](#) [LTC-](#)  
[4624P](#) [LTC-4627JD](#) [LTD-2601E](#) [LTD-2601P](#) [LTD-322G](#) [LTD-482PC](#) [LTP-1457AKR](#) [LTP-3784G-01](#) [LTS-313AP](#) [LTS-4812SKR-P](#) [LTS-](#)  
[547AE](#) [LTS-6780P](#) [446010401-3](#) [HV-7W30-6829](#) [CA12240\\_MINNIE-WWW-MTG-ASSY](#) [DA43-11GWA](#) [LDD-A516RI-17](#) [LDD-E305RI](#)  
[LDQ-M513RI](#) [LDQ-M5204RI-SI](#) [LDQ-N3402RI](#) [LDQ-N3606RI](#) [LDT-M2804RI](#)