

This document was generated on 09/18/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0022282102

Status: Active

Overview: KK® Interconnect System - Molex

Description: KK 254 Breakaway Header, Right-Angle, with Plastic Polarizing Peg, 10 Circuits,

0.38µm Gold (Au) Selective Plating

Replacement Part http://www.molex.com/molex/products/listview.jsp?

Number: channel=Products&sType=p&query=002228110122-28-1101 see comments

Documents:

<u>3D Model</u> <u>Product Specification PS-10-07-001 (PDF)</u>
<u>Drawing (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u>

Agency Certification

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series <u>42226</u>

Application Signal, Wire-to-Board

Application Tooling Part Link 11-20-1230

Comments Original part has a polarized backwall, replacement

has friction lock backwall. Pin length of FKL header is .750" vs. .670" of polarized version. Plating and other

dimensions are same.

Overview KK® Interconnect System - Molex

Product Name KK 254


Replacement Part Number <u>22-28-1101</u> see comments

UPC 800753808980

Physical

Breakaway Yes Circuits (Loaded) 10 Circuits (maximum) 10 Color - Resin Black Durability (mating cycles max) 100 Flammability 94V-0 Glow-Wire Capable No Lock to Mating Part None Material - Metal **Brass** Material - Plating Mating Gold Material - Plating Termination Tin Material - Resin Nylon Net Weight 1.474/g Number of Rows

Orientation Right Angle 3.05mm PC Tail Length **PCB Locator** No **PCB** Retention None PCB Thickness - Recommended 1.60mm Packaging Type Bag Pitch - Mating Interface 2.54mm Plating min - Mating 0.381um Plating min - Termination 2.540µm Polarized to Mating Part No Polarized to PCB No Shrouded No



EU ELV

Not Relevant

EU RoHS China RoHS Compliant

REACH SVHC Not Contained Per -ED/61/2018 (27 June

2018)

Halogen-Free

Status

Not Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

42226 Series

Mates With

KK Crimp Housing <u>2695</u>, <u>6471</u>, <u>7880</u>, KK PC Board Connector 4455

Stackable No

Temperature Range - Operating See Product Specification

Termination Interface: Style Through Hole

Electrical

Current - Maximum per Contact 4.0A Voltage - Maximum 500V

Solder Process Data

Duration at Max. Process Temperature (seconds)

Lead-freeProcess Capability

Max. Cycles at Max. Process Temperature

O01

Process Temperature max. C

235

Material Info

Engineering Number 42226-0045

Reference - Drawing Numbers

Product Specification PS-10-07-001

Sales Drawing SD-42226-001, SD-42226-001-002

This document was generated on 09/18/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 000-34000 0009482033 0009507031 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 636-1427 638009-1 641938-9 641991-4 644168-1 647662-1 65039-019ELF 65817-002LF 65817-015LF 65863-015LF 66207-023LF 67016-026LF 67046-001LF 67095-007LF 67230-005LF