

This document was generated on 10/01/2018

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** 0307005121

Status: **Active** 

Overview: H-DAC 64™ Dual-Row High Density Automotive Connectors

2.54mm Pitch, H-DAC 64 High Density Automotive Header, Dual Row, Right-Angle, 12 **Description:** 

Circuits, Polarization Option 2, Black, Tray

**Documents:** 

Product Specification PS-30700-0001-001 (PDF) 3D Model

**Drawing (PDF)** RoHS Certificate of Compliance (PDF)

General

**Product Family PCB Headers** 

30700 Series

Power, Wire-to-Board Application Comments Polarization Option 2

Overview H-DAC 64™ Dual-Row High Density Automotive

> Connectors H-DAC 64 800756065991

Nickel

No

**Physical** 

**UPC** 

**Product Name** 

Breakaway No Circuits (Loaded) 12 Circuits (maximum) 12 Color - Resin Black Durability (mating cycles max) 10 First Mate / Last Break No Glow-Wire Capable No Guide to Mating Part No Keying to Mating Part None Lock to Mating Part Yes Material - Metal Copper Material - Plating Mating Tin

Material - Resin Modified Polystyrene

Net Weight 5.566/g

Number of Rows

Orientation Right Angle 3.69mm PC Tail Length Yes **PCB** Locator **PCB** Retention Yes PCB Thickness - Recommended 1.57mm Packaging Type Tray Pitch - Mating Interface 2.54mm Polarized to Mating Part Yes Polarized to PCB Yes Shrouded Fully Stackable No


Surface Mount Compatible (SMC) Temperature Range - Operating -40° to +100°C Termination Interface: Style Through Hole

**Electrical** 

Current - Maximum per Contact 7.0A Voltage - Maximum 500V DC

**Solder Process Data** 

Material - Plating Termination



## **EU ELV Compliant**

**EU RoHS China RoHS** 

Compliant **REACH SVHC** Not Contained Per -ED/01/2018 (15 January 2018) **Halogen-Free** 

**Status** 

**Not Relevant** 

For more information, please visit Contact US

China ROHS Not Relevant Compliant ELV **RoHS Phthalates** Not Contained

Search Parts in this Series

30700 Series

**Mates With** 

H-DAC 64 Housing 30700-1121

Duration at Max. Process Temperature (seconds) 040

Lead-freeProcess Capability SMC&WAVE

Max. Cycles at Max. Process Temperature 003
Process Temperature max. C 260

**Material Info** 

**Reference - Drawing Numbers** 

Product Specification PS-30700-0001-001 Sales Drawing SD-30700-520

This document was generated on 10/01/2018

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

003-018-000 600858 60403001 60993906-B 60993913-B 629515004020001 M902-2131 M902-2161 M902-2344 72.330.1035.1

73.353.4028.0 F118010 F119300-B F132210 F132210-B F166900 F180100 F258300 F258300-B F294300-B F339100 F339700 F358300-B F374110 F407400 F412210 F427600 F444110 F487000 F495100-B F500900-B F509500B-B 770444-1 776880-1 827153-1 881735-1 8N1515-32-24P 9-1326729-8 925467-1 925474-1 928905-1 936398-2 964562-1 964562-4 964731-2 965051-1 968782-1 GT17SA-8DS-HU GT17VS-10DP-5.2CF 98315-0001