

This document was generated on 06/10/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0432236022 Status: Active Modular Jacks and Plugs **Overview: Description:** Modular Jack, Right Angle, Low Profile, 6/4, 2 Ports **Documents:** 3D Model Packaging Specification PK-43249-004 (PDF) Test Summary TS-43223-001 (PDF) Drawing (PDF) Product Specification PS-43223-001 (PDF) RoHS Certificate of Compliance (PDF) **Agency Certification** CSA LR19980 UL E107635 EU ELV Not Relevant General Product Family Modular Jacks/Plugs EU RoHS Series 43223 Compliant Comments Flush Mount|Flangeless|External Shield **REACH SVHC Component Type** PCB Jack Not Contained Per Magnetic -ED/79/2015 (17 No Overview Modular Jacks and Plugs December 2015) Performance Category 3, 4 **Halogen-Free** Power over Ethernet (PoE) N/A **Status Product Name RJ11 Not Low-Halogen** UPC 800754379298 Physical Boot Color N/A Color - Resin Black Durability (mating cycles max) 500 Flammability 94V-0 China ROHS Inverted / Top Latch No ELV Jack Height 12.83mm Lightpipes/LEDs None Material - Metal **Phosphor Bronze** Material - Plating Mating Gold Material - Plating Termination Tin 43223 Series Material - Resin **High Temperature Thermoplastic** Net Weight 7.862/g Mates With Orientation Right Angle (Side Entry) FCC 68 Plugs **PCB** Locator Yes PCB Retention Yes PCB Thickness - Recommended 1.57mm Packaging Type Trav Pitch - Mating Interface 1.02mm Pitch - Termination Interface 1.27mm Plating min - Mating 1.270µm Plating min - Termination 2.540µm Ports 2 Positions / Loaded Contacts 6/4 Surface Mount Compatible (SMC) No Temperature Range - Operating -40°C to +85°C **Termination Interface: Style Through Hole** Waterproof / Dustproof No Wire/Cable Type N/A

Series image - Reference only

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com Please visit the Contact Us section for any non-product compliance questions.

> Green Image Not Relevant

```
Search Parts in this Series
```

Electrical

Current - Maximum per Contact Shielded Voltage - Maximum	1.5A No 150V AC (RMS)
Solder Process Data Lead-freeProcess Capability	WAVE
Material Info Old Part Number	A432236022
Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing Test Summary	PK-43249-004 PS-43223-001 SDA-43223 TS-43223-001

This document was generated on 06/10/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 RJE231881317T
 MP1010RX-1000
 MP44RX-1000
 GAX-3-66
 GAX-8-62
 93606-0253
 GD-A-44
 GDCX-PA-66-50
 GDCX-PN-64
 GDCX-PN-64

 PN-66
 GDCX-PN-66-50
 GDLX-A-66
 GDLX-A-88
 GDLX-N-66
 GDLX-S-88K
 GDTX-S-88-50
 GDX-PA-1010
 GLX-N-1010M-BLK

 GLX-N-44M
 GLX-S-88M-BLK
 GMX-N-1010
 GMX-S-1010
 GMX-S-66
 GMX-SMT2-N-1010
 GMX-SMT2-N-64-50
 GMX-SMT2-S6-88

 GMX-SMT4-N-88
 GPX-2-64
 GRT1-BT1-5
 GSGX-N-2-88
 GSX-NS2-88-3.05
 GSX-NS2-88-3.05-50
 GSX-NS-88-3.05-30
 GSX-NS-88-3.05-30

 3.05-50
 GSX-NS-88-3.68
 1-1775629-2
 GWLX-S-88-GR
 GWLX-S9-88-YG
 1300500326
 1300500227
 1300530003
 1300570002
 1324640-4

 RJ11FTVC2G
 RJ11FTVC2N
 RJFTVX2SA1G
 132764-001
 1400000
 1413176
 1413235