

This document was generated on 06/10/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0443801010

Status: Active

Overview: Modular Jacks and Plugs

Description: Modular Jack, Right Angle, Low Profile, Inverted, 8/8

Documents:

<u>3D Model</u> <u>Packaging Specification PK-44380-005 (PDF)</u>

<u>Drawing (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u>

Product Specification PS-43860-003 (PDF) Product Literature (PDF)

Application Specification AS-43860-001 (PDF)

Agency Certification

CSA LR19980 UL E107635

General

Product Family Modular Jacks/Plugs

Series 44380
Component Type PCB Jack
Magnetic No

Overview Modular Jacks and Plugs

Performance Category

Power over Ethernet (PoE)

Product Literature Order No

Product Name

USA-154

RJ45

UPC

800754801737

Physical

Boot Color N/A
Color - Resin Black, Clear

Durability (mating cycles max) 500

Inverted / Top Latch Yes
Jack Height 13.54mm
Keying to Mating Part None
Lightpipes/LEDs Lightpipes

Material - Metal Brass, Phosphor Bronze

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic, Polysulfone

Net Weight 3.884/g

Orientation Right Angle (Side Entry)
PCB Locator Yes

PCB Retention Yes
PCB Thickness - Recommended 1.00mm
Packaging Type Tray

Packaging Type Tray
Panel Mount Without Flange

Pitch - Mating Interface 1.02mm
Pitch - Termination Interface 1.02mm
Plating min - Mating 1.270µm
Plating min - Termination 2.540µm
Ports 1
Positions / Loaded Contacts 8/8


Surface Mount Compatible (SMC)

Temperature Range - Operating

-40°C

Temperature Range - Operating -40°C to +85°C Termination Interface: Style Through Hole

Waterproof / Dustproof No Wire/Cable Type N/A



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant
REACH SVHC
Not Contained Per
-ED/79/2015 (17
December 2015)
Halogen-Free
Status

Not Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Green Image ELV Not Relevant

Search Parts in this Series

44380 Series

Mates With FCC 68 Plugs

Electrical

Current - Maximum per Contact 1.5A
Grounding to PCB No

Grounding to Panel With All Panel Grounding Tabs

Shielded Ye

Voltage - Maximum 150V AC (RMS)

Solder Process Data

Lead-freeProcess Capability WAVE

Material Info

Reference - Drawing Numbers

Application Specification AS-43860-001 Packaging Specification PK-44380-005

Product Specification PS-43860-003, RPS-43860-004, RPS-43860-007,

RPS-43860-008, RPS-43860-013

Sales Drawing SD-44380-001

This document was generated on 06/10/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

RJE231881317T MP1010RX-1000 MP44RX-1000 GAX-3-66 GAX-8-62 93606-0253 GD-A-44 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66-50 GDLX-A-66 GDLX-A-88 GDLX-N-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-N-44M GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT2-N-1010 GMX-SMT2-N-64-50 GMX-SMT2-S6-88 GMX-SMT4-N-88 GPX-2-64 GRT1-BT1-5 GSGX-N-2-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05-50 GSX-NS-88-3.05-30 GSX-NS-88-3.05-30 GSX-NS-88-3.05-50 GSX-NS-88-3.05-30 GSX-NS-88-3.05-