

This document was generated on 10/19/2016

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0051241030

Status: Active

Overview: LFH™ Interconnect System

**Description:** 1.27mm Pitch LFH™ Matrix 50 Receptacle, Shielded, 160 Circuits, Vertical

**Documents:** 

<u>3D Model</u> <u>Product Specification PS-71626 (PDF)</u>
<u>Drawing (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u>

**Agency Certification** 

CSA LR19980 UL E29179

General

Product Family I/O Connectors

Series 71626

Application Board-to-Board, Wire-to-Board

Component Type Receptacle

Overview <u>LFH™ Interconnect System</u>

Product Name LFH™
Type N/A

UPC 800754387118

**Physical** 

Circuits (Loaded) 160
Circuits (maximum) 160
Color - Resin Black
Flammability 94V-0
Keying to Mating Part None
Lock to Mating Part Yes

Material - Metal Beryllium Copper

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

Net Weight 11.695/g Vertical Orientation PC Tail Length 2.34mm **PCB** Retention Yes PCB Thickness - Recommended 4.60mm Packaging Type Tube Panel Mount Yes Pitch - Mating Interface 1.27mm Plating min - Mating 0.762µm Plating min - Termination 2.540µm Polarized to Mating Part Yes Surface Mount Compatible (SMC) Yes

Temperature Range - Operating -20°C to +80°C Termination Interface: Style Through Hole


Wire Size AWG N/A

**Electrical** 

Current - Maximum per Contact 1.0A
Grounding to Panel Yes
Shielded Yes
Voltage - Maximum 40V

**Solder Process Data** 

Lead-freeProcess Capability SMC&WAVE



**EU ELV** 

**Not Relevant** 

EU RoHS China RoHS

Compliant with
Exemption 6(c)
REACH SVHC
Not Contained Per ED/21/2016 (20 June

2016)

Halogen-Free
Status
Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS 50 Image
ELV Not Relevant
ROHS Phthalates Not Contained

Search Parts in this Series

71626 Series

Mates With 71624 LFH™ Plug

**Use With** 

71628 Guide Pin. Guide Sleeve 71629,

71771. 70982 Hex Screw Kit

Process Temperature max. C 260

**Material Info** 

**Engineering Number** 716261000

Reference - Drawing Numbers
Product Specification PS-71626

SDA-71626-1\*\*\*\* Sales Drawing

This document was generated on 10/19/2016

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

571763P 58098-0628 61-168618-12P D38999/20FJ24PA L/C D38999/20FJ29SB L/C D38999/24FG11SN L/C 72.250.1628.2 72.250.2428.2 74720-0505 76.350.0729.0 76871-1403 FCN-244F080-G/I FCN-260A9920 FCN-268D024-G/2F#10X-R10 PCS-E50FA PCS-XE26LKA PCS-XE26MA+ PCS-XES68MS+ G38A71314B 91-569719-35R 9776-18-6 DX40-50P(55) 1571250010 157-22500-3 MS3476W12-10S L/C 1888020-8 91-569786-35H 91-569786-35M 91-644626-35P 172501-4002 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 FCN-268D008-G/IK 2000314-1 200331-1 2007498-2 PCR-E28LMDAG1+ PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFDT+ G38A71214B HDRA-E68W1LFDTC-SL+ HDR-E14MSG1+ R88A-CNK81S CRT1-ATT02 54182-0605 U90B2054081210