

This document was generated on 10/08/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0757830112

Status: Active

Overview: iPass Connector System

Description: iPass I/O Surface Mount Receptacle, Right-Angle, Internal Assembly with Shell, 36

Circuit, 0.38µm Gold (Au), Surface Mount Option, Tail Length 1.96mm, Dual Key

Documents:

3D Model Packaging Specification PK-75783-002 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-75783-001-001 (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family I/O Connectors

Series 75783
Application Wire-to-Board

Comments Positive or passive latching cable available

Component Type Receptacle Electrical Model Yes

Overview <u>iPass Connector System</u>

Product Name iPass, Mini Multi-Lane, PCI Express

Type N//

UPC 822348852727

Physical

Circuits (Loaded) 36
Circuits (maximum) 36
Color - Resin Black
Durability (mating cycles max) 50
Flammability 94V-0
Gender Female

Keying to Mating Part Yes
Lock to Mating Part None

Material - Metal Copper-Nickel-Zinc, High Performance Alloy (HPA)

Material - Plating Mating
Material - Plating Termination
Gold

Material - Resin High Temperature Thermoplastic


Net Weight 3.076/g Number of Rows 2

Orientation Right Angle
PC Tail Length 1.96mm
PCB Locator Yes
PCB Retention Yes
PCB Thickness - Recommended 1.57mm

Packaging Type Embossed Tape on Reel

Panel Mount
Pitch - Mating Interface
0.80mm
Pitch - Termination Interface
0.80mm
Plating min - Mating
0.381µm
Plating min - Termination
2.540µm
Polarized to Mating Part
Yes
Ports
1
Surface Mount Compatible (SMC)
Yes

Temperature Range - Operating -40° to +80°C



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant
REACH SVHC
Not Contained Per ED/61/2018 (27 June

2018) <u>Halogen-Free</u> <u>Status</u>

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
ROHS Phthalates Not Contained

Search Parts in this Series

75783 Series

Use With

iPass Cable Assemblies, 79575, 79576,

74562, 74563, 79536, 74573,

Termination Interface: Style Surface Mount and Through Hole

Waterproof / Dustproof
Wire Insulation Diameter
N/A
Wire Size AWG
N/A

Electrical

Current - Maximum per Contact 0.5A
Grounding to Panel None

Voltage - Maximum 30V AC (RMS)/DC

Solder Process Data

Duration at Max. Process Temperature (seconds)

Lead-freeProcess Capability

Max. Cycles at Max. Process Temperature

O01

Process Temperature max. C

260

Material Info

Reference - Drawing Numbers

Electrical Model Document EE-75586-001
Packaging Specification PK-75783-002
Product Specification PS-75783-001-001
S-Parameter Model SP-75586-001
Sales Drawing SD-75783-001-001

This document was generated on 10/08/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

2332816-1 89006-1137LF 650827-1 65762-001LF 73474-201LF 74040-1346 74075-0267 1410191-1 1410337-1 1410368-3 1410964-2
1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 2187462-1 2226278-6 KA81-07 91290-101LF
163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 2226279-2 22354-8 437-5040-000 5-1393565-0 532449-3 5328032 34745-0001 0736440217 1-1393708-5 72388-0021LF 73774-1000 532939-1 5-531355-3 5532901-3 85838-180LF
HM1S43TRR460H6PLF 0760205010 1-966831-4 3-1469268-7 77427-121LF