

Termination Interface: Style

This document was generated on 02/20/2018 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0908143018		
Status:	Active		
Overview:	Picoflex Ribbon-Cable Connectors		
Description:		der with PCB Pegs, Vertical, Standard Profile, Surface Mount, PdNi	The Star Day Day Day
		ing, 18 Circuits, Tube, Natural	
			a sa
Documents:			
3D Model		Packaging Specification PK-90814-001-001 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
	n PS-99020-0011 (PDF		
		+	Series image - Reference only
Agency Certificatio	n		
UL		E29179	EUELV
			Not Relevant
General		DOD Lies dare	
Product Family		PCB Headers	EU RoHS China RoHS
Series		90814 Signal Wire to Poord	Compliant
Application		Signal, Wire-to-Board	REACH SVHC
Application Tooling Part Link Comments		69008-1070 Standard Drafila	Not Contained Per -
Overview		Standard Profile	ED/30/2017 (7 July
		Picoflex Ribbon-Cable Connectors Picoflex	2017)
Product Name UPC			Halogen-Free
UPC .		800753655089	<u>Status</u>
Physical			Not Low-Halogen
Breakaway		No	Need more information on product
Circuits (Loaded)		18	environmental compliance?
Circuits (maximum)		18	Email productcompliance@molex.com
Color - Resin		Natural	Please visit the <u>Contact Us</u> section for a
Durability (mating cycles max)		100	non-product compliance questions.
First Mate / Last Break		No	non product compliance questions.
Flammability		94V-0	China ROHS Green Image
Glow-Wire Capable		No	ELV Not Relevant
Guide to Mating Part		No	RoHS Phthalates Not Contained
Keying to Mating Part		None	
Lock to Mating Part		Yes	
Material - Metal		Brass	Connets Donte in this Conice
Material - Plating Mating		Gold over Palladium Nickel	Search Parts in this Series
Material - Resin		High Temperature Thermoplastic	<u>90814</u> Series
Net Weight		0.783/g	
Number of Rows		1	Mates With
Orientation		Vertical	90327 IDT Connector
PCB Locator		Yes	
PCB Retention		Yes	Application Tooling FAQ
PCB Thickness - Recommended		1.60mm	Tooling specifications and manuals ar
Packaging Type		Tube	found by selecting the products below
Pitch - Mating Interface		1.27mm	Crimp Height Specifications are then
Pitch - Termination Interface		1.27mm	contained in the Application Tooling
Plating min - Mating		0.762µm	Specification document.
Plating min - Termination		0.102µm	Global
Polarized to Mating Part		Yes	Description Product #
Polarized to PCB		Yes	Extraction Tool 0690081070
Shrouded		No	(Plastic) for 4-26
Stackable		No	Circuit
Surface Mount Com	patible (SMC)	N/A	
Temperature Range		-40°C to +105°C	
Termination Interface		Surface Mount	

Surface Mount

Electrical

Current - Maximum per Contact Voltage - Maximum

Material Info

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

PK-90814-001-001 PS-99020-0011 SDA-90814

1.2A

250V

This document was generated on 02/20/2018 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 000-34000 0009482033 0009507031 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 636-1427 638009-1 641938-9 641991-4 644168-1 647662-1 65039-019ELF 65817-002LF 65817-015LF 65863-015LF 66207-023LF 67016-026LF 67046-001LF 67095-007LF 67230-005LF