



MATERIALS:

Body: Brass, H.H. per QQ-B-626, Alloy 360

Insulation: RNF-100 shrink Tubing, Black.

Finish: Body: Electroless nickel plated per MIL-C-26074, Class 2 (.0002 min.) over copper strike.

RATINGS:

Operating Voltage: 300V

Operating Temperature: +102°C (+216°F) Max.

Current: 5 Amperes

ORDERING INFORMATION: Model 4311-*

*= Color, -0 Black, -2 Red

Part is packaged one (1) per bag, unassembled.

Part mates with Pomona Model 4011

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Test Connectors](#) category:

Click to view products by [Pomona](#) manufacturer:

Other Similar products are found below :

[5739](#) [5752](#) [5757](#) [912](#) [MXHS83QE1000](#) [IB3-10-SP01](#) [1691](#) [CR-43](#) [M08SW](#) [M10X100](#) [4247](#) [MM126037](#) [3316](#) [108-0772-001](#) [5747](#) [5754](#)
[86101-07A01](#) [5753](#) [MM126511](#) [MM126527](#) [5760](#) [2375380-1](#) [134328](#) [4248](#) [5735](#) [MM126056](#) [MM126310](#) [MXHS83QE3000](#) [4320-01069-](#)
[0](#) [SV225](#) [CS20MA](#) [3296](#) [3302](#) [783538-01](#) [3602](#) [3719](#) [3728](#) [4226](#) [4245](#) [4246](#) [4903](#) [MXFR01JA1000](#) [5734](#) [5740](#) [5744](#) [911](#) [4057](#) [BU-](#)
[30212-0](#) [CT3878-0](#) [CT3878-2](#)