

Model: PS-AAA




Sealed Nickel Cadmium Batteries


Specifications

Nominal Valtage		1.2 Volt
Nominal Voltage		1.2 VOIL
Rated Capacity		300 mAh
Dimensions	Diameter in. (mm)	0.40 (10.1)
	Height in. (mm)	1.72 (43.6)
	Height with solder tabs	1.76 (44.6)
	Weight Approx.	9 gm
	Internal Resistance	< 45 mΩ
	Standard Charge (0.1C)	30 mA
	Trickle Charge	(0.03C)~(0.05C)
	Fast Charge ΔV	300 mA
Recommended	Std/Trickle Charge	20±5°C
Operating	Fast Charge	20±5°C
Temperature	Discharge	20±5°C
Range	Storage	-20°C to 45°C
Standard Discharge (0.2C) Cut Off Voltage		1.0V per cell
High Rate Discharge (1 C) Cut Off Voltage		1.0V per cell


Dimensions




Charging and Discharging Characteristics




Discharge



Fast Charge




Standard Charge




Trickle Charge







▲ Standard Battery Cycle Life ▲




▲ Cycle Life Using Trickle Charging **▲**




▲ Capacity vs. Temperature ▲



▲ Fast Charging Cycle Life ▲



▲ Stand-by Battery Life ▲



▲ Retained Capacity In Storage ▲

Corporate Headquarters and Domestic Sales

Power-Sonic Corporation • 7550 Panasonic Way • San Diego, CA 92154 •U.S.A Phone: (619) 661-2020 • Fax: (619) 661.3650

Email Sales: national-sales@power-sonic.com

Email Customer Service: customer-service @power-sonic.com

E-mail Technical Support: technical-support@power-sonic.com

International Sales

Power-Sonic Corporation • P.O. Box 5242 • Redwood City, CA 94063 • U.S.A. Phone: (650) 364-5001 • Fax: (650) 366-3662
Email Sales: international-sales.com@power-sonic.com

www.power-sonic.com

© Copyright 2010 Power-Sonic Corporation. All rights reserved

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for NiCd - Nickel Cadmium Battery category:

Click to view products by Power-Sonic manufacturer:

Other Similar products are found below:

PS-CX PS-2/3AA PS-AA PS-AA PS-2/3A-T PS-A PS-SC PS-AAX-T PS-DL PS-1/2D-T PS-850AA-T PS-D-T PS-F PS-C-T PS-CH PS-CX-T PS-C PS-AAX PS-850AA PS-2/3AA-T PS-1/2D N-700AAC KR1800SCE PS-2/3A PS-AAA PS-D 15568-1 N-3000CR PS-AA-T