



## Technical data

- Control cable, special PVC with blue outer jacket for hazardous areas to hazard type -i- (=intrinsically safe)
- For intrinsically safe installation according to DIN EN 60079-14 and IEC 60079-14 section 12.2.2 (VDE 0165 part 1)
- **Temperature range**  
flexing -15 °C<sup>1)</sup> to +80 °C  
fixed installation -40 °C to +80 °C
- **Nominal voltage** U<sub>0</sub>/U 300/500 V
- **Test voltage** 3000 V
- **Breakdown voltage** min. 6000 V
- **Insulation resistance**  
min. 20 MΩm x km
- **Mutual capacitance**  
core/core approx. 120 nF/km
- **Inductance** approx. 0,68 mH/km
- **Minimum bending radius**  
flexing 7,5x cable ø  
fixed installation 4x cable ø
- **Radiation resistance**  
up to 80x10<sup>6</sup> cJ/kg (up to 80 Mrad)
- <sup>1)</sup> cold bending test, impact resistance test at low temperatures, elongation test at low temperatures. Tested according VDE 0473 Teil 811-1-4, EN 60811-1-4

## Cable structure

- Bare copper, fine wire conductors, bunch stranded to DIN VDE 0295 cl. 5, BS 6360 cl. 5 and IEC 60228 cl. 5
- Core insulation of special PVC Z 7225
- Black cores with white continuous figure imprint to DIN VDE 0293 without earth core
- Cores stranded in layers with optimal lay-length
- Special PVC outer sheath TM2, to DIN VDE 0281 part 1 and HD 21.1
- Colour blue (RAL 5015)
- with meter marking, change-over in 2011

## Properties

- Extensively oil resistant, oil-/ chemical Resistance - see table Technical Informations.
- PVC self-extinguishing and flame retardant according to VDE 0482-332-1-2, DIN EN 60332-1-2/ IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

## Note

- For underground laying use NYY with blue outer sheath.
- AWG sizes are approximate equivalent values. The actual cross-section is in mm<sup>2</sup>.
- Instrumentation cable RE-2Y(St)Yv with blue outer jacket see catalog part B.

## Application

For hazardous areas the cables with special marking (blue) (hazard type-i-) used as flexible control and measuring cables to meet the requirements for the installation of electrical apparatus. These installations are not earthed and require a separate power circuit. Those cables are not suitable for underground laying.

CE The product is conformed with the EC Low-Voltage Directive 2006/95/EG.

Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.	Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
14001	2 x 0,75	5,3	14,4	46,0	18	14019	2 x 1,5	6,4	29,0	70,0	16
14002	3 x 0,75	5,6	21,6	54,0	18	14020	3 x 1,5	6,8	43,0	90,0	16
14003	4 x 0,75	6,3	29,0	66,0	18	14021	4 x 1,5	7,4	58,0	109,0	16
14004	5 x 0,75	6,9	36,0	80,0	18	14022	5 x 1,5	8,3	72,0	131,0	16
14075	7 x 0,75	7,5	52,0	110,0	18	14023	7 x 1,5	9,2	101,0	184,0	16
14005	8 x 0,75	8,2	58,0	130,0	18	14024	12 x 1,5	12,0	173,0	309,0	16
14076	12 x 0,75	9,8	88,0	179,0	18	14025	18 x 1,5	14,6	259,0	440,0	16
14006	18 x 0,75	12,2	130,0	257,0	18	14026	25 x 1,5	17,4	360,0	620,0	16
14007	25 x 0,75	14,3	180,0	365,0	18	14027	30 x 1,5	18,6	440,0	842,0	16
14008	30 x 0,75	15,3	215,0	448,0	18	14100	3 x 2,5	8,3	72,0	148,0	14
14009	34 x 0,75	16,7	245,0	510,0	18	14101	4 x 2,5	9,2	96,0	178,0	14
14010	41 x 0,75	18,0	298,0	607,0	18	14102	5 x 2,5	10,1	120,0	221,0	14
14011	2 x 1	5,6	19,0	60,0	17						
14012	3 x 1	5,9	29,0	72,0	17						
14013	4 x 1	6,6	38,0	86,0	17						
14014	5 x 1	7,3	48,0	104,0	17						
14015	7 x 1	8,1	67,0	141,0	17						
14016	12 x 1	10,4	115,0	230,0	17						
14017	18 x 1	12,9	173,0	343,0	17						
14018	25 x 1	15,4	240,0	485,0	17						

Dimensions and specifications may be changed without prior notice. (RA04)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Multi-Conductor Cables](#) category:*

*Click to view products by [Helukabel](#) manufacturer:*

Other Similar products are found below :

[M27500-20SP2S23](#) [M3905-BK005](#) [6502FE 8771000](#) [CV6807-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#) [CXA-0140-16-6/9-9CS2405](#) [720451-000](#) [752687-000](#) [83709-002-1000](#) [8469 060100](#) [877541-000](#) [88444-002-1000](#) [9444 060U1000](#) [9497 0001000](#) [9684-060-1000](#) [1302110032](#) [EPD6062-12-9CS1693](#) [EPD-RWC-10972](#) [EPD-RWC-12305](#) [C35473-000](#) [2020D1301-9](#) [219538-6](#) [2412F-010-1000](#) [9534 060U500](#) [29531-010-2000](#) [22759/41-22-9CS2620](#) [259633-000](#) [29529C-010-2000](#) [29532-010-1500](#) [302595-000](#) [CTC-0018-22-9/5-9CS2340](#) [3600B/50 100SF](#) [3644B/16-100SF](#) [CXA-0078-20-3-9CS2405](#) [CXA-0092-14-6/9CS2973](#) [MC6A-16/0.2T2-YWGN](#) [44A0211-20-9CS3030](#) [44A0311-12-9-F871](#) [44A1221-14-9/9-9CS3030](#) [44A1221-16-9/9-9CS3030](#) [44A1321-14-9/9-9CS3030](#) [44A9685-0-F957CS2855](#) [506087-000](#) [5102UE 008500](#) [5201UE 0081000](#) [534553-000](#)