



DB25 PIN-OUT VIEW FOR DB25

| DB25 AND XLR FEMALE WIRING CHART | | | | | | | | | |
|----------------------------------|---------|-------|---------|--------|--|--|--|--|--|
| XLR | CABLE | PIN 2 | PIN 3 | PIN 1 | | | | | |
| (CHANNEL) | (COLOR) | (RED) | (BLACK) | (BARE) | | | | | |
| 1 | BROWN | 24 | 12 | 25 | | | | | |
| 2 | RED | 10 | 23 | 11 | | | | | |
| 3 | ORANGE | 21 | 9 | 22 | | | | | |
| 4 | YELLOW | 7 | 20 | 8 | | | | | |
| 5 | GREEN | 18 | 6 | 19 | | | | | |
| 6 | BLUE | 4 | 17 | 5 | | | | | |
| 7 | PURPLE | 15 | 3 | 16 | | | | | |
| 8 | GRAY | 1 | 14 | 2 | | | | | |

| PART NO. | CABLE LENGTH "X" | | | | | | |
|-------------|----------------------|--|--|--|--|--|--|
| DB25M02XLRF | 2.00 FT +/- 1.50 IN | | | | | | |
| DB25M03XLRF | 3.00 FT +/- 1.50 IN | | | | | | |
| DB25M10XLRF | 10.00 FT +/- 1.50 IN | | | | | | |

CUSTOMER DRAWING

| | | | | | | THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY. | | | | | | | | |
|-----------|------------|----------------------|----------------------------------|------|-------------------------------|--|------|---------|--------------|----------|-------|-----|--------|-----|
| | | | | | UNLESS OTHERWISE SPECIFIED | SIZE | W | IDTH | MULT | | LBS/M | | TEMPER | |
| | | | | | 1. ALL DIMENSIONS IN INCHES | FINISH | | | MATERIAL | | | | | |
| D | 26795 | 7-8-11 | то | TJK | - TWO PLACE DECIMALS ±0.02 | SPEC No. | | | SPEC No. | | | | | |
| С | 26637 | 10/11/10 | RS | TJK | - THREE PLACE DECIMALS ±0.005 | | | | -Swilehereft | | | | | |
| В | 25891 | 9/9/08 | SRC | TJK | | | | APVD | | | | | | |
| ^ | 25716 | 10/03/07 | JGK | TJK | | 9/12/06 JGK RS | | | TJK | | | | | |
| Α | 207 10 | 10/03/07 | JGK | IJK | | 0.12.00 | | 11/8/10 | 11/9/10 | | SHEET | 1 0 |)F 1 | |
| REV | ECO NUMBER | DATE | BY | APVD | | NAME | | | | PART No. | | | | REV |
| REVISIONS | | DO NOT SCALE DRAWING | DB25M TO 8 FEMALE XLR, RoHS DB25 | | | B25M_ | _XLI | RF | | | | | | |

NOTES:

- 1. BREAKOUT CABLE LENGTH: 18.00 +/- 0.75 INCHES. SEE TABLE FOR COLOR.
- 2. THIS PRODUCT COMES COILED AND PACKAGED IN BAG.
- 3. JACKSCREWS ARE SHIPPED UNASSEMBLED. CABLE COMES WITH BOTH #4-40 THREAD (2) AND #M3 THREAD (2) JACKSCREWS.
- 4. MATERIALS:

XLR FEMALE CONNECTOR:

HANDLE - ZINC ALLOY, NICKEL PLATED

HOUSING AND LATCH - ZINC ALLOY, NICKEL PLATED

INSULATOR - THERMOPLASTIC, GREEN

SOCKET CONTACTS - SPECIAL COPPER ALLOY, SILVER PLATED

H.S. TUBING - THERMOPLASTIC

DSUB - COPPER ALLOY, NICKEL PLATED WITH GOLD PINS

JACKSCREWS - STAINLESS STEEL

5. THIS PRODUCT IS ROHS COMPLIANT.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Audio Cables / Video Cables / RCA Cables category:

Click to view products by Switchcraft manufacturer:

Other Similar products are found below:

59384500100E 73-6310-10 73-6311-10 73-6313-3 73-6313-6 PCX-60-50 RCA10RCA 1-3737-600-3216 15AK25X 25FK25 LF3BLX 301511-10 30AR30 30AK30 30AN30 RCA05RCA RCA05RCAB RCA05TS RCA10RCAB 420001400-3 426058900-3 TT6RX TT7BKX

TT93602 426058300-3 LF1BKX LF3RX 0887418300 73-6312-6 73-6314-3 73-6352-3 VMP3YX VMP2YX 68767-0003 TT746 TT744

CN13B LF4GNX LF2GYX 426494200-3 LF1RX VMPBNCF LF10GNX 427492100-3 LF4BLX TT747N2 TT864 LF2YX 426491500-3 426523700-3