

2M-Series

MINIATURE TOGGLES

The 2M family of miniature toggle switches is composed of three switch series; the **2M1-Series** miniature toggle switch, the **2MS-Series** sealed miniature toggle switch, and the **2M1H-Series** premium sealed miniature toggle switch. These series all feature PC mounting and offer a variety of ratings, circuits, contact materials, terminal platings, toggle styles and lengths, and optional color caps.



Product Highlights:

- IP67 Sealing
- 8 Single and Double Pole Circuits
- Long, Short and Flatted Bushing Options
- Large Variety of Termination Options
- Available Gold, Silver and Tin Platings
- UL Approved
- Sleek Black Finish

Typical Applications:

- Telecommunications
- Instrumentation
- Networking
- Medical Equipment
- Military Communications

Resources:

[Download 3D CAD Files](#)

[IGS >](#) [STP >](#)



Carling Technologies, Inc.
60 Johnson Avenue, Plainville, CT 06062
Email: sales@carlingtech.com
Application Support: team2@carlingtech.com
Phone: 860.793.9281 Fax: 860.793.9231

www.carlingtech.com



2M1H-Series
Premium Sealed
Miniature
Toggle Switch



2MS-Series
Sealed
Miniature
Toggle Switch



2M1-Series
Miniature
Toggle Switch

Electrical


Contact Rating refer to ordering scheme
 Electrical Life 50,000 make & break cycles @ full load
 Contact Resistance 10 mΩ max. initial @ 2-4 VDC
 100mA for both silver & gold plated contacts
 Insulation Resistance 1000 MΩ min.
 Dielectric Strength 1500 Volts RMS @ sea level

Physical

Operating Temperature -30°C to +85°C
 Index of Protection *2M1H-Series:* IP67
2MS-Series: IP67
 Solder Heat Resistance MIL-STD-202, Method 210
 Actuator Travel 25°

Material

Case *2M1H-Series & 2M1-Series:* Diallyl phthalate (DAP) (UL 94V-0)
2MS-Series: Glass filled nylon 6/6, flame retardant, heat stabilized (UL 94V-0)
 Toggle *2M1H-Series:* Brass, black finish with o-ring seal
2MS-Series: Brass, chrome plated, internal o-ring sealed
2M1-Series: Brass, chrome plated
 Bushing *2M1H-Series:* Brass, black finish with o-ring seal
2MS-Series: Glass filled nylon 6/6, flame retardant, heat stabilized (UL 94V-0)
2M1-Series: Brass, nickel plated
 Housing Stainless Steel
 Bracket *2MS-Series:* Nylon (UL 94V-0)
2M1-Series: Stainless Steel
 Actuator Pivot Retainer *2MS-Series:* Stainless Steel
 Switch Support Brass, tin plated
 Terminal Seal Epoxy



1 SERIES
2M1H Premium Sealed Miniature Toggle Switch

2 POLE / CIRCUIT
 () - momentary
Position:

| | 1 | 2 | 3 |
|--------------|----------|---------------------|----------|
| | 2-3, 5-6 | Connected Terminals | 2-1, 5-4 |
| SP1 | ON | NONE | ON |
| SP2 | ON | NONE | (ON) |
| SP3 | ON | OFF | ON |
| SP4 | (ON) | OFF | (ON) |
| SP5 | ON | OFF | (ON) |
| DP1 | ON | NONE | ON |
| DP2 | ON | NONE | (ON) |
| DP3 | ON | OFF | ON |
| DP4 | (ON) | OFF | (ON) |
| DP5 | ON | OFF | (ON) |
| DP6 * | ON | ON | ON |
| DP7 * | (ON) | ON | (ON) |
| DP8 * | ON | ON | (ON) |

*Center position connects 2-3, 5-4

3 ACTUATOR STYLE
TJ .709" [18 mm] length **TK** .512" [13.00 mm] length

4 BUSHING
BJ .429" [10.90 mm] threaded, length **BK** .386" [9.80 mm] threaded, flat

5 TERMINATION ⁷

| | | | |
|-----------|---------------|------------|------------------------------------|
| M1 | Solder Lug | M51 | Wire Wrap, .750" [19.05mm] length |
| M2 | PCB | M52 | Wire Wrap, .964" [24.48mm] length |
| M3 | Quick Connect | M53 | Wire Wrap, .425" [10.80mm] length |
| | | M54 | Wire Wrap, 1.062" [25.97mm] length |

6 CONTACTS / TERMINALS

| | Contact Material | Terminal Plating | Rating | Approvals |
|----------|-----------------------|---------------------|-------------------------------|-----------|
| G | silver ¹ | gold over silver | 5A 125VAC or 28VDC, 2A 250VAC | IP67 |
| K | gold ^{2,5} | tin ^{4,7} | 0.4VA max 20V max (AC/DC) | IP67 |
| P | silver ^{1,6} | tin ^{4,7} | 5A 125VAC or 28VDC, 2A 250VAC | IP67 |
| Q | silver ¹ | silver ¹ | 5A 125VAC or 28VDC, 2A 250VAC | IP67 |
| R | gold ² | gold ³ | 0.4VA max 20V max (AC/DC) | IP67 |

7 EPOXY SEAL
E Epoxy Seal

Notes:
 Switches supplied with (1) 2M1-HDW4 hex nut and (1) 3MNH-WCP-0872 O-Ring
 1 Movable contact and terminal platings: silver over copper alloy
 2 Movable contact and terminal platings: gold over nickel over copper alloy
 3 Terminal platings: gold over nickel over copper alloy
 4 Terminal platings: tin over copper alloy
 5 Terminal contact platings: gold over nickel alloy
 6 Terminal contact platings: silver over nickel alloy
 7 Tin option not available with M1 & M3 terminations.

*Manufacturer reserves the right to change product specification without prior notice.

2MS - WSP 1 - T1 - B4 - M1 G E

1 Series 2 Poles 3 Circuit 4 Actuator Style 5 Bushing 6 Termination 7 Contacts 8 Seal

1 SERIES

2MS Sealed Miniature Toggle Switch

2 POLES

WSP Single pole - uses terminals 1, 2 & 3
WDP Double pole - uses terminals 1, 2, 3, 4, 5 & 6
W3P Three pole - uses terminals 1, 2, 3, 4, 5, 6, 7, 8 & 9

3 CIRCUIT

() - momentary

| Position: | 1 | 2 | 3 |
|-----------|---------------|---------------------|---------------|
| | 2-3, 5-6, 8-9 | Connected Terminals | 2-1, 5-4, 8-7 |
| 1 | ON | NONE | ON |
| 2 | ON | NONE | (ON) |
| 3 | ON | OFF | ON |
| 4 | (ON) | OFF | (ON) |
| 5 | ON | OFF | (ON) |

4 ACTUATOR STYLE

T1 Round Bat **T9** Long Black Plastic .492" length
T2 Round Short Bat **P1** Plastic Anti-Static .496" length
P2 Plastic Anti-Static .299" length



5 BUSHING

B1 Threaded, Keyway **B4** Unthreaded, Short, Keyway, Flat

6 TERMINATION

| | | | |
|------------------------|-------------------------------------|-------------|------------------------------------|
| M1 ⁴ | Solder Lug | VS21 | Vertical, Snap-In, .460" [11.70mm] |
| M2 | PCB | VS3 | Vertical, .630" [16mm] |
| M3 | Quick Connect | VS31 | Vertical, Snap-In, .630" [16mm] |
| M51 | Wire Wrap, .750" [19.05mm] | U2 | Vertical, .551" [14mm] - only 3PDT |
| M52 | Wire Wrap, .964" [24.48mm] | VS4 | Vertical, .461" [11.70mm] |
| M53 | Wire Wrap, .425" [10.80mm] | VS41 | Vertical, Snap-In, .461" [11.70mm] |
| M54 | Wire Wrap, 1.062" [25.97mm] | U4 | Vertical, .551" [14mm] - only 3PDT |
| M6 | Right Angle, PC Thru-Hole | VS5 | Vertical, .630" [16mm] |
| M61 | Right Angle, Snap-In | VS51 | Vertical, Snap-In, .630" [16mm] |
| M7 | Vertical, Right Angle, PC Thru-Hole | | |
| M71 | Vertical, Right Angle, Snap-In | | |
| VS2 | Vertical, .461" [11.70mm] | | |

7 CONTACTS / TERMINALS

| | Contact Material | Terminal Plating | Rating | Approvals |
|----------|---------------------|--------------------|-------------------------------|---|
| G | silver ¹ | gold over silver | 5A 125VAC or 28VDC, 2A 250VAC | e ²  us, IP67 |
| K | gold ² | tin ^{3,4} | 0.4VA max 20V max (AC/DC) | IP67 |
| P | silver ¹ | tin ^{3,4} | 5A 125VAC or 28VDC, 2A 250VAC | e ²  us, IP67 |
| R | gold ² | gold ² | 0.4VA max 20V max (AC/DC) | IP67 |

8 EPOXY SEAL

E Epoxy Seal **0** without Epoxy Seal

Notes:

B1 Bushing switches supplied with (2) 2M1-HDW2 nuts, (1) 2M1-HDW11 washer and (1) 2M1-HDW15 locking ring. See page 76-77.

- Movable contact & terminal platings: silver over copper alloy
- Movable contact & terminal platings: gold over nickel over copper alloy
- Terminal platings: tin over nickel over copper alloy
- Tin option not available with M1 terminal

2M1 - SP 1 - T1 - B1 - M1 Q E

1 Series 2 Poles 3 Circuit 4 Actuator Style 5 Bushing 6 Termination 7 Contacts 8 Seal

1 SERIES

2M1 Miniature Toggle Switch

2 POLES

SP Single pole - uses terminals 1, 2 & 3
DP Double pole - uses terminals 1, 2, 3, 4, 5 & 6
3P Three pole - uses terminals 1, 2, 3, 4, 5, 6, 7, 8 & 9
4P Three pole - uses terminals 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11 & 12

3 CIRCUIT

() - momentary

| Position: | 1 | 2 | 3 |
|-----------|----------------------|---------------------|----------------------|
| | 2-3, 5-6, 8-9, 11-12 | Connected Terminals | 2-1, 5-4, 8-7, 11-10 |
| 1 | ON | NONE | ON |
| 2 | ON | NONE | (ON) |
| 3 | ON | OFF | ON |
| 4 | (ON) | OFF | (ON) |
| 5 | ON | OFF | (ON) |
| 6* | ON | ON | ON |
| 7* | (ON) | ON | (ON) |
| 8* | ON | ON | (ON) |

*Available with DP and 4P switches only. Center position connects 2-3, 5-4, 8-9, 11-10

4 ACTUATOR STYLE

T1 Round Bat **T7** Large Bat (B0 bushing)
T2 Round Short Bat **T8** X-Large Bat (B0 bushing)
T3 Paddle **T9** Black Plastic
T4 Medium Paddle **T0** Rectangular
T5 Long Paddle **TA** Locking Lever
T6 Flat (B1,B2,B5,BA,BB,BE) **TI** Locking Lever
TL Locking Lever







5 BUSHING

B1 Threaded Standard, keyway **B8** Metric
B2 Non-Threaded Standard, keyway **B9** Splashproof
B3 Threaded Short, keyway **B0** 15/32" Threaded (Standard for T7 & T8 actuator styles)
B4 Non-Threaded Short, keyway **BA** Threaded for T6
B5 High Torque, 7.5mm, flat **BB** Non-Threaded for T6
B6 High Torque, 8.0mm, keyway **BE** Threaded Hi Torque for T6
B7 Long threaded **BL** Threaded, Locking

6 TERMINATION

| | | | |
|------------------------|-------------------------------------|-------------|------------------------------------|
| M1 ⁴ | Solder Lug | M71 | Vertical, Right Angle, Snap-In |
| M2 | PCB | VS2 | Vertical, .461" [11.70mm] |
| M3 | Quick Connect | VS21 | Vertical, Snap-In, .461" [11.70mm] |
| M51 | Wire Wrap, .750" [19.05mm] | VS3 | Vertical, .630" [16mm] |
| M52 | Wire Wrap, .964" [24.48mm] | VS31 | Vertical, Snap-In, .630" [16mm] |
| M53 | Wire Wrap, .425" [10.80mm] | VS4 | Vertical, .461" [11.70mm] |
| M54 | Wire Wrap, 1.062" [25.97mm] | VS41 | Vertical, Snap-In, .461" [11.70mm] |
| M6 | Right Angle, PC Thru-Hole | VS5 | Vertical, .630" [16mm] |
| M61 | Right Angle, Snap-In | VS51 | Vertical, Snap-In, .630" [16mm] |
| M7 | Vertical, Right Angle, PC Thru-Hole | | |

7 CONTACTS / TERMINALS

| | Contact Material | Terminal Plating | Rating | Approvals |
|----------|---------------------|---------------------|-------------------------------|--|
| G | silver ¹ | gold over silver | 5A 125VAC or 28VDC, 2A 250VAC |   IP67 |
| K | gold ² | tin ^{3,4} | 0.4VA max 20V max (AC/DC) | N/A |
| P | silver ¹ | tin ^{3,4} | 5A 125VAC or 28VDC, 2A 250VAC |   IP67 |
| Q | silver ¹ | silver ¹ | 5A 125VAC or 28VDC, 2A 250VAC |   IP67 |
| R | gold ² | gold ² | 0.4VA max 20V max (AC/DC) | N/A |

8 EPOXY SEAL

E Epoxy Seal **0** without Epoxy Seal

Notes:


B1 Bushing switches supplied with (2) 2M1-HDW2 nuts, (1) 2M1-HDW11 washer and (1) 2M1-HDW15 locking ring.

- Movable contact & terminal platings: silver over copper alloy
- Movable contact & terminal platings: gold over nickel over copper alloy
- Terminal platings: tin over nickel over copper alloy
- Tin option not available with M1 terminal

2M-Series Accessories

To order accessories assembled on a switch, specify the switch number followed by the accessory part number and the word "assembled". Ex: 2M1-SP1-T1-B1-M1QE-T12 ASSEMBLED. To order accessories in bulk, specify the Series, followed by the accessory. Ex: 2M1-T12. See page 76 for dimensional specifications.

Optional Toggle Cap




1 SERIES
2M1 Fits 2M1H, 2MS or 2M1

2 TOGGLE CAP SIZE
T1 10.6 mm **T2** 7.6 mm

3 CAP COLOR

| | |
|----------------|-----------------|
| 1 White | 5 Yellow |
| 2 Black | 6 Green |
| 3 Red | 7 Blue |


Optional Dress and Knurled Nuts



1 SERIES
2M1 Fits 2M1H, 2MS or 2M1


2 NUT
HDW3 Dress nut for 1/4" bushing
HDW5 Knurled nut for 15/32" bushing (2M1-Series only)

Optional Rubber Seals



1 SERIES
2M1 Fits 2M1H, 2MS or 2M1

2 RUBBER BOOT SEAL
E1A 1/4 - 40" UNS bushing (Not available for B0 bushing option)
K1 Metric M6 bushing (B8 bushing only)
YE1D 15/32 - 32" UNS bushing (TJ, TK and B0 bushings only)
YE1E 15/32 - 32" UNS bushing 1/2 boot (T7, T8, TJ, TK and B0 bushings only)




1 SERIES
3MNH Fits 3MNH or 2M1H


2 RUBBER O-RING
WCP-0872 For 15/32 bushing option

2M1H-Series Dimensional Specifications: in. [mm]


Single Pole



Double Pole




Actuator Options



| OPTION CODE | DIM. "A" |
|-------------|--------------|
| TJ | .709 [18.00] |
| TK | .512 [13.00] |


Bushing Options & Mounting




| OPTION CODE | DIM. "A" |
|-------------|--------------|
| BJ | .429 [10.90] |
| BK | .386 [9.80] |

Termination Options


M1 Standard Solder Lug




M2 PC Thru-Hole



M3 Quick Connect




M5 Wire Wrap




| OPTION CODE | DIM. "A" |
|-------------|---------------|
| M5-1 | .750 [19.05] |
| M5-2 | .964 [24.48] |
| M5-3 | .425 [10.80] |
| M5-4 | 1.062 [26.97] |

2MS-Series Dimensional Specifications: in. [mm]


Single Pole



Double Pole




Three Pole




Actuator Options


T1



T2




T9 with Plastic Cap





| NO. | COLOR |
|-----|-------------|
| 1 | White |
| 2 | Black(std.) |
| 3 | Red |
| 4 | Orange |
| 5 | Yellow |
| 6 | Green |
| 7 | Blue |
| 8 | Brown |
| 9 | Gray |

P1 Plastic Toggle



P2 Plastic Toggle




* Shown with B4 bushing. Subtract .075" (1.90 mm) from actuator height for B1 bushing.


2MS-Series Dimensional Specifications: in. [mm]

Bushing Options

B1




B4




Termination Options


M1 Standard Solder Lug




M2 PC Thru-Hole



M3 Quick Connect






M5 Wire Wrap




| OPTION CODE | DIM.'A' |
|-------------|---------------|
| M5-1 | .750 [19.05] |
| M5-2 | .964 [24.48] |
| M5-3 | .425 [10.80] |
| M5-4 | 1.062 [26.97] |




M6 Single Pole




P.C.MOUNTING






M6 Double Pole




P.C.MOUNTING






M6 Three Pole




P.C.MOUNTING



M7 Single Pole






P.C.MOUNTING




2MS-Series Dimensional Specifications: in. [mm]

Termination Options




M7 Double Pole




P.C.MOUNTING





M7 Three Pole



P.C.MOUNTING




VS2-VS3 Single Pole





| OPTION CODE | DIM.'A' |
|-------------|--------------|
| VS2 | .461 [11.70] |
| VS3 | .630 [16.00] |

P.C.MOUNTING




VS2-VS3 Double Pole





| OPTION CODE | DIM.'A' |
|-------------|--------------|
| VS2 | .461 [11.70] |
| VS3 | .630 [16.00] |

P.C.MOUNTING




U2-VS3 Three Pole



| OPTION CODE | DIM.'A' |
|-------------|--------------|
| U2 | .551 [14.00] |
| VS3 | .630 [16.00] |



P.C.MOUNTING



2MS-Series Dimensional Specifications: in. [mm]


Termination Options

VS4-VS5 Single Pole





| OPTION CODE | DIM.'A' |
|-------------|--------------|
| VS4 | .461 [11.70] |
| VS5 | .630 [16.00] |

P.C.MOUNTING




VS4-VS5 Double Pole





| OPTION CODE | DIM.'A' |
|-------------|--------------|
| VS4 | .461 [11.70] |
| VS5 | .630 [16.00] |

P.C.MOUNTING




U4-VS5 Three Pole




| OPTION CODE | DIM.'A' |
|-------------|--------------|
| U4 | .551 [14.00] |
| VS5 | .630 [16.00] |

P.C.MOUNTING




Snap-In Termination Options


M61




VS21, VS31



M71




VS41, VS51




* PC Mounting for M61, M71, VS21, VS31, VS41, VS51 refer to M6, M7, VS2, VS3, VS4, VS5 respectively.

2M1-Series Dimensional Specifications: in. [mm]




Actuator Options for Panel Rear Mount




* T6 actuator is available with B1, B2, B5, B6, BA, BB & BE bushing. Actuator length shown for T1 – T5, T9 and T10 is with B1 bushing. T7, P7, T8 & P8 does not require a bushing code.

Locking Lever




Bushing Options


B1 Threaded B2 Non-Threaded




B3 Threaded B4 Non-Threaded









B5 High Torque



B6 High Torque






2M1-Series Dimensional Specifications: in. [mm]




2M1-Series Dimensional Specifications: in. [mm]

Termination Options




M6 Three Pole .244 DIA [6.20]




P.C.MOUNTING






M7 Single Pole .244 DIA [6.20]




P.C.MOUNTING






M7 Double Pole .244 DIA [6.20]




P.C.MOUNTING






M7 Three Pole .244 DIA [6.20]




P.C.MOUNTING





M7 Four Pole .244 DIA [6.20]



P.C.MOUNTING




VS2-VS3 Single Pole



| OPTION CODE | DIM. 'A' |
|-------------|--------------|
| VS2 | .461 [11.70] |
| VS3 | .630 [16.00] |



P.C.MOUNTING



2M1-Series Dimensional Specifications: in. [mm]


Termination Options

VS2-VS3 Double Pole





| OPTION CODE | DIM. 'A' |
|-------------|--------------|
| VS2 | .461 [11.70] |
| VS3 | .630 [16.00] |

P.C.MOUNTING




VS4-VS5 Single Pole





| OPTION CODE | DIM. 'A' |
|-------------|--------------|
| VS4 | .461 [11.70] |
| VS5 | .630 [16.00] |

P.C.MOUNTING




VS4-VS5 Double Pole




| OPTION CODE | DIM. 'A' |
|-------------|--------------|
| VS4 | .461 [11.70] |
| VS5 | .630 [16.00] |

P.C.MOUNTING




Snap-In Termination Options


M61 (available with SP & DP)




VS21, VS31



M71 (available with SP & DP)



VS41, VS51



* PC Mounting for M61, M71, VS21, VS31, VS41, VS51 refer to M6, M7, VS2, VS3, VS4, VS5 respectively.

Authorized Sales Representatives and Distributors

Click on a region of the map below to find your local representatives and distributors or visit www.carlingtech.com/findarep.



About Carling

Founded in 1920, Carling Technologies is a leading manufacturer of electrical and electronic switches and assemblies, circuit breakers, electronic controls, power distribution units, and multiplexed power distribution systems. With four ISO registered manufacturing facilities and technical sales offices worldwide, Carling Technologies Sales, Service and Engineering teams do much more than manufacture electrical components, they engineer powerful solutions! To learn more about Carling please visit www.carlingtech.com/company-profile.

To view all of Carling's environmental, quality, health & safety certifications please visit www.carlingtech.com/environmental-certifications

Worldwide Headquarters

Carling Technologies, Inc.
60 Johnson Avenue, Plainville, CT 06062
Phone: 860.793.9281 **Fax:** 860.793.9231
Email: sales@carlingtech.com

Northern Region Sales Office: nrsm@carlingtech.com
Southeast Region Sales Office: sersm@carlingtech.com
Midwest Region Sales Office: mrrsm@carlingtech.com
West Region Sales Office: wrsm@carlingtech.com
Latin America Sales Office: larsm@carlingtech.com

Asia-Pacific Headquarters

Carling Technologies, Asia-Pacific Ltd.,
Suite 1607, 16/F Tower 2, The Gateway,
Harbour City, 25 Canton Road,
Tsimshatsui, Kowloon, Hong Kong
Phone: Int + 852-2737-2277 **Fax:** Int + 852-2736-9332
Email: sales@carlingtech.com.hk

Shenzhen, China: shenzhen@carlingtech.com
Shanghai, China: shanghai@carlingtech.com
Pune, India: india@carlingtech.com
Kaohsiung, Taiwan: taiwan@carlingtech.com
Yokohama, Japan: japan@carlingtech.com

Europe | Middle East | Africa Headquarters

Carling Technologies LTD
4 Airport Business Park, Exeter Airport,
Clyst Honiton, Exeter, Devon, EX5 2UL, UK
Phone: Int + 44 1392.364422 **Fax:** Int + 44 1392.364477
Email: ltd.sales@carlingtech.com

Germany: gmbh@carlingtech.com
France: sas@carlingtech.com



Carling Technologies®

Innovative Designs. Powerful Solutions.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Rocker Switches](#) category:

Click to view products by [Carling](#) manufacturer:

Other Similar products are found below :

[VKD2GHNB-00000-000](#) [VSD2GNNB-00000-000](#) [6-1571986-5](#) [6-1571986-9](#) [7036WWCDBX653+U622](#) [8055K52Z7V](#) [8138K20E6M50](#)
[FMC18A2200002](#) [84206L](#) [84312LX](#) [PREDD4-07F-BB0FW](#) [PREDD5-07F-BB0GW](#) [PRFDD1-16F-BB000](#) [PRFDD3-16F-BB000](#) [1-](#)
[1634201-0](#) [999-16702-001](#) [A101J2ZQ004](#) [A101J4ZQ004](#) [A101J51CB0004](#) [A107J51ZQ0004](#) [A201J1AQ004](#) [A201J1AV2Q004](#)
[A201J3ZB004](#) [A201J50ZQ004](#) [A203J51ZQ0004](#) [A226L11YZQ](#) [A22L11A](#) [A435S1YZQ](#) [H8500XBBBBL-A](#) [H8653VBBG2577W](#)
[HB130CHNWWNAAC](#) [1251.0303](#) [AE205J60V3B004](#) [RH110C2NBB](#) [1352.0107](#) [1363.0201](#) [AML25GBF2AA03GR](#) [1571099-3](#) [1571987-4](#)
[1571987-5](#) [1571989-7](#) [B123J77V7B2](#) [B226J50W4Q22P](#) [B433J37ZQ22M](#) [160212E](#) [1801.1164](#) [1831.1102](#) [1833.3402](#) [1837.1118](#) [1838.8302](#)