H/I-Series TOGGLE SWITCHES

General purpose workhorses with options tailored to meet most any need. Ratings to 17A 125VAC, various actuator, bushing, termination, and circuit choices allow this toggle to easily integrate into a variety of different applications. The H/I-Series is appropriate for usage in low voltage DC applications.









Product Highlights:

- Ratings up to 600VAC
- Available reversing and progressive switch circuits
- Variety of termination options
- Consult factory for large choice of bushing/toggle length combinations

Typical Applications:

- Food Service
- Generator
- Industrial Control
- Office Automation



Dielectric Strength

UL/CSA: 1000V - live to dead metal parts

Electrical Life

50,000 cycles - maintained 25,000 cycles - momentary

Mechanical Life

100,000 cycles

Operating Temperature

32°F to 185°F (0° to 85°C)





Three Posolder lug HK250 HK25A HK25L HL250 HL25A HK25L HL250 HL25A		screw term. HK254 HK255 HK25S HL254 HL25E HM254 HM255 HM255 HM25S	wire leads HK255 HK25F HK25E HL25E HL25F HM255 HM25F HM25T	Off-None-On Off-None-(On) On-None-(Off) On-None-On On-None-(On) On-Off-On On-Off-(On) (On)-Off-(On)	Four Pole solder lug IK250 IK25A IK25L IL250 IL25A IM25A IM25A	.250 tab tab IK251 IK25B IK25M IL251 IL25B IM251 IM25B IM25M	screw term. IK254 IK25E IK25S IL254 IL25E IM254 IM25E IM25S	wire leads IK255 IK25F IK25T IL255 IL25F IM255 IM25F IM25T
--------------------------------------------------------------------	--	-------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------

2 ACTUATOR	STYLE 1			
	unsealed	sealed	toggle length 0.687	bushing length
BAT	73	78	0.687	0.465
_	E3	E8	2.000	0.465
PADDLE ³	NBL3	NBL8	0.687	0.465

- Additional actuator options available. Consult factory for details.

 Consult factory for .187 tab and combination screw/tab/solder lug termination callouts.
- Nylon toggle with black ebanol plated bushing. Indicates momentary function.





*Manufacturer reserves the right to change product specification without prior notice

Authorized Sales Representatives and Distributors

Click on a region of the map below to find your local representatives and distributors or visit www.carlingtech.com/findarep.



About Carling

Founded in 1920, Carling Technologies is a leading manufacturer of electrical and electronic switches and assemblies, circuit breakers, electronic controls, power distribution units, and multiplexed power distribution systems. With four ISO registered manufacturing facilities and technical sales offices worldwide, Carling Technologies Sales, Service and Engineering teams do much more than manufacture electrical components, they engineer powerful solutions! To learn more about Carling please visit www.carlingtech.com/company-profile.

To view all of Carling's environmental, quality, health & safety certifications please visit www.carlingtech.com/environmental-certifications

Worldwide Headquarters

Carling Technologies, Inc. 60 Johnson Avenue, Plainville, CT 06062 **Phone:** 860.793.9281 **Fax:** 860.793.9231

Email: sales@carlingtech.com

Northern Region Sales Office: nrsm@carlingtech.com Southeast Region Sales Office: sersm@carlingtech.com Midwest Region Sales Office: mrsm@carlingtech.com West Region Sales Office: wrsm@carlingtech.com Latin America Sales Office: larsm@carlingtech.com

Asia-Pacific Headquarters

Carling Technologies, Asia-Pacific Ltd., Suite 1607, 16/F Tower 2, The Gateway, Harbour City, 25 Canton Road, Tsimshatsui, Kowloon, Hong Kong

Phone: Int + 852-2737-2277 Fax: Int + 852-2736-9332

Email: sales@carlingtech.com.hk

Shenzhen, China: shenzhen@carlingtech.com **Shanghai, China:** shanghai@carlingtech.com

Pune, India: india@carlingtech.com

Kaohsiung, Taiwan: taiwan@carlingtech.com **Yokohama, Japan:** japan@carlingtech.com

Europe | Middle East | Africa Headquarters

Carling Technologies LTD 4 Airport Business Park, Exeter Airport, Clyst Honiton, Exeter, Devon, EX5 2UL, UK

Phone: Int + 44 1392.364422 **Fax:** Int + 44 1392.364477

Email: ltd.sales@carlingtech.com

Germany: gmbh@carlingtech.com **France:** sas@carlingtech.com



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Hardware category:

Click to view products by Carling manufacturer:

Other Similar products are found below:

893102000 LZZ1A 0098.9234 61-9707.7 61-9771.0 M2PA-5011 635401 6PA104 6PA113 6PA147-E6 6PA148-E6 6PA32 6PA9 700106
700109 700201A56 700303A56 700701264 700C1GRY 700C2GRN 704-6001 704.960.4 704.960.9 704.965.1 704.965.2 704.965.6
704.966.0 7089-3 71M1048 757200264 778000A56 79215938 MHU35 MHU37 825.003.011 825.005.011 825.053.011 825.055.011
826.000.071 827.020.011 827.400.021 835.900.023 MML52C10C MML52E10C MML72EEK MML92HGH MML93K 84211M02CNNS
84211M02LGRS 84211M02LNNX3