

This document was generated on 10/15/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0760465002

Status: Active

Overview: SFP+ and SFP Interconnect Solutions

Description: Small Form-factor Pluggable Plus (SFP+) Stacked 2-by-4 Multi-Port Connector with 2

Inner Lightpipe Ports, EMI Metal Gasket, 160 Circuits, Tin (Sn) Tails

Documents:

<u>3D Model</u> <u>Application Specification AS-76090-001-001 (PDF)</u>
<u>Drawing (PDF)</u> <u>Packaging Specification PK-75450-001-001 (PDF)</u>

Application Specification AS-75310-001-001 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family I/O Connectors

Series <u>76046</u>

Application Module-to-Board Component Type Receptacle Electrical Model Yes

Overview SFP+ and SFP Interconnect Solutions

Product Name SFP Plus Type N/A

UPC 883906494957

Physical

Boot ColorN/ACircuits (Loaded)160Circuits (maximum)160Circuits Detail160

Color - Resin Black, Clear (Blue Tint)

Durability (mating cycles max) 100
Flammability 94V-0
Gender Female
Keying to Mating Part None
Lock to Mating Part Yes

Material - Metal High Performance Alloy (HPA)

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic, Polycarbonate

Net Weight 95.955/g

Number of Rows 2

Orientation Right Angle PC Tail Length 2.07mm PCB Locator Yes **PCB** Retention Yes PCB Thickness - Recommended 1.57mm Packaging Type Tray **Panel Mount** No Pitch - Mating Interface 0.80mm Pitch - Termination Interface 0.80mm Plating min - Mating 0.762µm Plating min - Termination 0.762µm Polarized to Mating Part Yes Polarized to PCB Yes **Ports** 8



Series image - Reference only

EU ELV

Not Relevant

EU RoHS China RoHS Compliant

REACH SVHC
Not Contained Per ED/61/2018 (27 June

Halogen-Free Status

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

76046 Series

Use With

75951-0999 SFP Dust Plug

Surface Mount Compatible (SMC) No

Temperature Range - Operating -40° to +85°C

Termination Interface: Style Through Hole - Compliant Pin

Waterproof / Dustproof No

Electrical

Current - Maximum per Contact0.5AGrounding to PanelNoneShield TypeEMI Gasket

Shielded Yes

Voltage - Maximum 120V AC (RMS)/DC

Solder Process Data

Lead-freeProcess Capability N/A

Material Info

Reference - Drawing Numbers

Application Specification AS-75310-001-001, AS-76090-001-001

Electrical Model Document EE-76090-001
Packaging Specification PK-75450-001-001
S-Parameter Model SP-76090-001

Sales Drawing RSD-76046-0003, SD-76046-0001

This document was generated on 10/15/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

571763P 58098-0628 61-168618-12P D38999/20FJ24PA L/C D38999/20FJ29SB L/C D38999/24FG11SN L/C 72.250.1628.2 72.250.2428.2 74720-0505 76.350.0729.0 76871-1403 FCN-244F080-G/I FCN-260A9920 FCN-268D024-G/2F#10X-R10 PCS-E50FA PCS-XE26LKA PCS-XE26MA+ PCS-XES68MS+ G38A71314B 91-569719-35R 9776-18-6 DX40-50P(55) 1571250010 157-22500-3 MS3476W12-10S L/C 1888020-8 91-569786-35H 91-569786-35M 91-644626-35P 172501-4002 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 FCN-268D008-G/IK 2000314-1 200331-1 2007498-2 PCR-E28LMDAG1+ PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFDT+ G38A71214B HDRA-E68W1LFDTC-SL+ HDR-E14MSG1+ R88A-CNK81S CRT1-ATT02 54182-0605 U90B2054081210