

This document was generated on 09/06/2018 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0761559803</u>		
Status:	Active		and the second se
ACTIVE		r and Cable Assembly System	and the second s
	Impact Backplane Connector and Cable Assembly System Impact 100 Ohm 4 Pair Vertical Backplane Header, Right Guided, Left Endwall, 8		
		ength 4.50mm, Plated Through Hole Dimension 0.46mm,	
	Lead-Free		
Documents:			
<u>3D Model</u>		Application Specification AS-76060-990-001 (PDF)	
Drawing (PDF)		Application Specification AS-76060-9999-001 (PDF)	
Product Specification PS		Packaging Specification PK-70873-757 (PDF)	Series image - Reference only
Product Specification TS	<u>S-76160-0001-001 (PDF)</u>	RoHS Certificate of Compliance (PDF)	
			EU ELV
Agency Certification			Not Reviewed
UL		E29179	
- ·			EU RoHS China RoHS
General			Not Reviewed
Product Family		Backplane Connectors	REACH SVHC
Series		<u>76155</u>	Not Reviewed
Application		Conventional	Halogen-Free
Application Tooling Doc	uments	TM-622018799	Status
Component Type		PCB Header	Not Reviewed
Overview		Impact Backplane Connector and Cable Assembly	Need more information on product
		System	environmental compliance?
Product Name		Impact	environmental compliance :
UPC		883906417673	Email productcompliance@molex.com
010		883388417873	Please visit the <u>Contact Us</u> section for a
Physical			non-product compliance questions.
Circuits (Loaded)		96	non-product compliance questions.
Circuits (maximum)		96	China ROHS Not Reviewed
Color - Resin		Black	ELV Not Reviewed
		200	RoHS Phthalates Not Reviewed
Durability (mating cycles max)			
First Mate / Last Break		No	
Flammability		94V-0	
Guide to Mating Part		Yes	Search Parts in this Series
Keying to Mating Part		None	76155 Series
Material - Metal		High Performance Alloy (HPA)	
Material - Plating Mating		Gold	Motoo With
Material - Plating Termination		Tin	Mates With
Material - Resin		High Temperature Thermoplastic	76160 Impact 100 Ohm Daughtercard
Net Weight		5.662/g	
Number of Columns		8	
Number of Pairs		4	
Number of Rows		12	
Orientation		Vertical	
PC Tail Length		1.40mm	
PCB Locator		No	
PCB Retention		Yes	
	mandad		
PCB Thickness - Recon	intended	1.00mm	
Packaging Type		Tray	
Pitch - Mating Interface		1.90mm	
Pitch - Termination Inter	face	1.90mm	
Plating min - Mating		0.762µm	
Polarized to PCB		Yes	
Stackable		No	
Temperature Range - O	perating	-55° to +85°C	
Termination Interface: S		Through Hole - Compliant Pin	

Electrical

Current - Maximum per Contact Data Rate Impedance Shield Type Shielded Voltage - Maximum

Material Info

Reference - Drawing Numbers Application Specification Packaging Specification Product Specification Sales Drawing Symbol/Footprint Data 0.75A 25.0 Gbps 100Ω N/A No 30V AC (RMS)/DC

AS-76060-990-001, AS-76060-9999-001 PK-70873-757 PS-76060-999-001, TS-76160-0001-001 SD-76155-003-001 SYM-76155-9803

This document was generated on 09/06/2018 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

2332816-1 89006-1137LF 650827-1 65762-001LF 73474-201LF 74040-1346 74075-0267 1410191-1 1410337-1 1410368-3 1410964-2 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 2187462-1 2226278-6 KA81-07 91290-101LF 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 2226279-2 22354-8 437-5040-000 5-1393565-0 532449-3 532803-2 34745-0001 0736440217 1-1393708-5 72388-0021LF 73774-1000 532939-1 5-531355-3 5532901-3 85838-180LF HM1S43TRR460H6PLF 0760205010 1-966831-4 3-1469268-7 77427-121LF