




- Features :
- 2:1 wide input range
- 4:1 wide input range(option)
- 1000VDC I/O isolation
- 3000VDC I/O isolation(option)
- Built-in EMI filter
- Protections: Short circuit / Overload
- Cooling by free air convection
- Six-sided shield metal case
- 100% burn-in test
- Low cost / High reliability
- Approvals: FCC / CE
- 2 years warranty



SPECIFICATION

ORDER NO.	DKE10A-05	DKE10B-05	DKE10C-05	DKE10A-12	DKE10B-12	DKE10C-12	DKE10A-15	DKE10B-15	DKE10C-15	DKE10A-24	DKE10B-24	DKE10C-24	
OUTPUT	DC VOLTAGE			±12V			±15V			±24V			
	CURRENT RANGE			±42 ~ ±420mA			±33.3 ~ ±333mA			±21 ~ ±210mA			
	RATED POWER												10W
	RIPPLE & NOISE (max.) Note.2			60mVp-p			60mVp-p			80mVp-p			
	LINE REGULATION Note.3												±0.3%
	LOAD REGULATION Note.4												±0.5%
	VOLTAGE ACCURACY												±2.0%
	SWITCHING FREQUENCY												250KHz min.
INPUT	VOLTAGE RANGE												A: 9 ~ 18VDC B: 18 ~ 36VDC C: 36 ~ 72VDC
	EFFICIENCY (Typ.)												78% 81% 82% 80% 80% 83% 80% 80% 82% 82% 81% 85%
	DC CURRENT		Full load										A: 1100mA B: 530mA C: 270mA
			No load										A: 30mA B: 16mA C: 8mA
	FILTER												Pi network
PROTECTION												Fuse recommended	
PROTECTION (Note. 5)	OVER CURRENT												160% ~ 250% rated output power Protection type : Hiccup mode, recovers automatically after fault condition is removed
	SHORT CIRCUIT												All output equipped with short circuit Protection type : Hiccup mode, recovers automatically after fault condition is removed
ENVIRONMENT	WORKING TEMP.												-25 ~ +71°C (Refer to output load derating curve)
	WORKING HUMIDITY												20% ~ 90% RH non-condensing
	STORAGE TEMP., HUMIDITY												-25 ~ +105°C, 10 ~ 95% RH
	TEMP. COEFFICIENT												±0.03% / °C (0 ~ 50°C)
	VIBRATION												10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes
SAFETY & EMC	WITHSTAND VOLTAGE												I/P-O/P:1KVDC
	ISOLATION RESISTANCE												I/P-O/P: 100M Ohms / 500VDC / 25°C / 70% RH
	EMC EMISSION												Compliance to EN55022 Class B, FCC part 15 Class B
	EMC IMMUNITY												Compliance to EN61000-4-2,3,4,5,6,8, light industry level, criteria A
OTHERS	MTBF												500Khrs min. MIL-HDBK-217F(25°C)
	DIMENSION												50.8*25.4*11.2mm or 2**1**0.44" inch (L*W*H)
	WEIGHT												32g


Mechanical Specification



Pin Configuration

Pin No.	Output
1	+Vin
2	-Vin
3	+Vout
4	COM
5	-Vout

Derating Curve



NOTE

1. All parameters are specified at normal input, rated load, 25°C 70% RH ambient.
2. Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor.
3. Line regulation is measured from low line to high line at rated load.
4. Load regulation is measured from 10% to 100% rated load.
5. Please prevent the converter from operating in overload or short circuit condition for more than 30 seconds.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Isolated DC/DC Converters](#) category:

Click to view products by [Mean Well](#) manufacturer:

Other Similar products are found below :

[ESM6D044440C05AAQ](#) [FMD15.24G](#) [PSL486-7LR](#) [PSR152.5-7IR](#) [Q48T30020-NBB0](#) [AVO240-48S12B-6L](#) [AVO250-48S28B-6L](#) [NAN-0505](#) [HW-L16D](#) [JAHW100Y1](#) [217-1617-001](#) [22827](#) [SPB05C-12](#) [SQ24S15033-PS0S](#) [18952](#) [19-130041](#) [CE-1003](#) [CE-1004](#) [GQ2541-7R](#) [PSE1000DCDC-12V](#) [RDS180245](#) [MAU228](#) [419-2065-201](#) [449-2075-101](#) [J80-0041NL](#) [V300C24C150BG](#) [419-2062-200](#) [419-2063-401](#) [419-2067-101](#) [419-2067-501](#) [419-2068-001](#) [DCG40-5G](#) [DFC15U48D15](#) [449-2067-000](#) [XGS-0512](#) [XGS-1205](#) [XGS-1212](#) [XGS-2412](#) [XGS-2415](#) [XKS-1215](#) [033456](#) [NCT1000N040R050B](#) [SPB05B-15](#) [SPB05C-15](#) [SSQE48T25025-NAA0G](#) [L-DA20](#) [HP3040-9RG](#) [HP1001-9RTG](#) [XKS-2415](#) [XKS-2412](#)